

SECTION BEFORE COMPRESSION



SECTION AFTER COMPRESSION
4-POINT SHALLOW INDENTATION CRIMPING SYSTEM



SECTION AFTER COMPRESSION WITH
BICC/BURNDY CIRCUMFERENTIAL DIE CRIMPING SYSTEM

NOTE :


1. NOT FOR MANUFACTURING PURPOSE.
2. BICC/BURNDY CIRCUMFERENTIAL JOINTS ONLY AVAILABLE TILL DECEMBER 2002.

ITEM		:- MIDSPAN JOINT		
MATERIAL SPECIFICATION		:-		
CORROSION SPECIFICATION		:-		
STANDARD SPECIFICATION		:-		
ESKOM SPECIFICATION		:- SCSSCAAG5		
TEST & CERTIFICATION REQUIREMENTS :- TYPE TEST AND PRODUCTION SAMPLE TEST				
INSPECTION	Yes	No	ESKOM RELEASE NOTE	
			Yes No	
IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS				
7	LOGO CHANGED AS PER CORPORATE I.D.	D.D.N.	P.VERMAAK J.SCHOLTZ 15.06.04	
6	SAP NUMBER CORRECTED FOR HARE/OAK C/C	P.A.V.	G.STANFORD H.GELDENHUYS 03.11.99	
5	OAK CIRCUMFERENTIAL CRIMP ADDED	P.A.V.	G.STANFORD P. CROWDY 03.11.99	
REV	REVISION DESCRIPTION	BY	CHKD AUTH DATE REF. DWGS	
AUTH:	P. CROWDY	DATE:	17.07.1995	
CHKD:	J. SWAN	DATE:	17.07.1995	
DRAWN:	P.A. VERMAAK	DATE:	23.05.1995	
SCALE		NTS		
CAD REF:		SERIES 3000		
FILE No:		3073		
		SAP No:		
		SET	SHEET	REV
D-DT-3073		5	1	7

SPEC SHEET

SAP MATERIAL No.:	0165606
SHORT DESCRIPTION:	JOINT,M/SPAN MINK/PINE I/C D3073
TECH. DESCRIPTION:	
<p>MIDSPAN TENSION JOINT * COMPRESSION INDENT CRIMP * TWO PART * TUBULAR * FOR MINK CONDUCTOR 10.98mm DIA. OR PINE CONDUCTOR 10.83mm DIA. * ACCOMMODATES CONDUCTOR RANGE 7.4-12.0mm DIA. * CONDUCTOR COLOUR CODE : RED * INCLUDES TUBULAR JOINT FOR STEEL CORE FILLED WITH JOINTING COMPOUND AND TUBULAR ALUMINIUM JOINT * INDIVIDUALLY PACKED IN SEALED PLASTIC BAG * FOR USE WITH HYDRAULIC 4-POINT SHALLOW INDENTATION CRIMPING TOOL * ESKOM DRAWING No. D-DT-3073 *</p>	

SAP MATERIAL No.:	0165848
SHORT DESCRIPTION:	JOINT,M/SPAN HARE/OAK I/C D3073
TECH. DESCRIPTION:	
<p>MIDSPAN TENSION JOINT * COMPRESSION INDENT CRIMP * TWO PART * TUBULAR * FOR HARE CONDUCTOR 14.16mm DIA. OR OAK CONDUCTOR 13.95mm DIA. * ACCOMMODATES CONDUCTOR RANGE 9.1-15.0mm DIA. * CONDUCTOR COLOUR CODE : BROWN * INCLUDES TUBULAR JOINT FOR STEEL CORE FILLED WITH JOINTING COMPOUND AND TUBULAR ALUMINIUM JOINT * INDIVIDUALLY PACKED IN SEALED PLASTIC BAG * FOR USE WITH HYDRAULIC 4-POINT SHALLOW INDENTATION CRIMPING TOOL * ESKOM DRAWING No. D-DT-3073 *</p>	

7	LOGO CHANGED AS PER CORPORATE I.D.	D.D.N.	P.VERMAAK	J.SCHOLTZ	15.06.04	
6	SAP NUMBER CORRECTED FOR HARE/OAK C/C	P.A.V.	G.STANFORD	H.GELDENHUYS	03.11.99	
5	OAK CIRCUMFERENTIAL CRIMP ADDED	P.A.V.	G.STANFORD	P. CROWDY	03.11.99	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS
AUTH:	P. CROWDY	DATE:	17.07.1995	 D-DT-3073	SAP No:	
CHKD:	J. SWAN	DATE:	17.07.1995		0165606	
DRAWN:	P.A. VERMAAK	DATE:	23.05.1995		0165848	
			SCALE NTS		SET	SHEET
			CAD REF: SERIES 3000		5	3
			FILE No: 3073			REV
						7