CONDUCTOR CONDUCTOR										
SAP MATERIAL No.:		0401307 CLAMP,STRAIN:3B ST/WIRE;70 KN;16-5 MM								
SHORT DESCRIPTION: TECH. DESCRIPTION:	CLAMP,STR	AIN:3B ST	/WIRE;70 KN;	16-5 MM						
CLAMP, STRAIN: TYPE: 3B ST/WIRE; CONDUCTOR: 16-5 MM; CAPACITY: 70 KN; TENSION LIP NOT TO BE GROUND BUT CAST AS PER DRAWING; ALL MOULDING LINES TO BE REMOVED ON INSIDE OF CLAMP; CLEVIS DESIGNATION 16L; SUPPLIED COMPLETE WITH: 1 X M16 X 75MM CLEVIS BOLT ASSEMBLY (D-DT-7043), 3 X GALVANISED STEEL 12MM U-BOLTS WITH 6 X SPRING WASHERS (D-DT-3014), 6 X M12 HEXAGON NUT (D-DT-3173), AND MALLEABLE IRON KEEPER; USED FOR 3X3.35 (D-DT-3124) AND 3X4.00, 7X3.35 AND 19X2.65 (D-DT-7036) STEEL SHIELD WIRE; ESKOM DRAWING No. D-DT-7022 *										
ITEM		PISTOL 3								
MATERIAL SPECIFICATION			92, BS EN 15	62						
CORROSION SPECIFICATION	:- SANS 12	21	- ,							
STANDARD SPECIFICATION		1284, SAN	S 60471							
ESKOM SPECIFICATION :- DSP 34-1667 TEST & CERTIFICATION REQUIREMENTS :- TYPE TEST ACCORDING TO SANS 61284 AND DSP 34-1667.										
INSPECTION Ye	-		ESKOM	RELEASE			No			
IDENTIFICATION :- INDELIBLE MANUFACTURERS TRADEMARK, PART No. AND FAILING LOAD ON ALL ITEMS. BOLTS TORQUED TO 45NM										
CASTING LINES TO BE REMOVED AI VARIOUS SAP NUMBERS AND DESC ACCORDING TO PILOG	RIPTION CHANGED	P.A.T.	M. SHUTER	B. HILL	il 1	6.01.2013				
NO. OFF SPRING WASHERS AND HE BOLT TORQUE REMOVED AND RAN 0243440		S. MASHABA				20.04.2010				
12 SAP 0243439 REMOVED AND RANGE REV REVISION DESC		P.A.T. BY	S. MASHABA CHKD	B.BRANFIEL AUTH		8.01.2010 DATE	REF. DWGS			
AUTH: P. CROWDY DATE	:: 07.03.1998 SC	CALE TS		kom	SAP N	o:	'			
CHKD: D. PILLAY DATE		AD REF: ERIES 7000	-		SET	SHEET	REV			
DRAWN: GC P.A. VERMAAK DATE	. 00.11.1337	LE No: 022	D-DT-	7022	2	1	14			

SPEC SHEET												
	TERIAL No.:		0401310									
	DESCRIPTION:	C	CLAMP,STRAIN:3B;70 KN;15-6 MM									
TECH. DESCRIPTION: CLAMP, STRAIN: TYPE: 3B; CONDUCTOR: 15-6 MM; CAPACITY: 70 KN; TENSION LIP NOT TO BE GROUND BUT CAST AS PER DRAWING; ALL MOULDING LINES TO BE REMOVED ON INSIDE OF CLAMP; CLEVIS DESIGNATION 16L; SUPPLIED COMPLETE WITH: 1 X M16 X 65MM CLEVIS BOLT ASSEMBLY (D-DT-7043), 3 X GALVANISED STEEL 12MM U-BOLTS WITH 6 X SPRING WASHERS (D-DT-3014), 6 X M12 HEXAGON NUT (D-DT-3173) AND DIE CAST ALUMINIUM KEEPER; USED FOR SQURRELL, FOX, MINK AND HARE CONDUCTOR; ALL ALUMINIUM TO BE GRAVITY DIE CAST PROCESSED FROM LM25 ALUMINIUM MATERIAL AND HEAT TREATED TO OBTAIN THE REQUIRED MECHANICAL PROPERTIES; ESKOM DRAWING No. D-DT-7022 *												
SAP MA	TERIAL No.:	02	243440									
	DESCRIPTION:	С	LAMP,STR	AIN:3	B ST;70 k	ΚN	I;30-18 MM					
TECH. DESCRIPTION: CLAMP, STRAIN: TYPE: 3B ST; CONDUCTOR: 30-18 MM; CAPACITY: 70 KN; TENSION LIP NOT TO BE GROUND BUT CAST AS PER DRAWING: ALL MOULDING LINES TO BE REMOVED ON INSIDE OF CLAMP; CLEVIS DESIGNATION 16L; SUPPLIED COMPLETE WITH 1 X M16 X 65 MM CLEVIS BOLT ASSEMBLY (D-DT-7043), 3 X GALVANISED STEEL 12 MM U-BOLTS WITH 6 X SPRING WASHERS (D-DT-3014), 6 X M12 HEXAGON NUT (D-DT-3173) AND DIE CAST ALUMINIUM KEEPER; USED FOR CHICADEE AND KINGBIRD CONDUCTOR TO BE GRAVITY DIE CAST PROCESSED FROM LM25 ALUMINIUM MATERIAL AND HEAT TREATED TO OBTAIN THE REQUIRED MECHANICAL PROPERTIES; ESKOM DRAWING No. D-DT-7022 *												
14 VAI AC	STING LINES TO BE REMO RIOUS SAP NUMBERS AN CORDING TO PILOG	ID DESCRIP	TION CHANGED		P.A.T.	м.	SHUTER	B. HILL	I	16.0	1.2013	
NO. OFF SPRING WASHERS AND HEX. BOLTS CORRECTED BOLT TORQUE REMOVED AND RANGE TAKING CHANGED ON 0243440				P.A.T.		MASHABA	L.CHRISTIAA	NS	20.0	4.2010		
12 SAP 0243439 REMOVED AND RANGE TAKING CHANGED   REV REVISION DESCRIPTION			P.A.T. BY	S.	MASHABA CHKD	B.BRANFIEL AUTH			01.2010 DATE	REF. DWGS		
AUTH:	P. CROWDY	DATE:	07.03.1998	SCA NTS					SAP 040	No:		
CHKD:	D. PILLAY	DATE:	07.03.1998	CAD REF: SERIES 7000			Eskom		040 024 SE	344		REV
DRAWN:	GC P.A. VERMAAK	DATE:	08.11.1997 06.03.1998	FILE 7022	No:		D-DT-	7022	2		2	14