



SAP MATERIAL No.: **0402629**
 SHORT DESCRIPTION: CLAMP,SUSP PIVOTED 25.0-40.0 D7009

TECH. DESCRIPTION:

PIVOTED SUSPENSION CLAMP * MALLEABLE CAST IRON *
 HOT DIPPED GALVANISED OR HEAT TREATED DIE CAST ALUMINIUM ALLOY *
 CLEVIS DIMENSIONS TO SANS 60471 DESIGNATION 16L *
 NOMINAL COUPLING LENGTH 100mm *
 SUPPLIED COMPLETE:
 1 x M16 CLEVIS BOLT ASSEMBLY (D-DT-7043),
 4 x M12 SPRING WASHERS (D-DT-3014), 4 x M12 HEX. BOLTS (D-DT-3173) *
 2 x M12 U-BOLTS (SUITABLE LENGTH FOR ALL CONDUCTOR RANGES)
 CONDUCTOR RANGE :- (INCLUDING PREFORMED ARMOR RODS)
 25.0mm TO 40mm DIAMETER *
CAN BE USED WITH WOLF, CHICADEE, BEAR, KINGBIRD, CENTIPEDE *
 MINIMUM FAILING LOAD 70kN *
 ESKOM DRAWING No. D-DT-7009 *

ITEM	:-	CLAMP,SUSP PIVOTED 25.0-40.0
MATERIAL SPECIFICATION	:-	SANS 991, SANS 992, BS EN 1562
CORROSION SPECIFICATION	:-	SANS 121
STANDARD SPECIFICATION	:-	SANS 61284, SANS 60471
ESKOM SPECIFICATION	:-	TRMSCAAH2, DSP 34-1667
TEST & CERTIFICATION REQUIREMENTS	:-	TYPE TEST ACCORDING TO SANS 61284 AND DSP 34-1667

INSPECTION	Yes	No	ESKOM RELEASE NOTE	Yes	No
------------	-----	----	--------------------	-----	----

IDENTIFICATION:- INDELIBLE MANUFACTURES TRADEMARK & PART No. ON ALL ITEMS

8	TURN REMOVED FROM TECH. DESCRIPTION	P.A.T.	B. HILL	B. HILL	01.07.2015	
7	BULL COND REMOVED FROM USE OF SUSPENSION CLAMP	P.A.T.	S. MASHABA	B.BRANFIELD	20.04.2010	
6	MATERIAL, STD. ESKOM SPECS CHANGED AND DRG. NO.'S ADDED	P.A.T.	S. MASHABA	S. MASHABA	03.08.2009	
REV	REVISION DESCRIPTION	BY	CHKD	AUTH	DATE	REF. DWGS

AUTH:	P. CROWDY	DATE:	26.03.1998	SCALE		SAP No:				
CHKD:	D. PILLAY	DATE:	26.03.1998	NTS		0402629				
DRAWN:	GC P.A. VERMAAK	DATE:	08.11.1997 01.03.1998	CAD REF: SERIES 7000			SET	SHEET	REV	
				FILE No: 7009	D-DT-7009			1	1	8