



NOTES

1. FOR MOUNTING AND LOCATION DETAILS DRAWING TD-R-RS-200
2. STANDARD SIZES OF REFERENCE MARKER BOARD TO BE 420x300x1.4mm THICK PREPAINTED GALVANISED MILD STEEL PLATE.
3. ALL MARKER BOARDS SHALL BE MANUFACTURED USING CLASS 1 WHITE RETROREFLECTIVE MATERIAL ON A BLUE SEMI-MATT BACKGROUND.
4. THE LEGEND SHALL BE DIN 1451 PART 2 STYLE "A" LETTERING AND NUMBERS SO THAT THE TOP LINE IS 77mm HIGH AND THE BOTTOM LINE IS 112mm HIGH.
5. THE LEGEND SHALL BE ARRANGED AS FOLLOWS -
TOP LINE -
"N" FOR NATIONAL ROUTE, AND
THE APPROPRIATE ROUTE NUMBER e.g. N2 AND
THE APPROPRIATE SECTION NUMBER e.g. N2-16 (TYPE 1); OR
THE APPROPRIATE SECTION NUMBER AND AN "X" SUFFIX FOR
A TEMPORARILY PROCLAIMED NATIONAL ROUTE,
e.g. N3-9X (TYPE 2)

BOTTOM LINE -
KILOMETRE DISTANCE FROM THE START OF A SECTION TO ONE DECIMAL,
FOR EVERY 0,2km
AND
E FOR AN EASTBOUND CARRIAGEWAY
W FOR A WESTBOUND CARRIAGEWAY
N FOR A NORTHBOUND CARRIAGEWAY
S FOR A SOUTHBOUND CARRIAGEWAY.

[illegible]