

SCOPE OF WORK FOR V-BELTS

1 Overview and purpose of the *goods* and *services*

The supply and delivery of various V-Belts at Grootvlei power station for as an when required for a period of 5 years. They are used on various pumps to transmits force from one driving component to the driven component. Brand FENNER is required on these V-Belts.

2 Specification and description of the *goods*

Detailed specifications of the goods are as follows:

Material	Detailed description	Unit of Measure
0028500	BELT, V: TOP WIDTH: 13 MM; THICKNESS: 10 MM; SUPPL P/N: 13NSPA1700; 1700MM PITCH CIRCUMFERENCE, PLEASE ENSURE THEY ARE ALL OF THE SAME LOT NUMBER	EA
0028644	BELT, V: PROFILE: 22N; SPC; REFERENCE NUMBER: 6700X20; SUPPL P/N: 6700X20; IN MATCHED SETS OF EIGHT(8); FOR SLURRY ASH PUMPS TYPE 250X200/25MG	EA
0028714	BELT, V: TOP WIDTH: 12.5 MM; THICKNESS: 13 MM; REFERENCE NUMBER: A37 8264; PITCH CIRCUMFERENCE: 985 MM; REFERENCE NO: 30518381	EA
0028719	BELT, V: TYPE: DRIVE; INSIDE CIRCUMFERENCE: 270 MM; OUTSIDE CIRCUMFERENCE: 290 MM; TOP WIDTH: 13 MM; MATERIAL: RUBBER; THICKNESS: 8 MM; PROFILE: 13; REFERENCE NUMBER: 13X920; PITCH CIRCUMFERENCE: 920 MM; REFERENCE NO: A35; SUPPL P/N: 13 X 920	EA
0028723	BELT, V: TOP WIDTH: 10 MM; THICKNESS: 8 MM; SUPPL P/N: 10NSPZ1270; PITCH 1270MM CIRCUMFERENCE	EA
0028724	BELT, V: TOP WIDTH: 10 MM; THICKNESS: 8 MM; SUPPL P/N: 10NSPZ1520; PITCH 1520MM CIRCUMFERENCE	EA
0028725	BELT, V: TOP WIDTH: 10 MM; THICKNESS: 8 MM; SUPPL P/N: 10NSPZ2030; PITCH 2030MM CIRCUMFERENCE	EA
0028726	BELT, V: TOP WIDTH: 16 MM; THICKNESS: 13 MM; SUPPL P/N: 16NSPB1800; PITCH 1800MM CIRCUMFERENCE	EA
0028755	BELT, V: TOP WIDTH: 13 MM; THICKNESS: 8 MM; SUPPL P/N: VB13X8X1860; 1860MM PITCH CIRCUMFERENCE	EA
0028765	BELT, V: TOP WIDTH: 22 MM; THICKNESS: 14 MM; 5010MM PITCH CIRCUMFERENCE	EA

0028766	BELT, V: TOP WIDTH: 22 MM; PROFILE: 22; REFERENCE NUMBER: 22X3710; PITCH CIRCUMFERENCE: 3710 MM; SUPPL P/N: 22X3710	EA
0028776	BELT, V: OUTSIDE CIRCUMFERENCE: 1670 MM; THICKNESS: 17 MM; REFERENCE NUMBER: B64	EA
0028777	BELT, V: TOP WIDTH: 17 MM; PROFILE: 17; REFERENCE NUMBER: 17X1570; PITCH CIRCUMFERENCE: 1570 MM; SUPPL P/N: 17X1570	EA
0028780	BELT, V: TOP WIDTH: 17 MM; PROFILE: 17; SPECIFICATION: BS 4; REFERENCE NUMBER: 17X1410; PITCH CIRCUMFERENCE: 1410 MM; SUPPL P/N: 17X1410	EA
0028784	BELT, V: TOP WIDTH: 22 MM; PROFILE: 22; REFERENCE NUMBER: 22X1630; PITCH CIRCUMFERENCE: 1630 MM; SUPPL P/N: 22X1630	EA
0028786	BELT, V: TOP WIDTH: 16 MM; PROFILE: 16N; SPB; PITCH CIRCUMFERENCE: 4310 MM; REFERENCE NO: NO5V1700; SUPPL P/N: 16X4310	EA
0028787	BELT, V: TOP WIDTH: 13 MM; PROFILE: 13; REFERENCE NUMBER: 13X1990; PITCH CIRCUMFERENCE: 1990 MM; SUPPL P/N: 13X1990	EA
0028813	BELT, V: TOP WIDTH: 17 MM; PROFILE: 17; REFERENCE NUMBER: 17X2530; PITCH CIRCUMFERENCE: 2530 MM; MANUF P/N: 17X2530	EA
0028849	BELT, V: TOP WIDTH: 10 MM; PROFILE: 10N/SPZ; PITCH CIRCUMFERENCE: 630 MM; SUPPL P/N: 10X630	EA
0028991	BELT, V: TYPE: FAN; INSIDE CIRCUMFERENCE: 2.5 M; OUTSIDE CIRCUMFERENCE: 2.5 M; TOP WIDTH: 22 MM; MATERIAL: RUBBER; PROFILE: 22N; SPC; REFERENCE NUMBER: 22NX2500; MANUF P/N: 22NX2500; MATCHED SET OF 6	EA
0029034	BELT, V: TOP WIDTH: 16 MM; PROFILE: 116N/SPB; PITCH CIRCUMFERENCE: 5680 MM; SUPPL P/N: 116NX5680; MATCH SETS OF FOUR EACH; SINGLE	EA
0029035	BELT, V: TOP WIDTH: 17 MM; PITCH CIRCUMFERENCE: 7610 MM; SUPPL P/N: 17X7610	EA
0029036	BELT, V: MANUF P/N: VB20 B1800	EA
0227252	BELT, V: TYPE: DRIVE; INSIDE CIRCUMFERENCE: 2.9 M; OUTSIDE CIRCUMFERENCE: 2.92 M; TOP WIDTH: 21 MM; MATERIAL: RUBBER; THICKNESS: 19.93 MM; SUPPL P/N: SPC 9000; FOR USE ON ASH CRUSHERS; 5 X BELTS PER SET TO BE MATCHED; PITCH 9000 MM CIRCUMFERENCE; HEAT AND OIL RESISTANCE	EA
0227253	BELT, V: TOP WIDTH: 21 MM; SUPPL P/N: SPC 6700; FOR USE ON ASH PUMPS, 8 X BELTS PER SET TO BE MATCHED; PITCH 6700MM CIRCUMFERENCE	EA
0251911	BELT, V: TYPE: ASH PUMPS 2/3 WEDGE; INSIDE CIRCUMFERENCE: 6.705 M; OUTSIDE CIRCUMFERENCE: 6.795 M; TOP WIDTH: 22 MM; THICKNESS: 14 MM; PROFILE: C264; INSIDE DIAMETER: 6.761 M; REFERENCE NO: VB22X 6760X14, UNK; SUPPL P/N: C264 PIX	EA

0254947	BELT, V: TYPE: WEDGE; INSIDE CIRCUMFERENCE: 9.3 M; OUTSIDE CIRCUMFERENCE: 9.5 M; TOP WIDTH: 22 MM; MATERIAL: RUBBER; SUPPL P/N:SPC9500	EA
0255962	BELT, V: TYPE: WEDGE; OUTSIDE CIRCUMFERENCE: 6860 MM; TOP WIDTH: 22 MM; MATERIAL: RUBBER; THICKNESS: 14 MM; REFERENCE NO:VB22X6860; SUPPL P/N: C270; REQUIRED FOR USE ON ASH PUMPS 2 AND 3; PIX	EA
0569738	BELT, TOOTHED: TYPE: SYNCHRONOUS; WIDTH: 33 MM; LENGTH: 900 MM; MATERIAL: RUBBER; TEETH: 95; PITCH: 10 MM; FOR USE WITH GEARMOTOR	EA
0606069	BELT, TOOTHED: TYPE: TIMING; WIDTH: 20 MM; LENGTH: 3.2 M; MATERIAL: RUBBER; TEETH: 400; PITCH: 8 MM; SPECIFICATION: HITD 3200-8M-20; THICKNESS: 2 MM; FOR USE ON LIFT EQUIPMENT FOR TRANSMISSION OF LIFT DOORS	EA
0606070	BELT, TOOTHED: TYPE: TIMING; WIDTH: 20 MM; LENGTH: 1.6 M; MATERIAL: RUBBER; TEETH: 200; PITCH: 8 MM; SPECIFICATION: HITD 1600-8M-20; THICKNESS: 2 MM; FOR USE ON LIFT EQUIPMENT FOR TRANSMISSION OF LIFT DOORS	EA
0606097	BELT, TOOTHED: TYPE: TIMING; WIDTH: 20 MM; LENGTH: 1.2 M; MATERIAL: RUBBER; TEETH: 150; PITCH: 8 MM; SPECIFICATION: HITD 1200-8M-20; THICKNESS: 2 MM; FOR USE ON LIFT EQUIPMENT(ON LIFTS) FOR TRANSMISSION OF LIFT DOORS	EA

Compiled by: Gloria Tshikomba

Signature: *gtshikomba*

Date: 15.09.2023