| | Quantity | Rate | Amo |
|--|----------|------|-----|
| SECTION 1 - PRELIMINARIES | | | |
| BILL NO. 1 | | | |
| PRELIMINARIES | | | |
| | | | |
| BUILDING AGREEMENT AND PRELIMINARIES | | | |
| The JBCC Series 2000 Principal Building Agreement (March 2005 edition 4.1) prepared by the Joint Building Contracts Committee shall be the applicable building agreement, amended as hereinafter described together with the associated documentation as prepared by the Joint Building Contracts Committee | | | |
| The JBCC Preliminaries (May 2005 edition) published by the Joint Building Contracts Committee for use with the said JBCC Principal Building Agreement shall be deemed to be incorporated in these bills of quantities | | | |
| The Contractor is deemed to have referred to the abovementioned documents for the full intent and meaning of each clause thereof | | | |
| These clauses are hereinafter referred to by clause number and heading only. Where standard clauses or alternatives are not entirely applicable to this contract such modifications, corrections or supplements as will apply are given under each relevant clause heading and such modifications, corrections or supplements shall take precedence notwithstanding anything contrary contained in the abovementioned documents | | | |
| Where any item is not relevant to this specific contract such item is marked N/A, signifying "not applicable" | | | |
| The Bills of Quantities have been drawn up in accordance with the "Standard System of Measuring Building Work Seventh Edition (Revised 2015)" published by The South African Association of Quantity Surveyors | | | |
| Carried Forward | | R | |
| Section No. 1 Bill No. 1 | | | |
| Preliminaries | | | |
| Diatho Consulting (PTY) LTD | | | |

R

| Brought | Forward |
|---------|---------|
|---------|---------|

The quantities or specifications contained in these bills of quantities are not to be used for the calculation or ordering of materials.

PREAMBLES FOR TRADES

The General Preambles for Trades (2017 edition) as published by The Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said Model Preambles will be entertained

Where Architect's or Engineer's specifications or drawings (where issued) are in conflict with the above Preambles, etc, the Architect's or Engineer's specification and drawings, as the case may be, are to take preference

Where the drawings and Architect's or Engineer's specifications are in conflict, the Contractor is to obtain written clarification from the Principal Agent prior to the closing of tenders

The Contractor's prices for all items throughout these bills of quantities must take account of and include for all of the obligations, requirements and specifications given in the said Model Preambles and in any supplementary preambles

Carried Forward

R

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

| Brought Forward | R | |
|--|---|--|
| PRICING OF PRELIMINARIES | | |
| If option A as set out in clause B10.3.1 hereinafter is to be used for the adjustment of the preliminaries each item priced is to be allocated to one or more of the three categories "F", "V" or "T" as the case may be below such item, where: | | |
| F - An amount which shall not be varied (Fixed) | | |
| V - An amount which shall be varied in proportion to the contract value as compared with the contract sum (Value) | | |
| T - An amount which shall be varied in proportion to the construction period as compared to the initial construction period excluding revisions to the construction period for which the Contractor is not entitled to adjustment of the contract value in terms of the agreement (Time) | | |
| Items not priced in these Preliminaries shall be deemed to be included elsewhere in these Bills of Quantities | | |
| | | |
| Carried Forward Section No. 1 Bill No. 1 Preliminaries | R | |
| Diatho Consulting (PTY) LTD | | |

| Brought Forward | R | |
|--|---|--|
| SECTION A: JBCC PRINCIPAL BUILDING AGREEMENT | | |
| | | |
| DEFINITIONS | | |
| 1.0 Definitions and Interpretation | | |
| 1.0 Clause | | |
| 1.1 Definition of "Commencement Date" is added: | | |
| "COMMENCEMENT DATE" means the date that the agreement, made in terms of the Form of Offer and Acceptance, comes into effect | | |
| Clause 1.1 Definition of "Construction Period" is amended by replacing it with the following: | | |
| "CONSTRUCTION PERIOD" means the period commencing on the commencement date and ending on the date of practical completion | | |
| Clause 1.1 Definition of " Interest " is amended by replacing it with the following: | | |
| " INTEREST " means the interest rates applicable on this contract, whether specifically indicated in the relevant clauses or not, will be in terms of the legislation of the Republic of South Africa, and in particular: | | |
| (a) In respect of interest owed by the employer, the interest rate as determined by the Minister of Justice and Constitutional Development, from time to time, in terms of section 1(2) of the Prescribed Rate of Interest Act, 1975 (Act No. 55 of 1975), will apply; and | | |
| (b) in respect of interest owed to the employer, the interest rate as determined by the Minister of Finance, from time to time, in terms of section 80(1)(b) of the Public Finance Management Act, 1999 (Act No. 1 of 1999), will apply. | | |
| Carried Forward | R | |
| Section No. 1 Bill No. 1 Preliminaries | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

1

| | Brought Forward | | R | |
|---|--|------|---|--|
| | Clause 1.6.4 is amended by replacing it with the following: | | | |
| | No clause | | | |
| | F: V: T: | | | |
| | | ltem | | |
| | OBJECTIVE AND PREPARATION | | | |
| 2 | 2.0 Offer, Acceptance and Performance | | | |
| | F: V: T: | ltem | | |
| 3 | 3.0 Documents | | | |
| | 3.7 is amended by the addition of the following: | | | |
| | The Contractor shall supply and keep a copy of the JBCC Series 2000 Principal Building Agreement and Preliminaries applicable to this contract on the site, to which the Employer, Principal Agent and agents shall have access at all times | | | |
| | F: V: T: | ltem | | |
| 4 | 4.0 Design Responsibility | | | |
| | F: V: T: | ltem | | |
| 5 | 5.0 Employer's Agent | | | |
| | 5.1.2 is amended to include clauses 32.6.3, 34.3 and 34.4 | | | |
| | F: V: T: | ltem | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | R | |
|----|---|------|---|--|
| 6 | 6.0 Site Representative | | | |
| | F: V: T: | | | |
| | | Item | | |
| 7 | 7.0 Compliance with Regulations | | | |
| ' | | | | |
| | Note: The provisions herein include inter alia, compliance with all the requirements set out in the Construction Regulations, 2003 issued under the | | | |
| | Occupational Health and Safety Act, 1993 (Act No 85 of | | | |
| | 1993), and in particular with Regulation 5(1) requiring the compilation of a health and safety plan, as well as | | | |
| | Regulation 6(1) requiring the appointment of a construction supervisor | | | |
| | See also clause C10 of Section C - Specific | | | |
| | Preliminaries | | | |
| | F: V: T: | | | |
| | | Item | | |
| 8 | 8.0 Works Risk | | | |
| | F: V: T: | lt | | |
| | | Item | | |
| 9 | 9.0 Indemnities | | | |
| | F: V: T: | Item | | |
| 10 | | | | |
| 10 | 10.0 WORKS INSURANCES | | | |
| | Clause 10.0 is amended by the addition of the following clauses: | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 | | | |
| | Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

R

Brought Forward

10.5 Damage to the Works

- (a) Without in any way limiting the contractor's obligations in terms of the contract, the contractor shall bear the full risk of damage to and/or destruction of the works by whatever cause during construction of the works and hereby indemnifies and holds harmless the employer against any such damage. The contractor shall take such precautions and security measures and other steps for the protection and security of the works as the contractor may deem necessary
- (b) The **contractor** shall at all times proceed immediately to remove or dispose of any debris arising from damage to or destruction of the **works** and to rebuild, restore, replace and/or repair the **works**
- (c) The **employer** shall carry the risk of damage to or destruction of the **works** and material paid for by the **employer** that is the result of the excepted risks as set out in 10.6
- (d) Where the **employer** bears the risk in terms of this contract, the **contractor** shall, if requested to do so, reinstate any damage or destroyed portions of the **works** and the costs of such reinstatement shall be measured and valued in terms of 32.0 hereof

10.6 Injury to Persons or loss of or damage to Properties

(a) The contractor shall be liable for and hereby indemnifies the employer against any liability, loss, claim or proceeding whether arising in common law or by statute, consequent upon personal injuries to or the death of any person whomsoever arising out of or in the course of or caused by the execution of the works unless due to any act or neglect of any person for whose actions the employer is legally liable

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

R

R

Brought Forward

- (b) The contractor shall be liable for and hereby indemnifies the employer against any liability, loss, claim or proceeding consequent upon loss of or damage to any moveable or immovable or personal property or property contiguous to the site, whether belonging to or under the control of the employer or any other body or person, arising out of or in the course of or by reason of the execution of the works unless due to any act or neglect of any person for whose actions the employer is legally liable
- (c) The contractor shall, upon receiving a contract instruction from the principal agent, cause the same to be made good in a perfect and workmanlike manner at his own cost and in default thereof the employer shall be entitled to cause it to be made good and to recover the cost thereof from the contractor or to deduct the same from amounts due to the contractor
- (d) The contractor shall be responsible for the protection and safety of such portions of the premises placed under his control by the employer for the purpose of executing the works until the issue of the certificate of practical completion
- (e) Where the execution of the works involves the risk of removal of or interference with support to adjoining properties including land or structures or any structures to be altered or added to, the **contractor** shall and will remain adequately insured or insured against the death of or injury to persons or damage to such property consequent on such removal or interference with the support until such portion of the **works** has been completed

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

R

R

Brought Forward

(f) The contractor shall at all times proceed immediately at his own cost to remove or dispose of any debris and to rebuild, restore, replace and/or repair such property and to execute the works

10.7 High risk insurance

In the event of the project being executed in a geological area classified as a "High Risk Area", that is an area which is subject to highly unstable subsurface conditions that might result in catastrophic ground movement evident by sinkhole or doline formation the following will apply:

10.7.1 Damage to the works

The **contractor** shall, from the commencement **date** of the **works** until the date of the **certificate of practical completion** bear the full risk of and hereby indemnifies and holds harmless the **employer** against any damage to and/or destruction of the **works** consequent upon a catastrophic ground movement as mentioned above. The **contractor** shall take such precautions and security measures and other steps for the protection of the **works** as he may deem necessary

When so instructed to do so by the Principal Agent, the Contractor shall proceed immediately to remove and/or dispose of any debris arising from damage to or destruction of the works and to rebuild, restore, replace and/or repair the works, at the contractor's own costs

10.7.2 Injury to persons or loss of or damage to property

The **contractor** shall be liable for and hereby indemnifies and holds harmless the **employer** against any liability, loss, claim or proceeding arising at any time during the period of the contract whether arising in common law or by statute, consequent upon personal injuries to or the death of any person whomsoever resulting from, arising out of or caused by a catastrophic ground movement as mentioned above

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

-9-

| | Brought Forward | | R | |
|----|--|------|---|--|
| | The contractor shall be liable for and hereby indemnifies the employer against any and all liability, loss, claim or proceeding consequent upon loss of or damage to any moveable or immovable or personal property or property contiguous to the site , whether belonging to or under the control of the employer or any other body or person whomsoever arising out of or caused by a catastrophic ground movement, as mentioned above, which occurred during the period of the contract | | | |
| | 10.7.3 It is the responsibility of the contractor to ensure that he has adequate insurance to cover his risk and liability as mentioned in 10.7.1 and 10.7.2. Without limiting the contractor's obligations in terms of the contract, the contractor shall, within twenty-one (21) calendar days of the commencement date but before commencement of the works , submit to the employer proof of such insurance policy, if requested to do so | | | |
| | 10.7.4 The employer shall be entitled to recover any and all losses and/or damages of whatever nature suffered or incurred consequent upon the contractor's default of his obligations as set out in 10.7.1; 10.7.2 and 10.7.3. Such losses or damages may be recovered from the contractor or by deducting the same from any amounts still due under this contract or under any other contract presently or hereafter existing between the employer and the contractor and for this purpose all these contracts shall be considered one indivisible whole | | | |
| | F: V: T: | ltem | | |
| 11 | 11.0 Liability Insurances | | | |
| | F: V: T: | ltem | | |
| 12 | 12.0 Effecting Insurances | | | |
| | F: V: T: | ltem | | |
| | Carried Forward Section No. 1 Bill No. 1 | | R | |
| | Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | | Brought Forward | | R | |
|----|---|---|-----|---|--|
| 13 | 13.0 | No clause | N/A | | |
| 14 | 14.0 | SECURITY | | | |
| | | es 14.1 - 14.8 are amended by replacing them e following: | | | |
| | R1 mil contra reduct | n respect of contracts with a contract sum up to lion, the security to be submitted by the actor to the employer will be as a payment ion of five per cent (5%) of the value certified in yment certificate (excluding VAT) | | | |
| | | The payment reduction of the value certified in a ent certificate shall be <i>mutatis mutandi</i> in terms B(A) | | | |
| | expens of 33.0 provisi entitler refund | The employer shall be entitled to recover se and loss from the payment reduction in terms) provided that the employer complies with the ions of 33.4 in which event the employer's ment shall take precedence over his obligations to the payment reduction security or portions f to the contractor | | | |
| | R1 mil the se 14.6, c shall b (21) ca the co or sho with th calence | in respect of contracts with a contract sum above lion, the contractor shall have the right to select curity to be provided in terms of 14.3, 14.4, 14.5, or 14.7 as stated in the schedule . Such security be provided to the employer within twenty-one alendar days from commencement date . Should ntractor fail to select the security to be provided uld the contractor fail to provide the employer be selected security within twenty-one (21) dar days from commencement date , the ity in terms of 14.7 shall be deemed to have been ed. | | | |
| | | Vhere security as a cash deposit of ten per cent of the contract sum (excluding VAT) has been ed: | | | |
| | Section Bill No | Carried Forward n No. 1 | | R | |
| | Prelim | | | | |
| | Diatho | o Consulting (PTY) LTD | | | |

| Brought Forward | R | |
|---|---|---|
| 14.3.1 The contractor shall furnish the employer with a cash deposit equal in value to ten per cent (10%) of the contract sum (excluding VAT) within twenty-one (21) calendar days from commencement date | | |
| 14.3.2 Within twenty-one (21) calendar days of the date of practical completion of the works the employer shall reduce the cash deposit to an amount equal to three per cent (3%) of the contract value (excluding VAT), and refund the balance to the contractor | | |
| 14.3.3 Within twenty-one (21) calendar days of the date of final completion of the works the employer shall reduce the cash deposit to an amount equal to one per cent (1%) of the contract value (excluding VAT) and refund the balance to the contractor | | |
| 14.3.4 On the date of payment of the amount in the final payment certificate , the employer shall refund the remainder of the cash deposit to the contractor | | |
| 14.3.5 The employer shall be entitled to recover expense and loss from the cash deposit in terms of 33.0 provided that the employer complies with the provisions of 33.4 in which event the employer's entitlement shall take precedence over his obligations to refund the cash deposit security or portions thereof to the contractor | | |
| 14.3.6 The parties expressly agree that neither the employer nor the contractor shall be entitled to cede the rights to the deposit to any third party | | |
| 14.4 Where security as a variable construction guarantee of ten percent (10%) of the contract sum (excluding VAT) has been selected: | | |
| 14.4.1 The contractor shall furnish the employer with an acceptable variable construction guarantee equal in value to ten per cent (10%) of the contract sum (excluding VAT) within twenty-one (21) calendar days from commencement date | | |
| Carried Forward | R | - |
| Section No. 1 Bill No. 1 Preliminaries | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| 14.4.2 The variable construction guarantee shall reduce and expire in terms of the Variable Construction Guarantee form included in the invitation to tender | | |
| 14.4.3 The employer shall return the variable construction guarantee to the contractor within fourteen (14) calendar days of it expiring | | |
| 14.4.4 Where the employer has a right of recovery against the contractor in terms of 33.0, the employer shall issue a written demand in terms of the variable construction guarantee | | |
| 14.5 Where security as a fixed construction guarantee of five per cent (5%) of the contract sum (excluding VAT) and a five per cent (5%) payment reduction of the value certified in the payment certificate (excluding VAT) has been selected: | | |
| 14.5.1 The contractor shall furnish a fixed construction guarantee to the employer equal in value to five per cent (5%) of the contract sum (excluding VAT) | | |
| 14.5.2 The fixed construction guarantee shall come into force on the date of issue and shall expire on the date of practical completion | | |
| 14.5.3 The employer shall return the fixed construction guarantee to the contractor within fourteen (14) calendar days of it expiring | | |
| 14.5.4 The payment reduction of the value certified in a payment certificate shall be in terms of 31.8 (A) and 34.8 | | |
| 14.5.5 Where the employer has a right of recovery against the contractor in terms of 33.0, the employer shall be entitled to issue a written demand in terms of the fixed construction guarantee or may recover from the payment reduction or may do both | | |
| | | |
| Carried Forward Section No. 1 Bill No. 1 Preliminaries | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| 14.6 Where security as a cash deposit of five per cent (5%) of the contract sum (excluding VAT) and a payment reduction of five per cent (5%) of the value certified in the payment certificate (excluding VAT) has been selected: | | |
| 14.6.1 The contractor shall furnish the employer with a cash deposit equal in value to five per cent (5%) of the contract sum (excluding VAT) within twenty-one (21) calendar days from commencement date | | |
| 14.6.2 Within twenty-one (21) calendar days of the date of practical completion of the works the employer shall refund the cash deposit in total to the contractor | | |
| 14.6.3 The payment reduction of the value certified in a payment certificate shall be <i>mutatis mutandi</i> in terms of 31.8(A) | | |
| 14.6.4 Where the employer has a right of recovery against the contractor in terms of 33.0, the employer may issue a written notice in terms of 33.4 or may recover from the payment reduction or may do both | | |
| 14.7 Where security as a payment reduction of ten per cent (10%) of the value certified in the payment certificate (excluding VAT) has been selected: | | |
| 14.7.1 The payment reduction of the value certified in a payment certificate shall be <i>mutatis mutandi</i> in terms of 31.8(B) | | |
| 14.7.2 The employer shall be entitled to recover expense and loss from the payment reduction in terms of 33.0 provided that the employer complies with the provisions of 33.4 in which event the employer's entitlement shall take precedence over his obligations to refund the payment reduction or portions thereof to the contractor | | |
| 14.8 Payments made by the guarantor to the employer in terms of the fixed or variable construction guarantee shall not prejudice the rights of the employer or contractor in terms of this agreement | | |
| Carried Forward | R | |
| Section No. 1 Bill No. 1 Preliminaries | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| I | | I | | 1 | I |
|----|---|------|---|---|---|
| | Brought Forward 14.9 Should the contractor fail to furnish the security in terms of 14.2, the employer, in his sole discretion and without notification to the contractor, is entitled to change the contractor's selected form of security to that of a ten per cent (10%) payment reduction of the value certified in the payment certificate (excluding VAT), whereafter 14.7 shall be applicable F: V: T: | Item | R | | |
| | EXECUTION | | | | |
| 15 | 15.0 PREPARATION FOR AND EXECUTION OF THE WORKS | | | | |
| | Clause 15.1.1 is amended by replacing it with: | | | | |
| | No Clause | | | | |
| | Clause 15.1 is amended by the addition of the following clause: 15.1.4 An acceptable health and safety plan, required in terms of the Occupational Health and Safety Act, 1993 (Act 85 of 1993), within twenty-one (21) calendar days of commencement date | | | | |
| | Clause 15.2.1 is amended by replacing it with the following clause: | | | | |
| | Give the contractor possession of the site within ten (10) working days of the contractor complying with the terms of 15.1.2 and 15.1.4 | | | | |
| | F: V: T: | 14 | | | |
| | | Item | | | |
| 16 | 16.0 Access to the Works | | | | |
| | F: V: T: | | | | |
| | | Item | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 1 | | R | | |
| | Bill No. 1 Preliminaries | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|--|------|---|--|
| 17 | 17.0 Contract Instructions | | | |
| | F: V: T: | ltem | | |
| 18 | 18.0 Setting out of the Works | | | |
| | F: V: T: | ltem | | |
| 19 | 19.0 Assignment | | | |
| | F: V: T: | ltem | | |
| 20 | 20.0 Nominated Subcontractors | | | |
| | 20.1.3 is amended by replacing it with the following: | | | |
| | Note: See item B9.1 hereinafter for adjustment of attendance on nominated subcontractors executing work allowed for under provisional sums | | | |
| | F: V: T: | ltem | | |
| 21 | 21.0 Selected Subcontractors | | | |
| | 21 is amended by replacing it with: | | | |
| | No Clause | | | |
| | F: V: T: | N/A | | |
| 22 | 22.0 Employer's Direct Contractors | | | |
| | F: V: T: | ltem | | |
| 23 | 23.0 Contractor's Domestic Subcontractors | | | |
| | F: V: T: | ltem | | |
| | Carried Forward Section No. 1 | | R | |
| | Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|----|---|------|---|---|
| | COMPLETION | | | |
| 24 | 24.0 Practical Completion | | | |
| | F: V: T: | ltem | | |
| 25 | 25.0 Work's Completion | | | |
| | F: V: T: | ltem | | |
| 26 | 26.0 Final Completion | | | |
| | F: V: T: | ltem | | |
| 27 | 27.0 Latent Defects Liability Period | | | |
| | F: V: T: | ltem | | |
| 28 | 28.0 Sectional Completion | | | |
| | F: V: T: | ltem | | |
| 29 | 29.0 Revision of Date for Practical Completion | | | |
| | F: V: T: | ltem | | |
| 30 | 30.0 Penalty for Noncompletion | | | |
| | F: V: T: | ltem | | |
| | PAYMENT | | | |
| 31 | 31.0 INTERIM PAYMENT TO THE CONTRACTOR | | | |
| | 31.8 is amended by replacing it with the following two alternative clauses: | | | |
| | Carried Forward Section No. 1 Bill No. 1 | | R | _ |
| | Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | | Nev.u |
|---------------------|---|---|-------|
| | Brought Forward | R | |
| | Iternative A | | |
| 1 a c | 1.8(A) Where a security is selected in terms of 14.1; 4.5 or 14.6, the value of the works in terms of 31.4.1 nd materials and goods in terms of 31.4.2 shall be ertified in full. The value certified shall be subject to the blowing percentage adjustments: | | |
| ir | 1.8(A).1 Ninety-five per cent (95%) of such value in nterim payment certificates issued up to the date of ractical completion | | |
| ir p | 1.8(A).2 Ninety-seven per cent (97%) of such value in nterim payment certificates issued on the date of practical completion and up to but excluding the date f final completion | | |
| ir c | 1.8(A).3 Ninety-nine per cent (99%) of such value in nterim payment certificates issued on the date of final ompletion and up to but excluding the final payment ertificate in terms of 34.6 | | |
| tł w Ir tł | 1.8(A).4 One hundred per cent (100%) of such value in the final payment certificate in terms of 34.6 except where the amount certified is in favour of the employer . In such an event the payment reduction shall remain at the adjustment level applicable to the final payment ertificate | | |
| | Iternative B | | |
| 0 n C | 1.8(B) Where security is a payment reduction in terms f 14.7 the value of the works in terms of 31.4.1 and naterials and goods in terms of 31.4.2 shall be ertified in full. The value certified shall be subject to the billowing percentage adjustments: | | |
| p | 1.8(B).1 Ninety per cent (90%) of such value in interim ayment certificates issued up to the date of practical ompletion | | |
| | | | |
| | | | |
| | Carried Forward | R | |
| B | ection No. 1 ill No. 1 reliminaries | | |
| | viatho Consulting (PTY) LTD | | |
| | | | |

| | Brought Forward | | R | |
|----|---|------|---|--|
| | 31.8(B).2 Ninety-seven per cent (97%) of such value in interim payment certificates issued on the date of practical completion and up to but excluding the date of final completion | | | |
| | 31.8(B).3 Ninety-nine per cent (99%) of such value in interim payment certificates issued on the date of final completion and up to but excluding the final payment certificate in terms of 34.6 | | | |
| | 31.8(B).4 One hundred per cent (100%) of such value in the final payment certificate in terms of 34.6 except where the amount certified is in favour of the employer . In such an event the payment reduction shall remain at the adjustment level applicable to the final payment certificate | | | |
| | Clause 31.12 is amended by deleting the following: | | | |
| | Payment shall be subject to the employer giving the contractor a tax invoice for the amount due | | | |
| | F: V: T: | Item | | |
| 32 | 32.0 Adjustment to the Contract Value | | | |
| | Clauses 32.5.1, 32.5.4 and 32.5.7 are amended by the addition of the following at the end of the sentence: | | | |
| | "due to no fault of the contractor" | | | |
| | F: V: T: | Item | | |
| 33 | 33.0 RECOVERY OF EXPENSE AND LOSS | | | |
| 00 | Clause 33.2 is amended by adding the following clauses: | | | |
| | 33.2.9 the contractor's failure or neglect to commence with the works on the dates prescribed in the contract | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |
| | | 1 1 | 1 | |

| | Brought Forward | | R | |
|----|---|------|---|------|
| | 33.2.10 the contractor's failure or neglect to proceed with the works in terms of the contract | | | |
| | 33.2.11 the contractor's failure or neglect for any reason to complete the works in accordance with the contract | | | |
| | 33.2.12 the contractor's refusal or neglect to comply strictly with any of the conditions of contract or any contract instructions and/or orders in writing given in terms of the contract | | | |
| | 33.2.13 the contractor's estate being sequestrated, liquidated or surrendered in terms of the insolvency laws in force within the Republic of South Africa | | | |
| | F: V: T: | ltem | | |
| 34 | 34.0 Final Account and Final Payment | | | |
| | Clause 34.13 is amended by replacing "seven (7) calendar days " with "twenty-one (21) calendar days " and deleting the words "subject to the employer giving the contractor a tax invoice for the amount due" | | | |
| | F: V: T: | | | |
| | | ltem | | |
| 35 | 35.0 Payment to other Parties | | | |
| | F: V: T: | ltem | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 | | | |
| | Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | | | | 1/64. | 00 |
|----|--|------|---|-------|----|
| | Brought Forward | | R | | |
| | CANCELLATION | | | | |
| | 36.0 CANCELLATION BY EMPLOYER - CONTRACTOR'S DEFAULT | | | | |
| | 36.3 is amended by removing the reference to "No clause" and replacing the words " principal agent " with " employer " | | | | |
| | 36.0 is amended by the addition of the following clause: | | | | |
| | 36.7 Notwithstanding any clause to the contrary, on cancellation of this agreement either by the employer or the contractor ; or for any reason whatsoever, the contractor shall on written instruction, discontinue with the works on a date stated and withdraw himself from the site . The contractor shall not be entitled to refuse to withdraw from the works on the grounds of any lien or right of retention or on the grounds of any other right whatsoever | | | | |
| | F: V: T: | | | | |
| | | | | | |
| 36 | 37.0 CANCELLATION BY EMPLOYER - LOSS AND DAMAGE | | | | |
| | 37.0 is amended by the addition of the following clause: | | | | |
| | 37.5 Notwithstanding any clause to the contrary, on cancellation of this agreement either by the employer or the contractor ; or for any reason whatsoever, the contractor shall on written instruction, discontinue with the works on a date stated and withdraw himself from the site . The contractor shall not be entitled to refuse to withdraw from the works on the grounds of any lien or right of retention or on the grounds of any other right whatsoever | | | | |
| | F: V: T: | ltem | | | |
| | | | | | |
| | Carried Forward Section No. 1 | | R | | |
| | Bill No. 1 Preliminaries | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | l |
|----|--|------|---|---|
| 37 | 38.0 CANCELLATION BY CONTRACTOR - EMPLOYER'S DEFAULT | | | |
| | Clause 38.0 is amended by the addition of the following clause: | | | |
| | 38.7 Notwithstanding any clause to the contrary, on cancellation of this agreement either by the employer or the contractor ; or for any reason whatsoever, the contractor shall on written instruction, discontinue with the works on a date stated and withdraw himself from the site . The contractor shall not be entitled to refuse to withdraw from the works on the grounds of any lien or right of retention or on the grounds of any other right whatsoever | | | |
| | F: V: T: | | | |
| 38 | 39.0 Cancellation - Cessation of the Works | | | |
| | F: V: T: | ltem | | |
| 39 | 40.0 Dispute Settlement | | | |
| | 40.2.2 is amended by replacing "one (1) year" with "three (3) years" | | | |
| | 40.6 is amended by removing the reference to: | | | |
| | No clause | | | |
| | 40.7.1 is amended by replacing "(10)" with "(15)" and by the addition of the following: | | | |
| | Whether or not mediation resolves the dispute, the parties shall bear their own cost concerning the mediation and equally share the costs of the mediator and related costs | | | |
| | F: V: T: | ltem | | |
| | | item | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | R | |
|----|--|------|---|--|
| | SUBSTITUTE PROVISIONS | | | |
| 40 | 41.0 State Clauses | | | |
| | F: V: T: | ltem | | |
| | CONTRACT VARIABLES | | | |
| | THE SCHEDULE (DPW04EC) | | | |
| 41 | 42.0 E-TENDER INFORMATION | | | |
| | Tenderers are referred to section "C1.2 Contract Data" on page 56 for variables pertaining to this contract | | | |
| | F: V: T: | ltem | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 | | ĸ | |
| | Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | R | |
|----|--|------|---|--|
| | SECTION B: JBCC PRELIMINARIES | | | |
| | 1.0 DEFINITIONS AND INTERPRETATION | | | |
| 42 | 1.1 Definitions and interpretation | | | |
| | F: V: T: | Item | | |
| | 2.0 DOCUMENTS | | | |
| 43 | 2.1 Checking of documents | | | |
| | F: V: T: | Item | | |
| 44 | 2.2* Provisional bills of quantities | | | |
| | F: V: T: | Item | | |
| 45 | 2.3* Availability of construction documentation | | | |
| | F: V: T: | ltem | | |
| 46 | 2.4* Interests of agents | | | |
| | F: V: T: | Item | | |
| 47 | 2.5 Priced documents | | | |
| | F: V: T: | Item | | |
| 48 | 2.6 Tender submission | | | |
| | Clause 2.6 is amended by replacing "JBCC Form of Tender" with "Form of Offer and Acceptance (DPW07)" | | | |
| | F: T: | ltem | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | l | |

| | Brought Forward | | R | |
|----|---|------|---|---|
| | <u>3.0 THE SITE</u> | | | |
| 49 | 3.*1 Defined works area | | | |
| | F: V: T: | ltem | | |
| 50 | 3.2* Geotechnical investigation | | | |
| | F: V: T: | ltem | | |
| 51 | 3.3 Inspection of the site | | | |
| | Tenderers shall complete the Site Inspection Certificate (DPW16 EC) included in the tender documents and return the same with the tender submission. | | | |
| | F: V: T: | ltem | | |
| 52 | 3.4* Existing premises occupied | | | |
| | F: V: T: | ltem | | |
| 53 | 3.5* Previous work - dimensional accuracy | | | |
| | F: V: T: | | | |
| | | ltem | | |
| 54 | 3.6 Previous work - defects | | | |
| | F: V: T: | ltem | | |
| 55 | 3.7* Services - known | | | |
| | F: V: T: | ltem | | |
| | Carried Forward Section No. 1 Bill No. 1 Preliminaries | | R | _ |
| | Diatho Consulting (PTY) LTD | | | |

| | | Brought Forward | | R | |
|----|--|-----------------|------|---|--|
| 56 | 3.8 Services - unknown | | | | |
| | F: V: | Т: | ltem | | |
| 57 | 3.9* Protection of trees | | | | |
| | F: V: | Т: | ltem | | |
| 58 | 3.10 Articles of value | | | | |
| | F: V: | Т: | ltem | | |
| 59 | 3.11* Inspection of adjoining properties | | | | |
| | F: V: | Т: | ltem | | |
| | 4.0 MANAGEMENT OF CONTRACT | | | | |
| 60 | 4.1 Management of the works | | | | |
| | F: V: | Т: | ltem | | |
| 61 | 4.2 Programme for the works | | | | |
| | F: V: | Т: | ltem | | |
| 62 | 4.3 Progress meetings | | | | |
| | F: V: | Т: | ltem | | |
| 63 | 4.4 Technical meetings | | | | |
| | F: V: | Τ: | ltem | | |
| | | | | | |
| | Section No. 1 Bill No. 1 Preliminaries | Carried Forward | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | R | |
|----|---|------|---|---|
| 64 | 4.5 Labour and plant records | | | |
| | F: V: T: | Item | | |
| | 5.0 SAMPLES, SHOP DRAWINGS AND MANUFACTURERS' INSTRUCTIONS | | | |
| 65 | 5.1 Samples of materials | | | |
| | F: V: T: | Item | | |
| 66 | 5.2 Workmanship samples | | | |
| | F: V: | Item | | |
| 67 | 5.3 Shop drawings | | | |
| | F: V: T: | Item | | |
| 68 | 5.4 Compliance with manufacturers' instructions | | | |
| | F: V: | Item | | |
| | 6.0 TEMPORARY WORKS AND PLANT | | | |
| 69 | 6.1 Deposits and fees | | | |
| | F: V: T: | Item | | |
| 70 | 6.2* Enclosure of the works | | | |
| | F: V: T: | Item | | |
| 71 | 6.3 Advertising | | | |
| | F: V: T: | Item | | |
| | Carried Forward | | R | + |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | Brought Forward | | R | |
|----|--|-----------------|------|---|--|
| 72 | 6.4* Plant, equipment, sheds and office | es | | | |
| | F: V: | Т: | ltem | | |
| 73 | 6.5* Main notice board | | | | |
| | F: V: | Т: | ltem | | |
| 74 | 6.6* Subcontractors' notice board | | | | |
| | F: V: | Т: | ltem | | |
| | 7.0 TEMPORARY SERVICES | | | | |
| 75 | 7.1 Location | | | | |
| | F: V: | Т: | ltem | | |
| 76 | 7.2& Water | | | | |
| | F: V: | Т: | ltem | | |
| 77 | 7.3& Electricity | | | | |
| | F: V: | Т: | ltem | | |
| 78 | 7.4& Telecommunication facilities | | | | |
| | F: V: | Т: | ltem | | |
| 79 | 7.5& Ablution facilities | | | | |
| | F: V: | T: | ltem | | |
| | | | | | |
| | Section No. 1 Bill No. 1 Preliminaries | Carried Forward | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | R | |
|----|--|------|---|--|
| | 8.0 PRIME COST AMOUNTS | | | |
| 80 | 8.1 Responsibility for prime cost amounts | | | |
| | F: V: T: | ltem | | |
| | 9.0 ATTENDANCE ON N/S SUBCONTRACTORS | | | |
| 81 | 9.1 General attendance | | | |
| | The schedule rates providing for attendance on nominated subcontractors and other contractors , will be adjusted only if the scope of the work has changed | | | |
| | F: V: T: | ltem | | |
| 82 | 9.2* Special attendance | | | |
| | F: V: T: | ltem | | |
| 83 | 9.3 Commissioning - fuel, water and electricity | | | |
| | F: V: T: | ltem | | |
| | 10.0 FINANCIAL ASPECTS | | | |
| 84 | 10.1 Statutory taxes, duties and levies | | | |
| | F: V: T: | ltem | | |
| 85 | 10.2 & Payment for preliminaries | | | |
| | F: V: T: | ltem | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | | Brought Forward | | R | |
|----|---|-----------------|------|---|--|
| 86 | 10.3 & Adjustment of preliminaries | | | | |
| | F: V: | T: | ltem | | |
| 87 | 10.4 Payment certificate cash flow | | | | |
| | F: V: | Т: | Item | | |
| | 11.0 GENERAL | | | | |
| 88 | 11.1* Protection of the works | | | | |
| | F: V: | Т: | ltem | | |
| 89 | 11.2* Protection / isolation of existing / socupied works | sectionally | | | |
| | F: V: | T: | ltem | | |
| 90 | 11.3 Security of the works | | | | |
| | F: V: | Т: | Item | | |
| 91 | 11.4 Notice before covering work | | | | |
| | F: V: | T: | Item | | |
| 92 | 11.5* Disturbance | | | | |
| | F: V: | Т: | Item | | |
| 93 | 11.6* Environmental disturbance | | | | |
| | F: V: | T: | ltem | | |
| | | | | | |
| | Section No. 1 Bill No. 1 Preliminaries | Carried Forward | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | R | |
|----|---|------|---|--|
| 94 | 11.7 Works cleaning and clearing | | | |
| | F: V: T: | ltem | | |
| 95 | 11.8 Vermin | | | |
| | F: V: T: | ltem | | |
| 96 | 11.9 Overhand work | | | |
| | F: V: T: | ltem | | |
| 97 | 11.10 Instruction manuals and guarantees | | | |
| | F: V: T: | ltem | | |
| 98 | 11.11 As built information | | | |
| | F: V: T: | ltem | | |
| 99 | 11.12 Tenant installations | | | |
| | F: V: T: | ltem | | |
| | 12.0 SCHEDULE OF VARIABLES | | | |
| | 12.1 PRE-TENDER INFORMATION | | | |
| | 12.1.1 Provisional bills of quantities [2.2] | | | |
| | YES | | | |
| | 12.1.2 Availability of construction documentation [2.3] | | | |
| | YES | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| Brought Forward | R | |
|---|---|--|
| 12.1.3 Interests of agents [2.4] | | |
| N/A | | |
| 12.1.4 Defined works area [3.1] | | |
| Give details and/or refer Architect's site plan drawing no where available | | |
| 12.1.5 Geotechnical Investigation [3.2] | | |
| Geotechnical investigation report where available | | |
| 12.1.6 Existing premises occupied [3.4] | | |
| The existing buildings on the site is occupied by school learners and staff | | |
| 12.1.7 Previous work - dimensional accuracy [3.5] | | |
| N/A | | |
| 12.1.8 Previous work - defects [3.6] | | |
| N/A | | |
| 12.1.9 Services - known [3.7] | | |
| Not known | | |
| 12.1.10 Protection of trees [3.9] | | |
| Trees not being removed must be protected. | | |
| 12.1.11 Inspection of adjoining properties [3.11] | | |
| This also applies to roads and services, etc. | | |
| 12.1.12 Enclosure of the works [6.2] | | |
| No specific requirements | | |
| | | |
| Carried Forward Section No. 1 Bill No. 1 Preliminaries | R | |
| Diatho Consulting (PTY) LTD | | |

R

R

Brought Forward

12.1.13 Offices [6.4.3]

The Contractor shall provide, maintain and remove on completion of the works an office for the exclusive use of the Principal Agent, minimum size $6 \times 3 \times 3$ m high internally, suitably insulated and ventilated, provided with electric lighting and fitted with boarded floor, desk, chair, drawing stool, drawing board and lock-up drawers for drawings. The office shall be kept clean and fit for use at all times

12.1.14 Main notice board [6.5]

Provide ONE (1) noticeboards, eg:

The Contractor shall provide, erect where directed, maintain and remove on completion of the works a notice board size 3 x 3m, constructed of suitable boarding with flat smooth surface and with edging bead 19mm thick round outer edges and projecting 12mm from face of boarding and rounded on front edge. The board shall be securely fixed to hoarding, where hoarding is provided, or fixed to and including a suitable supporting structure of timber or tubular posts and braces. The board is to be painted ivory white and the bead and 12mm wide dividing lines dark green. All wording shall be inscribed in dark green as per the coat of arms for SA. All wording shall be inscribed in dark green painted "sans serif" lettering

12.1.15 Subcontractors notice board [6.6]

NO

12.1.16 Water [7.2]

Option A (by contractor)

12.1.17 Electricity [7.3]

Option A (by contractor)

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

| Brought Forward | | R | | |
|--|---|---|---|--|
| 12.1.18 Telecommunications [7.4] | | | | |
| Telephone - YES Facsimile - YES Email - YES | | | | |
| 12.1.19 Ablution facilities [7.5] | | | | |
| Option A (by contractor) | | | | |
| 12.1.20 Protection of existing/sectionally occupied works [11.2] | | | | |
| Protection is required | | | | |
| YES | | | | |
| 12.1.21 Special attendance [9.2] | | | | |
| N/A | | | | |
| 12.1.22 Protection of the works [11.1] | | | | |
| No specific requirements | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Carried Forward | | R | | |
| Section No. 1 Bill No. 1 Preliminaries | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |
| | 1 | 1 | ı – – – – – – – – – – – – – – – – – – – | |

R

Brought Forward

12.1.23 Disturbance [11.5]

The Contractor shall be responsible for and take all precautions in controlling all forms of pollution during the contract period due to noise, artificial light, wind-blown sand, dust, etc in the dry season and deposits of mud etc in the wet season by whatever means necessary and daily removal of deposits etc, all to the satifaction of the Principal Agent and any costs, claims, etc will be for the Contractor's account

The surrounding buildings will be occupied and functioning during these works and the Contractor is to ensure that the works are carried out with as little mess and noise as possible and with a minimum of disturbance to adjoining and close buildings and properties and their occupants. The Contractor is to make use of appropriate plant and methods of execution which result in the least possible noise factors. All machinery shall be fully muffled

The Contractor shall keep the site, structures and materials well watered during the operations to prevent dust and shall provide, erect and maintain all temporary tarpaulins, dust and weatherproof screens, barriers and temporary plumbing that may be necessary during the progress of the works

The Contractor shall ensure that the functioning of the existing School is not disturbed or disrupted, except where special arrangements are made with the Principal Agent

The Contractor may not carry out construction operations outside of normal working times without the permission of the Principal Agent

12.1.24 Environmental disturbance [11.6]

No specific requirements

Carried Forward

R

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

| Brought Forward | R |
|--|---|
| 12.2 POST-TENDER INFORMATION | |
| 12.2.1 Payment of preliminaries | |
| [10.2] Option A or B (post tender) | |
| 12.2.2 Adjustment of preliminaries | |
| [10.3] Option A or B (post tender) | |
| 12.2.3 Additional agreed preliminaries items | |
| Details: To be agreed post tender where relevant | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| Carried Forward | R |
| Section No. 1 Bill No. 1 | |
| Preliminaries | |
| Diatho Consulting (PTY) LTD | |
| | |

| | Brought Forward | | R | |
|-----|--|------|---|--|
| | SECTION C: SPECIFIC PRELIMINARIES | | | |
| | Section C contains specific preliminary items which apply to this contract except where N/A (Not Applicable) appears against an item | | | |
| | C1: CONFIDENTIALITY | | | |
| 100 | The drawings issued with the tender documents do not comprise the complete set but serve as a guide only for tendering purposes and for indicating the scope of the work to enable the tenderer to acquaint himself with the nature and extent of the works and the manner in which they are to be executed | | | |
| | Should any part of the drawings not be clearly intelligible to the tenderer he shall, before submitting his tender, obtain clarification in writing from the principal agent | | | |
| | F: V: T: | ltem | | |
| | C2: TRADE NAMES | | | |
| 101 | Wherever a trade name for any product has been described in the bills of quantities , the tenderer's attention is drawn to the fact that any other product of equal quality may be used subject to the written approval of the principal agent being obtained prior to the closing date for submission of tenders | | | |
| | If prior written approval for an alternative product is not obtained,it shall be deemed that the tenderer the product described has been tendered for | | | |
| | F: V: T: | ltem | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 1 Bill No. 1 Preliminaries | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R |
|-----|--|------|---|
| | C3: IMPORTED MATERIALS | | |
| 102 | Where imported items are listed in the tender documents, the tenderer shall provide all the information called for, failing which the price of any such item, materials or equipment shall be excluded from currency fluctuations. | | |
| | Notwithstanding any provisions elsewhere regarding the adjustment of contract prices, the price of any item, material or equipment listed in terms of this clause shall be excluded from the Contract Price Adjustment Provisions (if applicable) | | |
| | F: V: T: | Item | |
| | C4: SECURITY CHECK OF PERSONNEL | | |
| 103 | The principal agent may require the contractor to have his personnel and workmen, or a certain number of them, security classified | | |
| | In the event of the principal agent requesting the removal of a person or persons from the works for security reasons, the contractor shall do so forthwith and shall thereafter ensure that such person or persons are denied access to the works and the site and/or to any document or information relating to the works | | |
| | F: V: T: | Item | |
| | C5: CONTRACT INSTRUCTIONS | | |
| 104 | Contract instructions issued on site are to be recorded in triplicate in a site instruction book which is to be maintained on site by the Contractor | | |
| | F: V: T: | Item | |
| | | | |
| | Carried Forward | | R |
| | Section No. 1 Bill No. 1 Preliminaries | | |
| | Diatho Consulting (PTY) LTD | | |
| | | | |

| | Brought Forward | | R | |
|-----|--|------|---|--|
| | <u>C6: SITE LEVELS</u> | | | |
| 105 | Before commencement of the works the Contractor shall carry out and provide the Principal Agent for approval a survey of the existing site levels in sufficient detail to enable the preparation of a final account | | | |
| | F: V: T: | Item | | |
| | C7: UNAUTHORISED PERSONS ON SITE | | | |
| 106 | The Contractor shall not permit unauthorised persons onto and workmen to lodge on the site | | | |
| | F: V: T: | Item | | |
| | C8: PLANT AND LABOUR RECORD | | | |
| 107 | At the end of each week the Contractor shall provide the Principal Agent with a written record, in schedule form, reflecting the number and description of tradesmen and labourers employed by him and all subcontractors on the works each day and the number, type and capacity of all plant, excluding hand tools, currently used on the works | | | |
| | F: V: T: | Item | | |
| | <u>C9: USE OF LOCAL LABOUR FROM THE</u> EMPLOYER'S AREAS OF OPERATION | | | |
| 108 | It is a requirement of the contract that the work be executed in such a manner as to maximise the use of local labour from the Employer's areas of operation in order to provide the local community with employment opportunities. | | | |
| | The tenderer is to identify all activities for which it is intended to employ workers from the local community and full details therof are to be provided in the tender documentation | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

R

R

Brought Forward

The total value of the work that is to be of a local labour nature may be a consideration in the adjudication process. Once a tender is accepted the activities and number of persons stated in the above-mentioned schedule shall become the minimum contractual commitment. In applying the principles set out above, it is a specific requirement of this tender that the successful tenderer employs, in consultation with the Employer's representative, unemployed persons from the ranks of the local communities and the immediate surroundings, who possess the appropriate skills required for a contract of this nature

- In order to achieve the recruitment of local labour, the Employer will establish, a database of unemployed persons, indicating their specialised training, previous experience and employment, etc. The successful tenderer will be required to directly employ suitable persons recruited from the employer's database and ensure that all legislative requirements regarding their employment are complied with and provide the Employer with the necessary documentary proof, if required

- The Contractor is required to produce weekly records suitably detailed to enable the Employer's representative to monitor the achievement of the required local labour percentages. The Contractor is required to provide the Employer's database for the purposes of assessing skills transfer from informal skills training

- The Contractor is required to provide informal skills training so that the required standard of workmanship is maintained

- Any difficulty experienced by the tenderer/Contractor in the procurement of the required percentages of local labour is to be referred immdiately to the Employer's representative

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

| Brought Forward | | R | I |
|---|------|---|---|
| - In respect to "Target Labour", the minimum rate for any and all workers contracted for this project shall be R120 per day | | | |
| F: V: T: | Item | | |
| | | | |
| Carried Forward Section No. 1 Bill No. 1 Preliminaries Diatho Consulting (PTY) LTD | | R | |

R

Brought Forward

C10: COMMUNITY LIASON OFFICER

It is a requirement of this Contract that a Community Liaison officer (CLO) be appointed for the area represented by the Tender. The function of the CLO shall be to represent the local community in matters concerning the use of local labour on the works and to assist with and facilitate communication between the Contractor, the Engineer and the local communities. The period of appointment of the CLO shall be as stated in the Contract for Temporary Employment as a Community Liaison officer referred to below. It must be noted that the date of commencement of temporary employment of the CLO shall be no later than the date of commencement of the Contract. The identification of the approved CLO to be appointed by the Contractor under the Contract shall be resolved by the Contractor, the particular Ward Councillors in collaboration with the Local Communities.

It will be required, therefore, that the successful Tenderer (i.e. the Contractor) enter into a contract for the employment of the abovementioned CLO, the parties to which will be the Contractor, the RDP/Development Forum and the CLO. To this end a specimen Form of Contract for the Temporary Employment as a Community Liaison Officer is included in this document; this Form of Contract sets out, inter alia, the agreement between the parties, the duties and conditions of employment of the CLO (including the rate of remuneration to be paid).

As said contract will be between the Contractor and the CLO, all costs involved shall be borne by the Contractor and the tender shall be deemed to include for this.

F: T: V:

Carried Forward

Section No. 1 Bill No. 1 Preliminaries

Diatho Consulting (PTY) LTD

Item

R

109

| Brought Forward | | R | |
|---|--|--|--|
| ANTEES | | | |
| re guarantees are called for, the Contractor obtain a written guarantee, addressed to Employer, from the firm supplying the trials and/or doing the work and shall er same to the Principal Agent no later than works completion date. guarantee shall state that workmanship, trials and installation are guaranteed for a ified period from the final completion dated that any defects that may arise during the ified period shall be made good at the nse of the firm supplying the materials or doing the work, upon written notice from Principal Agent to do so. This guarantee will be enforced if the work is damaged by cts in the construction of the building in th case the responsibility for replacement rest entirely with the Contractor. Principal Agent shall be the sole judge of ause responsible for defect of the works his decision shall be final and binding in s of clause 40.2 of the agreement | ltem | | |
| | | | |
| | ANTEES re guarantees are called for, the Contractor obtain a written guarantee, addressed to Employer, from the firm supplying the prials and/or doing the work and shall er same to the Principal Agent no later than vorks completion date. guarantee shall state that workmanship, rrials and installation are guaranteed for a dified period from the final completion dated that any defects that may arise during the ified period shall be made good at the nose of the firm supplying the materials or doing the work, upon written notice from Principal Agent to do so. This guarantee will be enforced if the work is damaged by cts in the construction of the building in h case the responsibility for replacement rest entirely with the Contractor. Principal Agent shall be the sole judge of ause responsible for defect of the works his decision shall be final and binding in s of clause 40.2 of the agreement | re guarantees are called for, the Contractor obtain a written guarantee, addressed to Employer, from the firm supplying the erials and/or doing the work and shall er same to the Principal Agent no later than works completion date. guarantee shall state that workmanship, erials and installation are guaranteed for a iffied period from the final completion dated that any defects that may arise during the iffied period shall be made good at the ense of the firm supplying the materials or doing the work, upon written notice from Principal Agent to do so. This guarantee will be enforced if the work is damaged by cts in the construction of the building in h case the responsibility for replacement rest entirely with the Contractor. Principal Agent shall be the sole judge of cause responsible for defect of the works his decision shall be final and binding in s of clause 40.2 of the agreement | re guarantees are called for, the Contractor obtain a written guarantee, addressed to Employer, from the firm supplying the erials and/or doing the work and shall er same to the Principal Agent no later than works completion date. guarantee shall state that workmanship, erials and installation are guaranteed for a iffied period from the final completion dated that any defects that may arise during the iffied period shall be made good at the ense of the firm supplying the materials or doing the work, upon written notice from Principal Agent to do so. This guarantee will be enforced if the work is damaged by cts in the construction of the building in h case the responsibility for replacement rest entirely with the Contractor. Principal Agent shall be the sole judge of cause responsible for defect of the works his decision shall be final and binding in s of clause 40.2 of the agreement |

| | Brought Forward | | R | |
|-----|--|------|---|---|
| | <u>C12: WARRANTIES FOR MATERIAL AND</u> WORKMANSHIP | | | |
| 111 | Where warranties for materials and/or workmanship are called for, the Contractor shall obtain a written warranty, addressed to the Employer, from the firm supplying the materials and/or doing the work and shall deliver same to the Principal Agent on the certified practical completion of the contract | | | |
| | The warranty shall state that workmanship, materials and installation are warranteed for a specified period from the date of final completion and that any defects that may arise during the specified period shall be made good at the expense of the firm supplying the materials and/or doing the work, upon written notice to do so. The warranty will not be enforced if the work is damaged by defects in the construction of the building in which case the responsibility for replacement shall rest entirely with the Contractor | | | |
| | F: V: T: | ltem | | |
| | C13: OVERTIME | | | |
| 112 | Should overtime be required to be worked for any reason whatsoever, the costs of such overtime are to be borne by the Contractor unless the Principal Agent has specifically authorised, in writing, prior to execution thereof, that costs for such overtime are to be borne by the Employer F: V: | | | |
| | | Item | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | 1 |

| | Brought Forward | | R | |
|-----|---|------|---|--|
| | C14: CO-OPERATION OF CONTRACTOR FOR COST MANAGEMENT | | | |
| 113 | It is specifically agreed that the Contractor accepts the obligation of assisting the agents in implementing proper cost management on this project. The Contractor will be advised by the Principal Agent of all cost management procedures which will be implemented to ensure that the final account does not exceed the budget | | | |
| | F: V: T: | | | |
| | | Item | | |
| | C15: FINANCIAL INVESTIGATION | | | |
| 114 | Tenderers must be prepared to furnish the following documentation at own cost within seven (7) days of being called upon to do so: | | | |
| | - Audited financial statements for the past three financial years plus a certified financial statement covering the period from the end of the last financial year to date. If audited statements are not readily available provisional certified statements must be submitted | | | |
| | A resolution of the board of directors authorising the signatory to certify such statements | | | |
| | An extract of the relevant memorandum and article(s) of association from which it is clear that the company is empowered to issue such statement | | | |
| | A list of all major shareholders indicating the percentage shareholding of each | | | |
| | F: V: T: | Item | | |
| | | item | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 1 Bill No. 1 Preliminaries | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| Brought Forward | | R | |
|---|------|---|--|
| <u>C16:REINSTATEMENT OF DAMAGED AREAS ON</u> THE SITE OR EMPLOYERS' PROPERTIES IN | | | |
| GENERAL CAUSED BY CONSTRUCTION OPERATIONS, ETC. | | | |
| Before commencing the works, the Contractor shall arrange with the Principal Agent to inspect, among others, existing buildings, structures, roads, pavings, kerbs, channels and fences on the site or Employers' properties in general | | | |
| The Contractor shall note in writing, all conditions that the works could affect and copy the Principal Agent accordingly. The Contractor should pay particular attention to cracks, defects and existing levels related to structures, roads, pavings, kerbs, channels and fences, which later could be claimed to have been caused or disturbed by the construction operations | | | |
| Where instructed by the Principal Agent, levels and photographs shall be taken by the Contractor and the cost thereof shall be for the Employer's account.Certified copies shall be lodged with the Principal Agent | | | |
| The Contractor will be held responsible for maintaining the above in its present condition during execution of the works and will be liable for all costs relating to the repairing or replacing of damaged areas caused by the construction operations | | | |
| F: V: T: | Item | | |
| SUMMARY OF CATEGORIES | | | |
| Category : Fixed R | | | |
| Category : Value R | | | |
| Category : Time R | | | |
| | | | |
| Carried to Final Summary | | R | |
| Section No. 1 Bill No. 1 Preliminaries | | | |
| | i I | 1 | |

| | Quantity | Rate | Amoun |
|--|----------|------|-------|
| SECTION NO. 2 | | | |
| BILL NO.1 | | | |
| ALTERATIONS (PROVISIONAL) | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition), as published by the Association of South African Quantity Surveyors, shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items, fully described in the said General Preambles, will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| <u>View Site:</u> | | | |
| Before submitting his tender, the Contractor shall visit the site and satisfy himself as to the nature and extent of the work to be done and the value of the materials contained in the buildings or portions of the buildings to be demolished. No claim for any variations of the contract sum in respect of the nature and extent of the work or of inferior or damaged materials will be entertained | | | |
| Old materials to become property of the Contractor: | | | |
| Old materials from demolitions, except where described as to be re-used or handed over, become the property of the Contractor, who must allow credit for same in the last item of the "Demolitions" trade | | | |
| Carried Forward | | R | |
| Section No. 2 Bill No. 1 Alterations | | | |
| Diatho Consulting (PTY) LTD | | | |

R

R

Brought Forward

Old materials to be re-used:

None of the old materials are to be used for new work, except where specifically described as being set aside for re-use

Old materials, debris, etc to be carted away:

All old materials from the demolitions, except where described as to be re-used or handed over, as well as all rubbish, debris, etc must be regularly carted from the site and not be allowed to accumulate on or around the site

Handing over of materials:

Where certain materials or articles from demolitions are described as to be "handed over to the Employer", it shall be taken to mean "handed over by the Contractor to the Principal Agent" and such materials or articles shall be properly stored by the Contractor until handing over thereof and shall include all necessary transport

The Contractor must obtain an official receipt from the Principal Agent listing the materials or articles and dates of handing over

Should the Contractor fail to submit the receipt when requested to do so, it shall be deemed that the materials or articles are still in his possession and he will be held liable to the Employer for the full replacement value thereof, which amount will be deducted from any monies due to the Contractor

Explosives:

No explosives whatsoever may be used for demolition purposes, unless otherwise stated

Carried Forward

Section No. 2 Bill No. 1 Alterations

| | | | | |
|---|--|---|---|------|
| | Brought Forward | | R | |
| | <u>General:</u> | | | |
| | The Contractor shall carry out the whole of the works with as little mess and noise as possible and with a minimum of disturbance to adjoining premises and their tenants. He shall provide proper protection and provide, erect and remove when directed, any temporary tarpaulins that may be necessary during the progress of the works, all to the satisfaction of the Principal Agent | | | |
| | Water supply pipes and other piping that may be encountered and found necessary to disconnect or cut, shall be effectually stopped off or grubbed up and removed, and any new connections that may be necessary shall be made with proper fittings, to the satisfaction of the Principal Agent | | | |
| | Hazardous materials: | | | |
| | Demolitions of buildings, services, external works, site services, etc are to include for the safe removal and disposal of <u>asbestos or asbestos products or other</u> <u>hazardous materials</u> by approved Registered Specialists | | | |
| | | | | |
| | REMOVAL OF EXISTING WORK | | | |
| | Breaking up and removing: | | | |
| 1 | Taking out and removing, grubbing up concretefoundations and concrete to toilet pits not exceeding1500mm deep, filling in holes with imported earth filling,compacted to 93% Mod AASHTO density to existing5000 x 2000mm toilet structuresNo | 3 | | |
| | DEMOLITIONS, ETC | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 2 Bill No. 1 Alterations | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

Rev.06

| | Brought Forward | | | R | |
|---|--|-------|---|---|------|
| | Demolish existing toilet structures: | | | P | |
| 2 | Demolish existing pit toilet structure overall size 5000 x 2000 x 3000mm high including desludging waste to municipality waste site, hacking and removing foundations, concrete surface beds, walls, doors, windows, door frames, ironmongery, zink, plumbing fittings complete, backfilling, compacting and clear debris and etc.Service Provider to submit relevant and valid permit of disposal to the municipal waste and all rubble's to be carted away from site. | No | 3 | | |
| 3 | Demolish existing pit toilet structure overall size 4800 x 3800 x 3000mm high including desludging waste to municipality waste site, hacking and removing foundations, concrete surface beds, walls, doors, windows, door frames, ironmongery, zink, plumbing fittings complete, backfilling, compacting and clear debris and etc. Service Provider to submit relevant and valid permit of disposal to the municipal waste and all rubble's to be carted away from site. | No | 4 | | |
| | CHEMICAL TOILETS RENTALS | | | | |
| | The following is for the rental of chemical toilets: | | | | |
| 4 | Temporary chemical toilets (12No) for a period of original construction (site handover date to original practical completion date) up to approved extension of time including all servicing necessary as per standards. All servicing of the temporary chemical toilets on late completion of works by contractor till actual practical completion date, all costs will be on the contractor's account. | | | | |
| | | MNTHS | 5 | | |
| | | | | | |
| | | | | | |
| | Carried to Final Summary | | | R | |
| | Section No. 2 Bill No. 1 Alterations | | | | — |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Quantity | Rate | Amou |
|--|----------|------|------|
| SECTION NO. 3 | | | |
| BILL NO.1 | | | |
| ALTERATIONS (PROVISIONAL) | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition), as published by the Association of South African Quantity Surveyors, shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items, fully described in the said General Preambles, will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| View Site: | | | |
| Before submitting his tender, the Contractor shall visit the site and satisfy himself as to the nature and extent of the work to be done and the value of the materials contained in the buildings or portions of the buildings to be demolished. No claim for any variations of the contract sum in respect of the nature and extent of the work or of inferior or damaged materials will be entertained | | | |
| Old materials to become property of the Contractor: | | | |
| Old materials from demolitions, except where described as to be re-used or handed over, become the property of the Contractor, who must allow credit for same in the last item of the "Demolitions" trade | | | |
| Carried Forward | | R | |
| Section No. 3 Bill No. 1 Alterations | | | |
| Diatho Consulting (PTY) LTD | | | |

R

R

Brought Forward

Old materials to be re-used:

None of the old materials are to be used for new work, except where specifically described as being set aside for re-use

Old materials, debris, etc to be carted away:

All old materials from the demolitions, except where described as to be re-used or handed over, as well as all rubbish, debris, etc must be regularly carted from the site and not be allowed to accumulate on or around the site

Handing over of materials:

Where certain materials or articles from demolitions are described as to be "handed over to the Employer", it shall be taken to mean "handed over by the Contractor to the Principal Agent" and such materials or articles shall be properly stored by the Contractor until handing over thereof and shall include all necessary transport

The Contractor must obtain an official receipt from the Principal Agent listing the materials or articles and dates of handing over

Should the Contractor fail to submit the receipt when requested to do so, it shall be deemed that the materials or articles are still in his possession and he will be held liable to the Employer for the full replacement value thereof, which amount will be deducted from any monies due to the Contractor

Explosives:

No explosives whatsoever may be used for demolition purposes, unless otherwise stated

Carried Forward

Section No. 3 Bill No. 1 Alterations

R

R

Brought Forward

General:

The Contractor shall carry out the whole of the works with as little mess and noise as possible and with a minimum of disturbance to adjoining premises and their tenants. He shall provide proper protection and provide, erect and remove when directed, any temporary tarpaulins that may be necessary during the progress of the works, all to the satisfaction of the Principal Agent

Water supply pipes and other piping that may be encountered and found necessary to disconnect or cut, shall be effectually stopped off or grubbed up and removed, and any new connections that may be necessary shall be made with proper fittings, to the satisfaction of the Principal Agent

Hazardous materials:

Demolitions of buildings, services, external works, site services, etc are to include for the safe removal and disposal of <u>asbestos or asbestos products or other</u> <u>hazardous materials</u> by approved Registered Specialists

GENERAL

The contractor shall carry out the whole of the work with as little mess and noise as possible and with a minimum of disturbance to adjoining premises and their tenants. He shall provide proper protection and provide and erect any temporarytarpaulins and temporary plumbing that may be necessary during the progress of the works, all to the satisfaction of the Architect, and remove when directed.

Any water supplies pipes and other piping that may be met withand found necessary to disconnect or cut, shall be effectually stopped of or grubbed up and removed, and any new connections that may be necessary shall be made with proper fittings, to the satisfaction of the

Carried Forward

Section No. 3 Bill No. 1 Alterations

R

R

| Drou | ~ 64 | Eam | ~ ~ ~ |
|------|------|------|--------------|
| Brou | qnt | FOLM | aru |

Architect.

Doors, fanlights, fittings, frames, linings, etc shall be thoroughly overhauled before re-fixing including taking off, easing and rehanging, cramping up, re-wedging as required and making good cramps, dowels, etc and easing, oiling, adjusting and repairing ironmongery if necessary, replacing any glass damaged in removal or subsequently and stopping up all nail and screw holes with tinted wood to match timber.

Where doors, windows, etc are described as taken out this shall be understood to include for removal of all beads, architraves, ironmongery, etc and doors which are re-fixed are to be provided with new architraves (elsewhere measured).

Prices for taking out and removing doors and frames shall include for removing door stops, cabin locks, etc and making good to match existing.

With regard to building up openings in existing walls, cement screeds and pavings, granolithic, etc, shall be levelled and prepared for raising of brickwork.

Allow for making good all existing plastered walls where damaged by furniture, etc, and stopping up all screw and holes before painting.

Making good finishes shall be deemed to iclude making good of the brick and concrete surfaces onto which new finishes are applied, where necessary.

The contractor will be required to take all dimensions affecting existing building on the site and he will be held solely responsible for the accuracy of all such dimensions

Hazardous materials:

Demolitions of buildings, services, external works, site services, etc are to include for the safe removal and disposal of asbestos or asbestos products or other hazardous materials by approved Registered Specialist

Carried Forward

Section No. 3 Bill No. 1 Alterations

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | | | | | |
| | TEMPORARY BARRIERS, SCREENS, ETC | | | | |
| | Temporary barriers, screens, etc including removal: | | | | |
| 1 | "Joluka Orange/ Yellow" or similar approved safety barrier netting 1500mm high including suitable timber framing, corners, ends, etc | m | 42 | | |
| | REMOVAL OF EXISTING WORK | | | | |
| | Breaking up and removing reinforced concrete, including cutting off and removing reinforcement: | | | | |
| 2 | Concrete toilet seats | m2 | 3 | | |
| 3 | 150mm Thick surface beds | m2 | 3 | | |
| | Carefully taking out and handing over to the Employer doors, windows, etc including taking out and removing thresholds, sills, etc from brickwork and preparing openings to receive new similar doors, windows, etc (elsewhere measured) and making good cement plaster on both sides and into reveals: | | | | |
| 4 | Timber single door and frame not exceeding 2,5m ² | No | 4 | | |
| | Taking out/off and removing ironmongery: | | | | |
| 5 | Window stays | No | 5 | | |
| 6 | Window handles | No | 5 | | |
| 7 | Taking out and removing piping, sanitary fittings, etc including cutting off as necessary, disconnecting piping from fittings and blocking off and making good damaged plasterwork to walls and screeds to floors (all redecoration work elsewhere):Vitreous china wall hung urinal with flush valve | No | 4 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 3 Bill No. 1 Alterations | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | I | I | R | I |
|----|---|----|----|---|---|
| | Taking out/off and removing glass and mirrors: | | | | |
| 8 | Glass panes not exceeding 0,1m ² from steel windows with putty, including cleaning out rebates and preparing for new glass | m2 | 10 | | |
| | MAKING GOOD OF FINISHES, ETC | | | | |
| | Making good untinted granolithic | | | | |
| 9 | 25mm Thick on floors in patches | m2 | 32 | | |
| | Making good internal/external cement plaster: | | | | |
| 10 | Walls in patches | m2 | 23 | | |
| | Wash down thorougly with sugarsoap and remove all stains, paint marks, etc, repoint and re-mortar joints as required on existing | | | | |
| 11 | Face brick work | m2 | 43 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | | | R | |
| | Section No. 3 Bill No. 1 | | | | |
| | Alterations | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | | | | |
| | Carried Forward Section No. 3 Bill No. 2 Concrete, Formwork and Reinforcement | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | | 1.00.00 |
|--|---|---------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 3 Bill No. 2 Concrete, Formwork and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | | | R | |
|---|--|------|-----|---|--|
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 25MPa/19mm concrete: | | | | |
| 1 | Aprons cast in panels | m3 | 12 | | |
| | TEST BLOCKS | | | | |
| 2 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional | Sets | 1,0 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a wood float: | | | | |
| 3 | Ramps to falls | m2 | 5 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 4 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 20 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 5 | Not exceeding 300mm high to edges of surface beds | m | 20 | | |
| | REINFORCEMENT (PROVISIONAL | | | | |
| | Fabric reinforcement: | | | | |
| 6 | Type 193 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 80 | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 Section No. 3 Bill No. 2 Concrete, Formwork and Reinforcement | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | P | |
| | BILL NO.3 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | DAMPPROOFING OF WALLS AND FLOORS | | | |
| | | | | |
| | Carried Forward | | R | |
| | Bill No. 3 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| | One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape: | | | | |
| 1 | Under aprons | m2 | 80 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 Section No. 3 | | | R | |
| | Bill No. 3 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.4 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 3 Bill No. 4 Capentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|--|----|----|---|--|
| Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
| Particle board | | | | |
| All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| Decorative thermosetting plastic laminate covering: | | | | |
| Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| <u>Sizes:</u> | | | | |
| Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| <u>Prices</u> | | | | |
| Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | |
| ROOFS, ETC | | | | |
| Sundries: | | | | |
| Two coats creosote on sawn timbers | m2 | 80 | | |
| EAVES, VERGES, ETC | | | | |
| | | | | |
| | | | | |
| Carried Forward Section No. 3 Bill No. 4 Capentry and Joinery | | | R | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

Rev.06

| | Brought Forward | | | R | |
|---|---|----|----|---|------|
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 2 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 18 | | |
| | DOORS, ETC | | | | |
| | <u>Semi-solid core flush panel timber door with</u> <u>hardboard edging, face suitable for paint on both</u> <u>sides, hung to steel frames</u> | | | | |
| 3 | 44 x 762 x 1882mm high | No | 4 | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 4 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard | No | 2 | | |
| | weatherboard | NO | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | | | R | |
| | Section No. 3 Bill No. 4 Capentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.5 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 3 Bill No. 5 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 2 | | |
| | LOCKS | | | | |
| | Approved: | | | | |
| 2 | 50mm Padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| 4 | Indicator lockset | No | 2 | | |
| | Carried Forward Section No. 3 Bill No. 5 | | | R | |
| | Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|---|--|----|---|---|------|
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | 75 x 150mm Natural anodised aluminium plate with male or female symbol | No | 2 | | |
| 6 | "Ref. SS5066E-06SSE14" stainless steel pictogram engraved with a disabled sign | No | 2 | | |
| | SUNDRIES | | | | |
| 7 | 25mm Diameter wall mounted door stop plugged | No | 6 | | |
| | BATHROOM FITTINGS | | | | |
| | "Kimberley-Clark"or similar approved: | | | | |
| 8 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 4 | | |
| 9 | Brushed stainless steel body, rust resistant, she bin, approximately 330 x 280 x 180mm etc | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | | | R | |
| | Section No. 3 Bill No. 5 | | | | |
| | Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.6 | | | |
| | <u>METALWORK</u> | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 3 Bill No. 6 Metalwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Drought Forward | | l D | 1 1 | |
|---|--|-----|-----|---|
| Brought Forward | | ĸ | | |
| Fixing: | | | | |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | | |
| References: | | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | | |
| • 21111/FSPS/S005 | | | | |
| and bound into the back of these bills of quantities | | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | | |
| | | | | I |
| | | | | |
| | | | | I |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | |
| | | | | I |
| | | | | |
| Carried Forward | | R | | |
| Section No. 3 Bill No. 6 Metalwork | | | | |
| | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | 1 |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Welded screens and gates, to brickwalls: Single gate and frame 813 x 2032mm high of 25 x 25 x 2mm hollow section frame and 25 x 25 x 2mm hollow section horizontal middle rail filled in with 12 x 12mm square section vertical rails at 75mm centers and fitted with a pair of suitable hinges welded to frame and with locking mechanism for padlock all in and including outer frame of 25 x 25 x 2mm hollow section welded frame bolted to brickwor | No | 2 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | | | R | |
| | Section No. 3 Bill No. 6 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | P | |
| | BILL NO.7 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 3 Bill No. 7 Plastering | | ĸ | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 3 Bill No. 7 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Duesse | | - | |
|--------|-----|----------|------|
| Broug | int | FOR | ward |
| | | | |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 3 Bill No. 7 Plastering

Diatho Consulting (PTY) LTD

| Brought Forward | | | R | |
|--|----|----|---|--------------|
| TINTED WHITE CEMENT SCREEDS | | | | |
| Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| Coarse sand is to be used for these screeds | | | | |
| All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| CEMENT PLASTER | | | | |
| Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | |
| FLOOR AND WALL SEALERS | | | | |
| Minimum two coats approved epoxy coat, on concrete: | | | | |
| On screed | m2 | 80 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | - |
| Carried Forward to Summary of Section No. 3 Section No. 3 | | | R | <u> </u> |
| Bill No. 7 Plastering | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.8 | | | |
| | <u>PLUMBING AND DRAINAGE</u> (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | Carried Forward Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) Diatho Consulting (PTY) LTD | | R | |

| | | • |
|--|---|---|
| Brought Forward | R | 1 |
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 3 Bill No. 8 Plumbing and drainage(Provisional)

Diatho Consulting (PTY) LTD

| Brought Forward | к | |
|---|---|--|
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| | | |
| Carried Forward Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward R | |
|---|--|
| General: | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | |
| As-built drawings: | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | |
| | |
| Carried Forward R Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) Image: Consulting (PTY) LTD | |
| | |
| 22 | |

| | Brought Forward | | | R | |
|---|--|----|---|---|--|
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | SANITARY FITTINGS | | | | |
| | "Vaal" or similar approved: | | | | |
| 1 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 3 | | |
| 2 | Flat back urinal overall size 295 x 315 x 415mm high with 40mm chromium plated domical grating (Code 878720) and top inlet spreader (Code 8543) with two hanger brackets with flushmaster junior (Code 812720) hung to wall | No | 2 | | |
| | Supply and install "Enviroloo systems" or similar approved: | | | | |
| 3 | "Enviro Loo System FG-1040 STDCA/A Standard" strictly in accordance with manufacturers instructions, unit comprising of top unit and two x louvered inlets (PL.1), drying plate (PL.2), two x air inlets (PL.3), toilet pan, seat and lid (PL.4), 3500mm long outlet vent pipe (PL.5), ventilation extraction unit (PL.6) fixed to wall with vent wall bracket (PL.7), 1 bag mounting screws and organic starter, enzyme and toilet cleaner (PL.8) including all necessary interconnector piping between multiple tanks, emergency outlet piping, et | No | 4 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | | | ĸ | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | | | | | Rev.06 |
|----|--|----|---|----|--------|
| | Brought Forward | | | R | |
| 4 | "Enviro Loo Urinal Evaporative Tank System code FG B62B" strictly in accordance with manufacturers instructions, unit comprising of urinal evaporative tank (PL.1), urinal bowl (PL.5), 3500mm long outlet vent pipe (PL.3), ventilation extraction unit (PL.3) fixed to wall with vent wall bracket (PL.4), 1 bag mounting screws and organic starter, enzyme and toilet cleaner (PL.8) including all necessary piping, traps, etc | No | 2 | | |
| | Precast concrete wash trough | | | | |
| 5 | Standard SABS approved Pre-Cast Concrete Double Wash Trough, 1080 x 650 x 850mm high with support legs fitted with standard 3/4 Brass Garden Taps, including all necessary pipework including soak away approximately 10 meters away from the wash trough, sized at 1000 x 1000 x 1000mm covered with "bidim" complete etc | No | 1 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 6 | 50mm Code 365 CP bottle trap | No | 5 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 7 | 19mm chrome plated push button taps to wash troughs | No | 1 | | |
| 8 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 4 | | |
| 9 | 15mm Code 503-21CP elbow action pillar tap | No | 3 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 10 | 50mm Pipes | m | 5 | | |
| | | | | | |
| | Carried Forward Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | I | ll | I |

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| 11 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 5 | | |
| | Extra over uPVC pipes for fittings: | | | | |
| 12 | 50mm Bend | No | 4 | | |
| 13 | 50mm Junction | No | 2 | | |
| 14 | 50mm Junction with cleaning eye and lid | No | 2 | | |
| 15 | 110mm "GI Two-way" vent valve | No | 4 | | |
| | Testing: | | | | |
| 16 | Testing waste pipe system | | Item | | |
| | WATER SUPPLIES | | | | |
| | <u>Class 16 uPVC pressure pipes with solvent welded</u> joints: | | | | |
| 17 | 32mm Pipes laid in and including trenches not exceeding 1m deep | m | 30 | | |
| 18 | 50mm Pipes laid in and including trenches not exceeding 1m deep | m | 30 | | |
| | Extra over class 16 uPVC pressure pipes for fittings with solvent welded joints: | | | | |
| 19 | 32mm Bend | No | 6 | | |
| 20 | 32mm Reducer | No | 2 | | |
| 21 | 32mm Tee | No | 4 | | |
| 22 | 50mm Bend | No | 6 | | |
| 23 | 50mm Tee | No | 4 | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 3 Bill No. 8 Plumbing and drainage(Provisional) | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| I | Brought Forward | | I | R | |
|----|--|----|------|---|-----------|
| | Class 1 copper pipes with capillary couplings: | | | | |
| 24 | 15mm Pipe fixed to walls, in chases, etc | m | 20 | | |
| 25 | Ditto, but 22mm diameter | m | 20 | | |
| | Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 26 | 15mm Fittings | No | 4 | | |
| 27 | 22mm Fittings | No | 4 | | |
| | Testing: | | | | |
| 28 | Testing water pipe system | | ltem | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | | | R | \square |
| | Section No. 3 | | | N | ╞ |
| | Bill No. 8 Plumbing and drainage(Provisional) | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.9 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Float glass: | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | TOPS, SHELVES, DOORS, MIRRORS, ETC | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 3 | | R | |
| | Bill No. 9 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | R | |
|---|--|----|---|--|
| | <u>4mm Silvered float glass copper backed mirrors</u> with 10mm bevelled and polished edges fixed with double sided adhesive tape: | | | |
| 1 | Stainless steel mirror size 350 x 400m plugged to wall with chrome platted screws No | 2 | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | 6,38mm Obscure safety glass: | | | |
| 2 | Panes not exceeding 0,1m ² m2 | 10 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 3 | | R | |
| | Section No. 3 Bill No. 9 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 3 | | | |
| | BILL NO.10 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 3 Bill No. 10 Paintwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

-87-

| Brought Forward | | | R | |
|---|----|---|---|--|
| Previously painted wood surfaces: | | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | | |
| PAINT SPECIFICATIONS | | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | | |
| COLOURS | | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | | |
| | | | | |
| PAINTWORK, ETC TO NEW WORK | | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | | |
| Fascias and barge boards, including priming metal jointing strips | m2 | 9 | | |
| METAL SURFACES WITH | | | | |
| | | | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 3 Bill No. 10 Paintwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| | Brought Forward | ı | | R | |
|---|--|----|----|---|--|
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 3 | Extra over for paintwork in the "Deep" colour group | m2 | 7 | | |
| | ON WOOD SURFACES | | | | |
| | One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: | | | | |
| 4 | Doors | m2 | 25 | | |
| 5 | Extra over for paintwork in the "pastel" colour group | m2 | 24 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 3 | 6 | | R | |
| | Section No. 3 Bill No. 10 Paintwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| Bill No | SECTION SUMMARY - Refurbishment of 4 Enviro-loo seats(Edu | <u>cators)</u> Page No | | Amount |
|------------|--|------------------------------|---|--------|
| 1 | Alterations | 56 | | |
| 2 | Concrete, Formwork and Reinforcement | 59 | | |
| 3 | Waterproofing | 61 | | |
| 4 | Capentry and Joinery | 64 | | |
| 5 | Ironmongery | 67 | | |
| 6 | Metalwork | 70 | | |
| 7 | Plastering | 74 | | |
| 8 | Plumbing and drainage(Provisional) | 84 | | |
| 9 | Glazing | 86 | | |
| 10 | Paintwork | 89 | | |
| | Carried to Final Summary Section No. 3 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount | |
|------------|---|----------|------|--------|---|
| | SECTION NO. 4 | | | | |
| | BILL NO.1 | | | | |
| | EARTHWORKS (PROVISIONAL) | | | | |
| | | | | | |
| | PREAMBLES | | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | | |
| | SUPPLEMENTARY PREAMBLES | | | | |
| | Nature of ground | | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | | |
| | | | | | |
| | Carried Forward | | R | | - |
| | Section No. 4 Bill No. 1 Earthworks | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

R

| Bro | ugh | t Fo | rwa | rd |
|-----|------------|------|-----|----|
| | ~ <u>9</u> | | | |

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 4 Bill No. 1 Earthworks

Diatho Consulting (PTY) LTD

R

| | Brought Forward | | | R | |
|---|---|----|-----|---|--|
| | Filling | | | | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 3 | | |
| 2 | Trenches | m3 | 8 | | |
| 3 | Trenches and holes for thickening under surface beds, etc | m3 | 2 | | |
| 4 | Pit | m3 | 30 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 5 | Soft rock | m3 | 1 | | |
| 6 | Hard rock | m3 | 0,5 | | |
| | Extra over all excavations for carting away: | | | | |
| 7 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 12 | | |
| | | | | | |
| | Carried Forward Section No. 4 Bill No. 1 Earthworks | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Risk of collapse of excavations: | | | | |
| 8 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 28 | | |
| | Keeping excavations free of water: | | | | |
| 9 | Keeping excavations free of all water other than subterranean water | | ltem | | |
| | FILLING ETC | | | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 10 | Backfilling to trenches, holes, etc | m3 | 3 | | |
| | G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: | | | | |
| 11 | Under floors, steps, pavings, etc | m3 | 3 | | |
| | Compaction of surfaces: | | | | |
| 12 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 32 | | |
| | Prescribed density tests on filling: | | | | |
| 13 | "Modified AASHTO Density" test | No | 4 | | |
| | SOIL POISONING | | | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 14 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 32 | | |
| | Operational Foreward | | | P | |
| | Carried Forward Section No. 4 Bill No. 1 Earthworks | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|---|----|---|--|
| 15 | To bottoms and sides of trenches, etc m2 | 44 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 4 | | R | |
| | Section No. 4 Bill No. 1 Earthworks | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | Corried Ferryard | | Р | |
| | Carried Forward Section No. 4 Bill No. 2 Concrete, Formwork and Reinforcement | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | | NOV. | |
|--|---|------|--|
| Brought Forward | R | | |
| Lightweight concrete: | | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | | |
| Waterproof concrete: | | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | | |
| Formwork: | | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | | |
| | | | |
| Carried Forward Section No. 4 Bill No. 2 Concrete, Formwork and Reinforcement | R | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | |

| | Brought Forward | | | R | |
|---|--|------|-----|---|----------|
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 2 | | |
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| 2 | Strip footings | m3 | 3 | | |
| 3 | Surface beds on waterproofing | m3 | 4 | | |
| 4 | Surface beds in tank bottoms | m3 | 3 | | |
| 5 | Aprons cast in panels to falls | m3 | 2 | | |
| | TEST BLOCKS | | | | |
| 6 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | Sets | 2,0 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 7 | Surface beds, slabs, etc | m2 | 23 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 8 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 47 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | | | | | <u> </u> |
| | Carried Forward Section No. 4 Bill No. 2 Concrete, Formwork and Reinforcement | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 9 | Not exceeding 300mm high to edges of surface beds | m | 57 | | |
| | Saw-cut joints: | | | | |
| 10 | 6 x 10mm Saw-cut joints in top of concrete | m | 10 | | |
| | REINFORCEMENT (PROVISIONAL) | | | | |
| | Mild steel reinforcement to structural concrete work: | | | | |
| 11 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,08 | | |
| | High tensile steel reinforcement to structural concrete work: | | | | |
| 12 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,18 | | |
| | Fabric reinforcement: | | | | |
| 13 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 23 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Ferward to Summary of Section No. 4 | | | R | |
| | Carried Forward to Summary of Section No. 4 Section No. 4 | | | ĸ | |
| | Bill No. 2 Concrete, Formwork and Reinforcement | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 3 Masonry | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|---|----|----|---|--|
| Hollow walls: | | | | |
| Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| Bagged and sealed walls: | | | | |
| Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| Face bricks : | | | | |
| Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| Pointing: | | | | |
| Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | |
| FOUNDATIONS (PROVISIONAL) | | | | |
| Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| One brick walls | m2 | 14 | | |
| 2,5mm Brickwork reinforcement: | | | | |
| 150mm Wide reinforcement built in horizontally | m | 69 | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 4 Bill No. 3 Masonry | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | I | R | |
|----|---|----|-----|---|--|
| | FACE BRICKWORK | | | | |
| | <u>Face bricks (Allow a Prime Cost Amount of R5</u> 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 5 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 65 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 59 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 133 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 216 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 31 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 33 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 131 | | |
| | | | | | |
| | Carried Forward Section No. 4 Bill No. 3 Masonry | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 7 | | |
| 12 | Fair raking cutting | m | 10 | | |
| | Brick-on-edge header course coping, sills, etc. of face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 7 | R | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| - | SECTION NO. 4 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | <u>One layer 375 micron embossed polyethylene</u> dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 67 | | |
| 2 | In walls vertically at reveals | m2 | 3 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 27 | | |
| | JOINT SEALANTS ETC | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 10 | | |
| | <u>White silicone sealing compound including backing</u> cord, bond breaker, primer, etc | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 57 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 4 | | | R | |
| | Section No. 4 Bill No. 4 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | Carried Forward Section No. 4 Bill No. 5 Roofcovering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 40 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 8 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at | | | | |
| | edges where required | m2 | 40 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 4 Section No. 4 Bill No. 5 Roofcovering | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.6 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 6 Capentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
|---|--|---|----|---|--|
| | Particle board | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| | <u>Sizes:</u> | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| | Prices | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | | |
| | ROOFS, ETC | | | | |
| | Sawn softwood grade 5: | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 16 | | |
| | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 52 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 4 Bill No. 6 Capentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

TMT-LDOE-2023/24-LPCL23/02D Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| 3 | 50 x 76mm Purlins | m | 53 | | |
| | EAVES, VERGES, ETC | | | | |
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 20 | | |
| | DOORS, ETC | | | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 5 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm undercut (D2) | No | 7 | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | | | | |
| | | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 4 | | | R | |
| | Section No. 4 Bill No. 6 Capentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 7 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward | | | R | |
| | Section No. 4 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|---|---|-------|-----|---|--|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 7 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres</u> | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 14 | | |
| | DOOR CLOSER | | | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | "Dorma" or similar approved: | | | | |
| 7 | DSS-131 Engraved "Female" information sign, plugged | No | 1 | | |
| 8 | DSS-133 Engraved "Disabled" information sign, plugged | No | 1 | | |
| | SUNDRIES | | | | |
| 9 | 25mm Diameter wall mounted door stop plugged | No | 7 | | |
| | BATHROOM FITTINGS | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 4 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|---|---|--|
| | "Kimberley-Clark"or similar approved: | | | | |
| 10 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 7 | | |
| 11 | Brushed stainless steel body, rust resistant, she bin, approximately 330 x 280 x 180mm etc | No | 7 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 4 | | | R | |
| | Section No. 4 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | P | |
| | BILL NO.8 | | | |
| | <u>METALWORK</u> | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward Section No. 4 Bill No. 8 Metalwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | 1 |
|---|---|---|
| Fixing: | | |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | |
| References: | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | |
| • 21111/FSPS/S005 | | |
| and bound into the back of these bills of quantities | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | |
| | | |
| | | |
| | | 1 |
| | | 1 |
| | | 1 |
| | | 1 |
| | | 1 |
| | | 1 |
| | | 1 |
| | | 1 |
| | | |
| Carried Forward Section No. 4 | R | 1 |
| Bill No. 8 Metalwork | | 1 |
| Diatho Consulting (PTY) LTD | | |
| | | 1 |

| | Brought Forward | | | R | |
|---|--|----|---|---|---|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 7 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 2 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 4 | Window type NE1, 533 x 654mm high (N1) | No | 7 | | |
| 5 | Window type NE7, 1022 x 654mm high (N2) | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | - |
| | Carried Forward to Summary of Section No. 4 | | | R | |
| | Section No. 4 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 9 Plastering | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 4 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought Forwar | - |
|----------------|---|
| | α |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 4 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|---|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 23 | | |
| | SPECIAL FLOOR COATING | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 23 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 4 | | | R | |
| | Section No. 4 Bill No. 9 Plastering | | | | _ |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.10 | | | |
| | <u>PLUMBING AND DRAINAGE</u> (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | |
|--|---|--|
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| | | |
| Carried Forward Section No. 4 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 4 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 4 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| | | 1 |
|---|---|---|
| Brought Forward | R | |
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| | | |
| Carried Forward | R | |
| Section No. 4 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|---|-----|-----|
| <u>General:</u> | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| | | |
| Carried Forward Section No. 4 Bill No. 10 Plumbing and Drainage Diatho Consulting (PTY) LTD | R | |
| | | |
| | 1 1 | I I |

| | | | | | 1.64.00 |
|---|--|----|---|---|---------|
| | Brought Forward | | | R | |
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 1 | 150 x150mm Box gutters | m | 9 | | |
| 2 | 100 x 75mm Rainwater pipes | m | 5 | | |
| 3 | Extra over gutter for stopped end | No | 2 | | |
| 4 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | |
| 5 | Extra over rainwater pipe for bend | No | 2 | | |
| 6 | Extra over rainwater pipe for shoe | No | 2 | | |
| 7 | Extra over rainwater pipe for eaves or plinth offset | No | 2 | | |
| | SANITARY FITTINGS | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 4 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | I | I | I |

| | | - | | | . . |
|----|---|----|----|---|------------|
| | Brought Forward | | | R | |
| | "Vaal" or similar approved: | | | | |
| 8 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 5 | | |
| 9 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 7 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 10 | 50mm Code 365 CP bottle trap | No | 5 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 11 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 12 | | |
| 12 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 5 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 13 | 50mm Pipes | | | | |
| | | m | 25 | | |
| 14 | 110mm Pipes | m | 35 | | |
| 15 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 33 | | |
| 16 | Ditto, but 110mm diameter | m | 45 | | |
| | | | | | |
| | Carried Forward Section No. 4 Bill No. 10 Plumbing and Drainage | | | R | |
| | | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Fo | rward | | R |
|----|--|-------|------|---|
| | Extra over uPVC pipes for fittings: | | | |
| 17 | 50mm Bend | No | 10 | |
| 18 | 50mm Junction | No | 10 | |
| 19 | 50mm Junction with cleaning eye and lid | No | 10 | |
| 20 | 110mm Straight pan connector | No | 7 | |
| 21 | 110mm Bend | No | 14 | |
| 22 | 110mm Junction | No | 14 | |
| 23 | 110mm Reducing junction | No | 26 | |
| 24 | 110mm Access bend | No | 7 | |
| 25 | 110mm Double junction | No | 24 | |
| 26 | 110mm "GI Two-way" vent valve | No | 13 | |
| | Testing: | | | |
| 27 | Testing waste pipe system | | ltem | |
| | WATER SUPPLIES | | | |
| | Class 1 copper pipes with capillary couplings: | | | |
| 28 | 15mm Pipe fixed to walls, in chases, etc | m | 36 | |
| 29 | Ditto, but 22mm diameter | m | 60 | |
| | Extra over Class 1 copper pipes for capillary fittings: | | | |
| 30 | 15mm Fittings | No | 60 | |
| 31 | 22mm Fittings | No | 60 | |
| | Carried Fo Section No. 4 Bill No. 10 Plumbing and Drainage Diatho Consulting (PTY) LTD | rward | | R |

| Item | | |
|---------------|---------------|---------------|
| Item | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Section No. 4 | R | |
| | | |
| | | |
| | | |
| | Section No. 4 | Section No. 4 |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Float glass:</u> | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 4 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward <u>6,38mm Obscure safety glass:</u> | | R | |
|---|--|-----|---|---|
| 1 | Panes not exceeding 0,1m ² m | 2 4 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 4 | | R | - |
| | Section No. 4 Bill No. 11 Glazing | | | = |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 4 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | Carried Forward Section No. 4 Bill No. 12 | | R | |
| | Paintwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|---|----|---|---|--|
| Previously painted wood surfaces: | | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | | |
| PAINT SPECIFICATIONS | | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | | |
| COLOURS | | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | | |
| | | | | |
| PAINTWORK, ETC TO NEW WORK | | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | | |
| Fascias and barge boards, including priming metal jointing strips | m2 | 5 | | |
| METAL SURFACES WITH | | | | |
| | | | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 4 Bill No. 12 Paintwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| | | <u>-</u> | <u>.</u> | | _ |
|---|---|----------|----------|----|---|
| | Brought Forward | | | R | |
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Door frames | m2 | 17 | | |
| 3 | Windows | m2 | 9 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 32 | | |
| | ON WOOD SURFACES | | | | |
| | <u>One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on:</u> | | | | |
| 6 | Doors | m2 | 32 | | |
| 7 | Roof timbers at eaves and verges | m2 | 34 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 65 | | |
| | Carried Forward to Summary of Section No. 4 Section No. 4 Bill No. 12 Paintwork | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | I | I | II | I |

| Bill | SECTION SUMMARY - SFD5 Female Educators Ablutions | Page | | Amount |
|----------------|--|-----------------|---|--------|
| No 1 | Earthworks | No 95 | | |
| 2 | Concrete, Formwork and Reinforcement | 99 | | |
| 3 | Masonry | 103 | | |
| 4 | Waterproofing | 105 | | |
| 5 | Roofcovering | 107 | | |
| 6 | Capentry and Joinery | 110 | | |
| 7 | Ironmongery | 114 | | |
| 8 | Metalwork | 117 | | |
| 9 | Plastering | 121 | | |
| 10 | Plumbing and Drainage | 131 | | |
| 11 | Glazing | 133 | | |
| 12 | Paintwork | 136 | | |
| | Carried to Final Summary Section No. 4 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 1 Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

| Brou | Jaht | For | wai | rd |
|------|------|-----|-----|----|
| | | | | |

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 5 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|----|----------|--|
| | Filling | | | <u>p</u> | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 5 | | |
| 2 | Trenches | m3 | 10 | | |
| 3 | Pit | m3 | 30 | | |
| 4 | Trenches and holes for thickening under surface beds, etc | m3 | 2 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 5 | Soft rock | m3 | 1 | | |
| 6 | Hard rock | m3 | 1 | | |
| | Extra over all excavations for carting away: | | | | |
| 7 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 14 | | |
| | Carried Forward | | | R | |
| | Section No. 5 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| Risk of collapse of excavations: 35 8 Sides of trench and hole excavations not exceeding 1.5m deep m2 35 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 10 Backfilling to trenches, holes, etc m3 3 11 Under floors, steps, pavings, etc m3 5 12 Compaction of ground surface under floors etc including scarting for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 < | | Brought Forward | | | R | |
|---|----|---|----|------|---|--|
| 1,5m deep m2 35 9 Keeping excavations free of water: subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item FILLING ETC Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: 10 10 Backfilling to trenches, holes, etc m3 3 25 G5 filling material supplied by the contractor, compacted to 93% Mod AASHTO density: 11 11 Under floors, steps, pavings, etc m3 5 26 Compaction of ground surface under floors etc including scartifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 13 "Modified AASHTO Density" test No 5 13 "Modified AASHTO Density" test No 5 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R Earthwork | | Risk of collapse of excavations: | | | | |
| 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 9 Keeping excavations free of all water other than subterranean water Item 10 Backfilling to trenches, holes, etc m3 3 10 Backfilling material supplied by the contractor. compacted to 95% Mod AASHTO density: m3 5 11 Under floors, steps, pavings, etc m3 5 12 Compaction of ground surfaces under floors etc including scathym ground oversize material, adding sutable material where necessary and compacting to 91% Mod AASHTO maxing own oversize material, adding sutable material where necessary and compacting to 91% Mod AASHTO and the material where necessary and compacting to 91% Mod AASHTO and the material where necessary and compacting to 91% Mod floor may and the postend of floore, etc. including forming and poster mater | 8 | | m2 | 35 | | |
| subterranean water Item FILLING ETC Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: 3 10 Backfilling to trenches, holes, etc m3 3 25 G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: | | Keeping excavations free of water: | | | | |
| Earth filling material supplied by the contractor, compacted to 93%, Mod AASHTO density: 3 10 Backfilling to trenches, holes, etc m3 3 11 Under floors, steps, pavings, etc m3 5 12 Compaction of surfaces: 1 12 Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 13 "Modified AASHTO Density" test No 5 14 Soil insecticide in accordance with SANS 5859: 1 5 14 Soil insecticide (protection against termites) applied as specified under floors, etc including grand poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R | 9 | | | ltem | | |
| prescribed stock piles on site, compacted to 93% 3 10 Backfilling to trenches, holes, etc m3 3 25 5111ing material supplied by the contractor, compacted to 95% Mod AASHTO density: m3 5 11 Under floors, steps, pavings, etc m3 5 Compaction of surfaces: 12 Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO m2 41 Prescribed density tests on filling: 13 "Modified AASHTO Density" test No 5 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R E E | | FILLING ETC | | | | |
| G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: m3 11 Under floors, steps, pavings, etc m3 12 Compaction of surfaces: 12 12 Compacting for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 13 "Modified AASHTO Density" test No 13 "Modified AASHTO Density" test No 50il insecticide in accordance with SANS 5859: 14 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R | | prescribed stock piles on site, compacted to 93% | | | | |
| compacted to 95% Mod AASHTO density: 11 Under floors, steps, pavings, etc m3 5 Compaction of surfaces: | 10 | Backfilling to trenches, holes, etc | m3 | 3 | | |
| Compaction of surfaces: 12 Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 Prescribed density tests on filling: m2 41 13 "Modified AASHTO Density" test No 5 Soil Insecticide in accordance with SANS 5859: 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R | | <u>G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density:</u> | | | | |
| 12 Compaction of ground sufface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 Prescribed density tests on filling: m2 41 13 "Modified AASHTO Density" test No 5 SOIL POISONING Soil insecticide in accordance with SANS 5859: 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R Retrink Forward | 11 | Under floors, steps, pavings, etc | m3 | 5 | | |
| scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density m2 41 Prescribed density tests on filling: 13 "Modified AASHTO Density" test No 5 <u>SOIL POISONING</u> <u>Soil insecticide in accordance with SANS 5859:</u> 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 <u>Carried Forward</u> R Section No. 5 Bill No. 1 Earthwork | | Compaction of surfaces: | | | | |
| Prescribed density tests on filling: No 13 "Modified AASHTO Density" test No 5 SOIL POISONING 5 Soil insecticide in accordance with SANS 5859: 5 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 R Earthwork R R | 12 | scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO | m2 | 41 | | |
| SOIL POISONING Soil insecticide in accordance with SANS 5859: 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming multiple floor Multiple floor Carried Forward R Section No. 5 Bill No. 1 Earthwork | | Prescribed density tests on filling: | | | | |
| 14 Soil insecticide in accordance with SANS 5859: 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R Section No. 5 Bill No. 1 Earthwork | 13 | "Modified AASHTO Density" test | No | 5 | | |
| 14 Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R Section No. 5 Bill No. 1 Earthwork | | SOIL POISONING | | | | |
| specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming m2 41 Carried Forward R Section No. 5 Bill No. 1 Earthwork | | Soil insecticide in accordance with SANS 5859: | | | | |
| Section No. 5 Bill No. 1 Earthwork | 14 | specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc | m2 | 41 | | |
| Bill No. 1 Earthwork | | Carried Forward | | | R | |
| Diatho Consulting (PTY) LTD | | Section No. 5 Bill No. 1 | | | | |
| | | Diatho Consulting (PTY) LTD | | | | |
| | | | | | | |

| | Brought Forward | | R | | |
|----|---|----|---|--|--|
| 15 | To bottoms and sides of trenches, etc m2 | 53 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | R | | |
| | Section No. 5 Bill No. 1 | | | | |
| | Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 2 Concrete,Formwork, and Reincforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R R | |
|--|-----|--|
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 5 Bill No. 2 Concrete,Formwork, and Reincforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | | R | |
|---|--|---|---|--|
| | EXCAVATED SURFACES | | | |
| | 15MPa/19mm concrete: | | | |
| 1 | Surface blinding under footings and bases m3 | 1 | | |
| | Carried Forward Section No. 5 Bill No. 2 Concrete,Formwork, and Reincforcement Diatho Consulting (PTY) LTD | | R | |

| | Brought Forward | ı | | R | |
|---|---|----|----|---|--|
| I | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| | Strip footings | m3 | 4 | | |
| | Surface beds on waterproofing | m3 | 5 | | |
| 2 | Surface beds in tank bottoms | | | | |
| | | m3 | 3 | | |
| 3 | Aprons cast in panels to falls | m3 | 2 | | |
| | TEST BLOCKS | | | | |
| 4 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 3 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 5 | Surface beds, slabs, etc | m2 | 32 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 6 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 59 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 7 | Not exceeding 300mm high to edges of surface beds | m | 72 | | |
| | | | | | |
| | | | | _ | |
| | Carried Forward Section No. 5 Bill No. 2 Concrete,Formwork, and Reincforcement | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----------|--|----|------|---|--|
| 5 | Saw-cut joints: | | | | |
| 6 | 6 x 10mm Saw-cut joints in top of concrete | m | 108 | | |
| <u> </u> | REINFORCEMENT (PROVISIONAL) | | | | |
| 1 | Mild steel reinforcement to structural concrete work: | | | | |
| ſ | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,10 | | |
| | High tensile steel reinforcement to structural concrete work: | | | | |
| | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,22 | | |
| Ē | Fabric reinforcement: | | | | |
| | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 32 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | | R | |
| | Section No. 5 | | | | |
| | Bill No. 2 Concrete,Formwork, and Reincforcement | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 3 Masonry | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | ł | | R | |
|---|----|----|---|--|
| Hollow walls: | | | | |
| Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| Bagged and sealed walls: | | | | |
| Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| Face bricks : | | | | |
| Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| Pointing: | | | | |
| Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | |
| FOUNDATIONS (PROVISIONAL) | | | | |
| Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| One brick walls | m2 | 15 | | |
| 2,5mm Brickwork reinforcement: | | | | |
| 150mm Wide reinforcement built in horizontally | m | 87 | | |
| | | | | |
| Carried Forward | ł | | R | |
| Section No. 5 Bill No. 3 Masonry | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|----|--|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 5 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 84 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 74 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 133 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 271 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 43 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 33 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 168 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 5 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | ll | |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 9 | | |
| 12 | Fair raking cutting | m | 10 | | |
| | <u>Brick-on-edge header course coping, sills, etc. of face</u> <u>bricks (Allow a Prime Cost Amount of R5</u> <u>500.00/1000 bricks delivered to site excluding VAT)</u> pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 7 | | |
| | Carried Forward to Summary of Section No. 5 Section No. 5 Bill No. 3 Masonry | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| ĺ | Brought Forward | | | R | |
|---|---|----|-----|---|--|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | One layer 375 micron embossed polyethylene dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 83 | | |
| 2 | In walls vertically at reveals | m2 | 3 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 38 | | |
| | JOINT SEALANTS ETC | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 108 | | |
| | <u>White silicone sealing compound including backing</u> cord, bond breaker, primer, etc | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 72 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | | R | |
| | Section No. 5 | | | | |
| | Bill No. 4 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | Carried Forward Section No. 5 Bill No. 5 Roof Covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|------|----|---|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 50 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 10 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at edges where required | m2 | 50 | | |
| | edges where required | 1112 | 50 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | | R | |
| | Section No. 5 Bill No. 5 Roof Covering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.6 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 6 Carpentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | | |
|---|--|---|----|---|-----|--|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | | |
| | Particle board | | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | | |
| | <u>Sizes:</u> | | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | | |
| | Prices_ | | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | | |
| | | | | | | |
| | ROOFS, ETC | | | | | |
| | Sawn softwood grade 5: | | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 20 | | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 64 | | | |
| | | | | | | |
| | Carried Forward | | | R | | |
| | Section No. 5 Bill No. 6 Carpentry and Joinery | | | | | |
| | Diatho Consulting (PTY) LTD | | | | | |
| | | | | | | |
| | | | | • | • I | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| 3 | 50 x 76mm Purlins | m | 66 | P | |
| | EAVES, VERGES, ETC | | | | |
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 20 | | |
| | DOORS, ETC | | | | |
| | Solid chipcore flush doors with hardwood veneer, hung to steel frames: | | | | |
| 5 | 40mm Door 914 x 2032mm high (D3) | No | 1 | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm | | _ | | |
| | undercut (D2) | No | 7 | | |
| 7 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | | | | |
| | | No | 1 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | | R | |
| | Section No. 5 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|----|---|---|---|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 7 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward Section No. 5 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | I | | 1 |

| | Brought Forward | | | R | |
|----|---|-------|-----|---|--|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 7 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres</u> | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 14 | | |
| | DOOR CLOSERS | | | | |
| | <u>"Dorma" or similar approved:</u> | | | | |
| 7 | "Dorma" TS73N/EN3-4 parallel arm door closer delayed closing-push side fitting | No | 1 | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | "Dorma" or similar approved: | | | | |
| 8 | DSS-131 Engraved "Female" information sign, plugged | No | 1 | | |
| 9 | DSS-133 Engraved "Disabled" information sign, plugged | No | 1 | | |
| | SUNDRIES | | | | |
| 10 | 25mm Diameter wall mounted door stop plugged | No | 9 | | |
| | | | | | |
| | Carried Forward Section No. 5 Bill No. 7 Ironmongery Diatho Consulting (PTY) LTD | | | R | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|----|---|---|--|
| | BATHROOM FITTINGS | | | | |
| | "Vaal Paragon" or similar approved | | | | |
| 11 | 32mm Type 9 back grab rail 800mm long plugged | No | 1 | | |
| 12 | 32mm Type 8 side grab rail 900mm girth plugged | No | 1 | | |
| | <u>"Kimberley-Clark"or similar approved:</u> | | | | |
| 13 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 8 | | |
| 14 | Brushed stainless steel body, rust resistant, she bin, | No | 8 | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 Section No. 5 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 8 Metalwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Prought Forward | | 1 1 | |
|---|-----|-----|---|
| Brought Forward | | | I |
| Fixing: | | | 1 |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | |
| References: | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | |
| • 21111/FSPS/S005 | | | |
| and bound into the back of these bills of quantities | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | |
| | | | |
| | | | |
| | | | I |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | I |
| | | | I |
| | | | |
| Carried Forward | R | | |
| Section No. 5 Bill No. 8 Metalwork | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | |
| | ı I | 1 1 | |

| | Brought Forward | | | R | |
|---|--|----|---|---|----------|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 7 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 1 | | |
| 4 | Frame for door size 914 x 2032mm high | No | 1 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 5 | Window type NE1, 533 x 654mm high (N1) | No | 8 | | |
| 6 | Window type NE7, 1022 x 654mm high (N2) | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | \vdash |
| | Carried Forward to Summary of Section No. 5 Section No. 5 | | | R | ╞ |
| | Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 9 Plastering | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 5 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought Forwar | - |
|----------------|---|
| | α |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 5 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 32 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 32 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 | | | R | |
| | Section No. 5 Bill No. 9 Plastering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.10 | | | |
| | <u>PLUMBING AND DRAINAGE</u> (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | |
|--|---|--|
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 5 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 5 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 5 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| Durant for a second | | 1 |
|---|---|---|
| Brought Forward | R | |
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| | | |
| Carried Forward | R | |
| Section No. 5 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|---|---|--|
| General: | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| Carried Forward Section No. 5 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |
| | | |

| | | | | | Nev.00 |
|---|--|----|----|---|--------|
| | Brought Forward | | | R | |
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 1 | 150 x150mm Box gutters | m | 10 | | |
| 2 | 100 x 75mm Rainwater pipes | m | 5 | | |
| 3 | Extra over gutter for stopped end | No | 2 | | |
| 4 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | |
| 5 | Extra over rainwater pipe for bend | No | 2 | | |
| 6 | Extra over rainwater pipe for shoe | No | 2 | | |
| 7 | Extra over rainwater pipe for eaves or plinth offset | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 5 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| | SANITARY FITTINGS | | | | |
| | ENVIRO-LOO TOILET SYSTEMS | | | | |
| | Supply and install "Enviroloo systems" or similar approved: | | | | |
| 8 | "Enviro Loo System FG-1040 STDCA/A Standard" strictly in accordance with manufacturers instructions, unit comprising of top unit and two x louvered inlets (PL.1), drying plate (PL.2), two x air inlets (PL.3), toilet pan, seat and lid (PL.4), 3500mm long outlet vent pipe (PL.5), ventilation extraction unit (PL.6) fixed to wall with vent wall bracket (PL.7), 1 bag mounting screws and organic starter, enzyme and toilet cleaner (PL.8) including all necessary interconnector piping between multiple tanks, emergency outlet piping, etc | No | 7 | | |
| 9 | Supply and install pre-cast concrete double wash⊡trough,complete with all necessary 19mm galvanised pipework including soakaway size 1000 x 1000 x 1000mm covered with "bidim" | No | 2 | | |
| | INSPECTION BY ENVIRO-LOO/SUPPLIER | | | | |
| 10 | Two site visits to be made by the "Enviro loo" suppliers to assist/support the contractor in the installation of the "enviro loo" and a final inspection to be ascertain the enviro loo has been installed correctly at which time a Certificate of Compliance should be issued between the Department of Education Limpopo and Enviro Loo Options Limpopo | | Item | | |
| | | | | | |
| | Carried Forward Section No. 5 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|--|----|----|---|--|
| | <u>White glazed fireclay or vitreous china coupling with</u> SABS specification 497 in | | | | |
| 11 | Lecico Atlas 50cm basin colour White, fixed with stainless steel screws and washers to plugs in wall and sealed with abe Dow Corning acetoxy silicone sealant where basin meets wall. • Material: Vitreous China • Basin code: (ATLBASWHU0500UE) • Height: 500mm • Width: 410mm • Depth: 480mm | No | 2 | | |
| 12 | | No | 2 | | |
| 12 | Elbow taps | NO | 2 | | |
| 12 | "Vaal" or similar approved: | | | | |
| 13 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 6 | | |
| 14 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 7 | | |
| 15 | "Pearl Paraplegic" 7300SC paraplegic WC suite with lid, fitments, purpose made CP side flush lever and purpose made double flap white epoxy painted wooden seat | No | 1 | | |
| 16 | 19mm chrome plated push button taps to wash troughs | No | 6 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 17 | 50mm Code 365 CP bottle trap | No | 6 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 18 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 14 | | |
| | Carried Forward | | | R | |
| | Section No. 5 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|----|----|---|--|
| 19 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 5 | | |
| 20 | 15mm Code 503-21CP elbow action pillar tap | No | 1 | | |
| | SUNDRIES | | | | |
| 21 | Stainless-steel 24L SHE-BIN plugged to wall | No | 8 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 22 | 50mm Pipes | m | 30 | | |
| 23 | 110mm Pipes | m | 40 | | |
| 24 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 39 | | |
| 25 | Ditto, but 110mm diameter | m | 52 | | |
| | Extra over uPVC pipes for fittings: | | | | |
| 26 | 50mm Bend | No | 12 | | |
| 27 | 50mm Junction | No | 12 | | |
| 28 | 50mm Junction with cleaning eye and lid | No | 12 | | |
| 29 | 110mm Straight pan connector | No | 8 | | |
| 30 | 110mm Bend | No | 16 | | |
| 31 | 110mm Junction | No | 16 | | |
| 32 | 110mm Reducing junction | No | 24 | | |
| 33 | 110mm Access bend | No | 8 | | |
| | Carried Forward | | | R | |
| | Section No. 5 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| Brought Forw | vard | | R | |
|--|------|------|---|--|
| 110mm Double junction | No | 24 | | |
| 5 110mm "GI Two-way" vent valve | No | 8 | | |
| Testing: | | | | |
| 6 Testing waste pipe system | | Item | | |
| WATER SUPPLIES | | | | |
| Class 1 copper pipes with capillary couplings: | | | | |
| 15mm Pipe fixed to walls, in chases, etc | m | 42 | | |
| Ditto, but 22mm diameter | m | 70 | | |
| Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 9 15mm Fittings | No | 70 | | |
| 0 22mm Fittings | No | 70 | | |
| Testing: | | | | |
| 1 Testing water pipe system | | Item | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Carried Forward to Summary of Section N | o. 5 | | R | |
| Section No. 5 Bill No. 10 Plumbing and Drainage | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Float glass:</u> | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 5 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|---|---|---|--|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m2 | 5 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 5 | | R | |
| | Section No. 5 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 5 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | - · · - · | | | |
| | Carried Forward Section No. 5 Bill No. 12 Paintwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|---|----|---|---|--|
| Previously painted wood surfaces: | | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | | |
| PAINT SPECIFICATIONS | | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | | |
| COLOURS | | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | | |
| | | | | |
| PAINTWORK, ETC TO NEW WORK | | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | | |
| Fascias and barge boards, including priming metal jointing strips | m2 | 5 | | |
| METAL SURFACES WITH | | | | |
| | | | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 5 Bill No. 12 Paintwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| | | <u>.</u> | | <u>.</u> | <u>.</u> |
|---|---|----------|----|----------|----------|
| | Brought Forward | | | R | |
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Door frames | m2 | 17 | | |
| 3 | Windows | m2 | 9 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 33 | | |
| | ON WOOD SURFACES | | | | |
| | <u>One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on:</u> | | | | |
| 6 | Doors | m2 | 32 | | |
| 7 | Roof timbers at eaves and verges | m2 | 42 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 74 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 5 Section No. 5 Bill No. 12 Paintwork Diatho Consulting (PTY) LTD | | | R | |

| Bill No | SECTION SUMMARY - FD7 Female Learners Ablutions | Page No | | Amount |
|------------|--|------------|---|--------|
| 1 | Earthwork | 142 | | |
| 2 | Concrete, Formwork, and Reincforcement | 147 | | |
| 3 | Masonry | 151 | | |
| 4 | Waterproofing | 153 | | |
| 5 | Roof Covering | 155 | | |
| 6 | Carpentry and Joinery | 158 | | |
| 7 | Ironmongery | 162 | | |
| 8 | Metalwork | 165 | | |
| 9 | Plastering | 169 | | |
| 10 | Plumbing and Drainage | 180 | | |
| 11 | Glazing | 182 | | |
| 12 | Paintwork | 185 | | |
| | Carried to Final Summary Section No. 5 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Carried Forward Section No. 6 Bill No. 1 Earthwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

| Brou | Jaht | For | wai | rd |
|------|------|-----|-----|----|
| | | | | |

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 6 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|-----|---|--|
| | Filling | | | P | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 2 | | |
| 2 | Trenches | m3 | 6 | | |
| 3 | Pit | m3 | 30 | | |
| 4 | Trenches and holes for thickening under surface beds, etc | m3 | 1 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 5 | Soft rock | m3 | 1 | | |
| 6 | Hard rock | m3 | 0,3 | | |
| | Extra over all excavations for carting away: | | | | |
| 7 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 8 | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Risk of collapse of excavations: | | | | |
| 8 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 21 | | |
| | Keeping excavations free of water: | | | | |
| 9 | Keeping excavations free of all water other than subterranean water | | ltem | | |
| | FILLING ETC | | | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 10 | Backfilling to trenches, holes, etc | m3 | 2 | | |
| | <u>G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density:</u> | | | | |
| 11 | Under floors, steps, pavings, etc | m3 | 2 | | |
| | Compaction of surfaces: | | | | |
| 12 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 21 | | |
| | Prescribed density tests on filling: | | | | |
| 13 | "Modified AASHTO Density" test | No | 3 | | |
| | SOIL POISONING | | | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 14 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 17 | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| To bottoms and sides of trenches, etc | m2 | 32 | | |
|--|----|----|----|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | 11 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Carried Forward to Summary of Section No. 6 Section No. 6 | | | R | |
| Bill No. 1 Earthwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | - · · - · | | | |
| | Carried Forward Section No. 6 Bill No. 2 Concrete,Formwork and Reinforcement | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | | 1107.00 |
|--|---|---------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 6 Bill No. 2 Concrete,Formwork and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 1 | | |
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 30MPa/19mm concrete: | | | | |
| | Strip footings | m3 | 2 | | |
| | Surface beds on waterproofing | m3 | 3 | | |
| 2 | Surface beds in tank bottoms | | | | |
| | | m3 | 2 | | |
| 3 | Aprons cast in panels to falls | m3 | 2 | | |
| | TEST BLOCKS | | | | |
| 4 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 5 | Surface beds, slabs, etc | m2 | 17 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 6 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 35 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 2 Concrete,Formwork and Reinforcement | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 7 | Not exceeding 300mm high to edges of surface beds | m | 34 | | |
| | Saw-cut joints: | | | | |
| 8 | 6 x 10mm Saw-cut joints in top of concrete | m | 40 | | |
| | REINFORCEMENT (PROVISIONAL) | | | | |
| | Mild steel reinforcement to structural concrete work: | | | | |
| 9 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,06 | | |
| | High tensile steel reinforcement to structural concrete work: | | | | |
| 10 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,14 | | |
| | Fabric reinforcement: | | | | |
| 11 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 17 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 | | | | |
| | Bill No. 2 Concrete,Formwork and Reinforcement | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 6 Bill No. 3 Masonry | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | Hollow walls: | | | | |
| | Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| | Bagged and sealed walls: | | | | |
| | Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| | Face bricks : | | | | |
| | Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| | All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| | Pointing: | | | | |
| | Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | | |
| | FOUNDATIONS (PROVISIONAL) | | | | |
| | Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| 1 | One brick walls | m2 | 9 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 2 | 150mm Wide reinforcement built in horizontally | m | 52 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|---|---|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 3 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 49 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 44 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 63 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 162 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 20 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 16 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 98 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | I | 1 | Ш | I |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 6 | | |
| 12 | Fair raking cutting | m | 10 | | |
| | Brick-on-edge header course coping, sills, etc. of face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 4 | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | P | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 6 Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | <u>One layer 375 micron embossed polyethylene</u> dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 50 | | |
| 2 | In walls vertically at reveals | m2 | 4 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 20 | | |
| | JOINT SEALANTS ETC | | | | |
| | Two- part grey polysulphide sealing compound including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 40 | | |
| | <u>White silicone sealing compound including backing</u> cord, bond breaker, primer, etc | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 34 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 Bill No. 4 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 6 Bill No. 5 Roof covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|------|----|---|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 29 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 6 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at odgos where required | m2 | 29 | | |
| | edges where required | III2 | 29 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 Bill No. 5 Roof covering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Quantity | Rate | Amount |
|---|----------|------|--------|
| SECTION NO. 6 | | | |
| BILL NO.6 | | | |
| CARPENTRY AND JOINERY | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| Fixing: | | | |
| Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| Joinery: | | | |
| Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| Carried Forward | | R | |
| Section No. 6 Bill No. 6 Carpentry and Joinery | | | |
| Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|---|----|---|--|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
| | Particle board | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| | <u>Sizes:</u> | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| | Prices | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | | |
| | ROOFS, ETC | | | | |
| | Sawn softwood grade 5: | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 14 | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 45 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 6 Bill No. 6 | | | | |
| | Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| 3 | 50 x 76mm Purlins | m | 46 | | |
| | EAVES, VERGES, ETC | | | | |
| 4 | Medium density plain fibre-cement fascias and barge boards: 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | | | | |
| | | m | 16 | | |
| | DOORS, ETC | | | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 5 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm undercut (D2) | No | 3 | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | No | 0 | | |
| | | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 6 Bill No. 7 Ironmongery | | ĸ | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 3 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward Section No. 6 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| "Ref. CZ80941SC" Indicator bolt HANDLES "Union Assa Abloy" or similar approved: ASSA ABLOY Anodised Silver straight pull handle Code: AL5515-300BBAS) with 300mm fixing centres PUSH PLATES AND KICK PLATES "Union Assa Abloy" or similar approved: "Union Thick satin finished "Union" stainless steel "Diates countersunk screwed along edges at not exceeding 200mm centres | No Pairs | 3 2,0 | | |
|--|--|--|---|--|
| CUnion Assa Abloy" or similar approved: ASSA ABLOY Anodised Silver straight pull handle Code: AL5515-300BBAS) with 300mm fixing centres PUSH PLATES AND KICK PLATES CUnion Assa Abloy" or similar approved: 1.2mm Thick satin finished "Union" stainless steel Dates countersunk screwed along edges at not exceeding 200mm centres | Pairs | 2,0 | | |
| ASSA ABLOY Anodised Silver straight pull handle Code: AL5515-300BBAS) with 300mm fixing centres PUSH PLATES AND KICK PLATES "Union Assa Abloy" or similar approved: " | Pairs | 2,0 | | |
| Code: AL5515-300BBAS) with 300mm fixing centres PUSH PLATES AND KICK PLATES Union Assa Abloy" or similar approved: 1.2mm Thick satin finished "Union" stainless steel Dates countersunk screwed along edges at not exceeding 200mm centres | Pairs | 2,0 | | |
| <u>'Union Assa Abloy" or similar approved:</u> I.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres | | | | |
| 1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres | | | | |
| <u>plates countersunk screwed along edges at not</u> exceeding 200mm centres | | | | |
| 200 x 800mm Type "SS5089-200W" kicking plate | | | | |
| | No | 6 | | |
| <u>ETTERS, NAMEPLATES, ETC</u> | | | | |
| Dorma" or similar approved: | | | | |
| DSS-130 Engraved "Male" information sign | No | 2 | | |
| SUNDRIES | | | | |
| 25mm Diameter wall mounted door stop plugged | No | 5 | | |
| BATHROOM FITTINGS | | | | |
| Kimberley-Clark"or similar approved: | | | | |
| Ref. SQ2 code 405607B" white lockable toilet roll nolder | No | 3 | | |
| | | | | |
| Carried Forward to Summary of Section No. Section No. 6 Bill No. 7 ronmongery Diatho Consulting (PTY) LTD | 6 | | R | |
| | Dorma" or similar approved: DSS-130 Engraved "Male" information sign SUNDRIES Somm Diameter wall mounted door stop plugged BATHROOM FITTINGS Kimberley-Clark"or similar approved: Ref. SQ2 code 405607B" white lockable toilet roll older Carried Forward to Summary of Section No. Section No. 6 Sill No. 7 ronmongery | ETTERS, NAMEPLATES, ETC Dorma" or similar approved: DSS-130 Engraved "Male" information sign No SUNDRIES Somm Diameter wall mounted door stop plugged No Carried Forward to Summary of Section No. 6 Section No. 6 Sill No. 7 Tommongery | LETTERS, NAMEPLATES, ETC Dorma" or similar approved: DSS-130 Engraved "Male" information sign No 2 SUNDRIES '5mm Diameter wall mounted door stop plugged No 5 BATHROOM FITTINGS Kimberley-Clark"or similar approved: Ref. SQ2 code 405607B" white lockable toilet roll older No 3 Carried Forward to Summary of Section No. 6 Section No. 6 ill No. 7 onmongery | LETTERS, NAMEPLATES, ETC Dorma" or similar approved: DSS-130 Engraved "Male" information sign No 2 SUNDRIES 55mm Diameter wall mounted door stop plugged No 5 BATHROOM FITTINGS Kimberley-Clark"or similar approved: Ref. SQ2 code 405607B" white lockable toilet roll older No 3 Carried Forward to Summary of Section No. 6 iff No. 7 onmongery |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward Section No. 6 Bill No. 8 Metalwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward R Fixing: Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | |
|---|--|
| Unless otherwise described, descriptions of items shall | |
| | |
| | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | |
| References: | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | |
| • 21111/FSPS/S001 | |
| and bound into the back of these bills of quantities | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| Carried Forward R | |
| Section No. 6 Bill No. 8 Metalwork | |
| Diatho Consulting (PTY) LTD | |
| | |

| | Brought Forward | | | R | |
|---|--|----|---|---|--|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 3 | | |
| | <u>1,6mm Double rebated frames suitable for one brick walls:</u> | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 2 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 4 | Window type NE1, 533 x 654mm high (N1) | No | 4 | | |
| 5 | Window type NE7, 1022 x 654mm high (N2) | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 6 Bill No. 9 Plastering | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 6 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought Forwar | |
|----------------|---|
| | α |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 6 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|------|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 17 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 17 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 6 | | | R | |
| | Section No. 6 Bill No. 9 Plastering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.10 | | | |
| | PLUMBING AND DRAINAGE (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 6 | | R | |
| | Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | • |
|--|---|---|
| Brought Forward | R | 1 |
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| | | |
| | | |
| Carried Forward Section No. 6 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 6 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 6 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| Brought Forward | R | | |
|---|-----|-----|--|
| Disinfection of water pipework: | | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | | |
| Laying, backfilling, bedding, etc of pipes: | | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | | |
| | | | |
| Carried Forward | R | | |
| Section No. 6 Bill No. 10 Plumbing and Drainage | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | |
| | 1 1 | i I | |

| | | 1 1 |
|---|---|-----|
| Brought Forward | R | |
| <u>General:</u> | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| | | |
| Carried Forward Section No. 6 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |
| | I | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | ENVIRO-LOO TOILET SYSTEMS | | | | |
| 1 | Enviro-loo industrial system CER/ABS-V1 (Code FG⊡1040STDCA/A) | No | 3 | | |
| 2 | "Enviro Loo 3 Pan Urinal Evaporative Tank System code FG-862B " strictly in accordance with manufacturers instructions, unit comprising of urinal evaporative tank (PL.1), urinal bowl (PL.5), 3500mm long outlet vent pipe (PL.3), ventilation extraction unit (PL.3) fixed to wall with vent wall bracket (PL.4), 1 bag mounting screws and organic starter, enzyme and toilet cleaner (PL.8) including all necessary piping, traps, etc | No | 3 | | |
| 3 | Supply and install pre-cast concrete double wash⊡trough, complete with all necessary 19mm galvanised pipework including soakaway size 1000 x | No | 3 | | |
| | | | | | |
| | Carried Forward Section No. 6 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | | R | |
|----|--|----|------|---|---|
| | INSPECTION BY ENVIRO-LOO/SUPPLIER | | | | |
| 4 | Two site visits to be made by the "Enviro loo" suppliers to assist/support the contractor in the installation of the "enviro loo" and a final inspection to be ascertain the enviro loo has been installed correctly at which time a Certificate of Compliance should be issued between the Department of Education Limpopo and Enviro Loo Options Limpopo | | ltem | | |
| | White glazed fireclay or vitreous china coupling with SABS specification 497 in | | | | |
| 5 | Lecico Atlas 50cm basin colour White, fixed with stainless steel screws and washers to plugs in wall and sealed with abe Dow Corning acetoxy silicone sealant where basin meets wall. • Material: Vitreous China • Basin code: (ATLBASWHU0500UE) • Height: 500mm • Width: 410mm | No | 0 | | |
| | • Depth: 480mm | No | 2 | | |
| 6 | Elbow taps | No | 2 | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 7 | 150 x150mm Box gutters | m | 6 | | |
| 8 | 100 x 75mm Rainwater pipes | m | 5 | | |
| 9 | Extra over gutter for stopped end | No | 2 | | |
| 10 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | |
| 11 | Extra over rainwater pipe for bend | No | 2 | | |
| 12 | Extra over rainwater pipe for shoe | No | 2 | | |
| | Carried Forward Section No. 6 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | 1 |

| Brought F | orward | | R | | |
|---|--|--------------------------------------|---|--|---|
| Extra over rainwater pipe for eaves or plinth offset | No | 2 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Carried F | orward | | R | | |
| Section No. 6 Bill No. 10 Plumbing and Drainage | | | | | |
| Diatho Consulting (PTY) LTD | | | | | |
| | | | | | |
| | Extra over rainwater pipe for eaves or plinth offset | Bill No. 10 Plumbing and Drainage | Extra over rainwater pipe for eaves or plinth offset No 2 | Extra over rainwater pipe for eaves or plinth offset No 2 Extra over rainwater pipe for eaves or plinth offset No 7 R Section No. 6 Bil No. 10 Plumbing and Drainage | Extra over rainwater pipe for eaves or plinth offset No 2 |

| | | | | | 100100 |
|----|---|----|---|---|--------|
| | Brought Forward | | | R | |
| | SANITARY FITTINGS | | | | |
| | "Vaal" or similar approved: | | | | |
| 14 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 3 | | |
| 15 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 3 | | |
| 16 | Flat back urinal overall size 295 x 315 x 415mm high with 40mm chromium plated domical grating (Code 878720) and top inlet spreader (Code 8543) with two hanger brackets with flushmaster junior (Code 812720) hung to wall | No | 3 | | |
| | | NO | 5 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 17 | 50mm Code 365 CP bottle trap | No | 3 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 18 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 9 | | |
| 19 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 3 | | |
| 20 | 15mm Code 503-21CP elbow action pillar tap | No | | | |
| | SUNDRIES | | | | |
| 21 | Stainless-steel 24L SHE-BIN plugged to wall | No | | | |
| | SANITARY PLUMBING | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 6 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| PVC pipes: Omm Pipes 10mm Pipes Omm Diameter pipe laid in and including trenches not xceeding 1m deep Ditto, but 110mm diameter Extra over uPVC pipes for fittings: Omm Bend | m m m | 45 15 135 45 | | |
|---|--|---|--|---|
| 10mm Pipes 0mm Diameter pipe laid in and including trenches not xceeding 1m deep Ditto, but 110mm diameter | m m | 15 135 | | |
| Omm Diameter pipe laid in and including trenches not xceeding 1m deep Ditto, but 110mm diameter | m | 135 | | |
| xceeding 1m deep Ditto, but 110mm diameter Extra over uPVC pipes for fittings: | | | | |
| extra over uPVC pipes for fittings: | m | 45 | | |
| | | | | |
| 0mm Bend | | | | |
| | No | 18 | | |
| 0mm Junction | No | 18 | | |
| 0mm Junction with cleaning eye and lid | No | 18 | | |
| 10mm Straight pan connector | No | 3 | | |
| 10mm Bend | No | 6 | | |
| 10mm Junction | No | 6 | | |
| 10mm Reducing junction | No | 9 | | |
| 10mm Access bend | No | 3 | | |
| 10mm Double junction | No | 9 | | |
| 10mm "GI Two-way" vent valve | No | 3 | | |
| esting: | | | | |
| esting waste pipe system | | ltem | | |
| VATER SUPPLIES | | | | |
| | | | | |
| | | | R | |
| <u>е</u> е V | <u>sting:</u> sting waste pipe system <u>ATER SUPPLIES</u> | sting: sting waste pipe system ATER SUPPLIES Carried Forward ction No. 6 No. 10 umbing and Drainage | sting: sting waste pipe system Item ATER SUPPLIES Carried Forward ction No. 6 No. 10 imbing and Drainage | sting: sting waste pipe system Item ATER SUPPLIES Carried Forward R ction No. 6 No. 10 |

| | Brought Forwar | d | | R | |
|----|--|----|------|---|--|
| | Class 1 copper pipes with capillary couplings: | | | | |
| 37 | 15mm Pipe fixed to walls, in chases, etc | m | 27 | | |
| 38 | Ditto, but 22mm diameter | m | 45 | | |
| | Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 39 | 15mm Fittings | No | 45 | | |
| 40 | 22mm Fittings | No | 45 | | |
| | Testing: | | | | |
| 41 | Testing water pipe system | | Item | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. | 6 | | R | |
| | Section No. 6 | - | | | |
| | Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 6 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Float glass:</u> | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 6 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|--|-----|---|---|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m | 2 3 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 6 Section No. 6 | | R | = |
| | Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Quantity | Rate | Amou |
|---|----------|------|------|
| SECTION NO. 6 | | | |
| BILL NO.12 | | | |
| PAINTWORK | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| PREPARATORY WORK TO EXISTING WORK | | | |
| Previously painted plastered surfaces: | | | |
| Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| Previously painted metal surfaces: | | | |
| Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | |
| Carried Forward | | R | |
| Section No. 6 Bill No. 12 Paintwork | | | |
| Diatho Consulting (PTY) LTD | | | |

lte N

| Brought Forward | | R | 1 |
|---|---|---|---|
| Previously painted wood surfaces: | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | |
| PAINT SPECIFICATIONS | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | |
| COLOURS | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | |
| | | | |
| PAINTWORK, ETC TO NEW WORK | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | |
| Fascias and barge boards, including priming metal jointing strips m2 | 4 | | |
| METAL SURFACES WITH | | | |
| | | | |
| | | | 1 |
| Carried Forward | | R | |
| Section No. 6 Bill No. 12 Paintwork | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | 1 |

1

| | Brought Forward | I | | R | 1 |
|---|--|----|----|---|---|
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Door frames | m2 | 9 | | |
| 3 | Windows | m2 | 5 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 22 | | |
| | ON WOOD SURFACES | | | | |
| | One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: | | | | |
| 6 | Doors | m2 | 18 | | |
| 7 | Roof timbers at eaves and verges | m2 | 29 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 47 | | |
| | Carried Forward to Summary of Section No. 6 Section No. 6 Bill No. 12 Paintwork Diatho Consulting (PTY) LTD | | | R | |

| Bill | SECTION SUMMARY - M3 + 3UR Male Learners Ablutions | Page | | Amount |
|------|--|------|---|--------|
| No | | No | | |
| 1 | Earthwork | 191 | | |
| 2 | Concrete,Formwork and Reinforcement | 195 | | |
| 3 | Masonry | 199 | | |
| 4 | Waterproofing | 201 | | |
| 5 | Roof covering | 203 | | |
| 6 | Carpentry and Joinery | 206 | | |
| 7 | Ironmongery | 209 | | |
| 8 | Metalwork | 212 | | |
| 9 | Plastering | 216 | | |
| 10 | Plumbing and Drainage | 228 | | |
| 11 | Glazing | 230 | | |
| 12 | Paintwork | 233 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried to Final Summary Section No. 6 | | R | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |
| | | | | |
| | I | l | I | I I |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 1 Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

| Bro | ugh | t Fo | rwa | rd |
|-----|------------|------|-----|----|
| | ~ <u>9</u> | | | |

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 7 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|-----|---|--|
| | Filling | | | | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 2 | | |
| 2 | Trenches | m3 | 6 | | |
| 3 | Trenches and holes for thickening under surface beds, etc | m3 | 1 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 4 | Soft rock | m3 | 1 | | |
| 5 | Hard rock | m3 | 0,3 | | |
| | Extra over all excavations for carting away: | | | | |
| 6 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 8 | | |
| | | | | | |
| | Consid Forward | | | | |
| | Carried Forward Section No. 7 Bill No. 1 Earthwork | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|---|----|------|---|---|
| | Risk of collapse of excavations: | | | | |
| 7 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 21 | | |
| | Keeping excavations free of water: | | | | |
| 8 | Keeping excavations free of all water other than subterranean water | | Item | | |
| | FILLING ETC | | | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 9 | Backfilling to trenches, holes, etc | m3 | 2 | | |
| | G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: | | | | |
| 10 | Under floors, steps, pavings, etc | m3 | 2 | | |
| | Compaction of surfaces: | | | | |
| 11 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 21 | | |
| | Prescribed density tests on filling: | | | | |
| 12 | "Modified AASHTO Density" test | No | 3 | | |
| | SOIL POISONING | | | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 13 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 17 | | |
| | Carried Forward | | | R | |
| | Section No. 7 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | |] |

| | Brought Forward | | R | |
|----|---|----|---|--|
| 14 | To bottoms and sides of trenches, etc m2 | 32 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 7 | | R | |
| | Section No. 7 Bill No. 1 Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | | | | |
| | Carried Forward Section No. 7 Bill No. 2 Concrete,Formwork and Reinforcement | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | | IVEN.00 |
|--|---|---------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 7 Bill No. 2 Concrete,Formwork and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|---|
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 1 | | |
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| | Strip footings | m3 | 2 | | |
| | Surface beds on waterproofing | m3 | 3 | | |
| | TEST BLOCKS | | | | |
| 2 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 3 | Surface beds, slabs, etc | m2 | 17 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 4 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 35 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 5 | Not exceeding 300mm high to edges of surface beds | m | 34 | | |
| | | | | | _ |
| | Carried Forward Section No. 7 Bill No. 2 Concrete,Formwork and Reinforcement | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R |
|---|--|----|------|---|
| | Saw-cut joints: | | | |
| 6 | 6 x 10mm Saw-cut joints in top of concrete | m | 40 | |
| | REINFORCEMENT (PROVISIONAL) | | | |
| | Mild steel reinforcement to structural concrete work: | | | |
| 7 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,06 | |
| | High tensile steel reinforcement to structural concrete work: | | | |
| 8 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,14 | |
| | Fabric reinforcement: | | | |
| 9 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 17 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 7 Section No. 7 | | | R |
| | Bill No. 2 Concrete,Formwork and Reinforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 3 Masonry | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forwa | rd | | R | |
|---|----|----|---|--|
| Hollow walls: | | | | |
| Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| Bagged and sealed walls: | | | | |
| Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| Face bricks : | | | | |
| Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| Pointing: | | | | |
| Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | |
| FOUNDATIONS (PROVISIONAL) | | | | |
| Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| One brick walls | m2 | 9 | | |
| 2,5mm Brickwork reinforcement: | | | | |
| 2 150mm Wide reinforcement built in horizontally | m | 52 | | |
| | | | | |
| Carried Forward | rd | | R | |
| Section No. 7 Bill No. 3 Masonry | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|---|---|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 3 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 49 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 44 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 63 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 162 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 20 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 16 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 98 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 7 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | I | 1 | Ш | I |

| | Brought Forward | | R | |
|----|---|------|---|---|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | n 6 | 5 | |
| 12 | Fair raking cutting | n 10 | | |
| | Brick-on-edge header course coping, sills, etc. of face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with recessed joints on all exposed faces | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | n 4 | | |
| | Carried Forward to Summary of Section No. 7 Section No. 7 Bill No. 3 Masonry | | R | _ |
| | Diatho Consulting (PTY) LTD | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ĺ | Brought Forward | | | R | |
|---|---|----|----|---|------------------|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | <u>One layer 375 micron embossed polyethylene</u> dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 50 | | |
| 2 | In walls vertically at reveals | m2 | 4 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 20 | | |
| | JOINT SEALANTS ETC | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 40 | | |
| | <u>White silicone sealing compound including backing</u> cord, bond breaker, primer, etc | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 34 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 | | | R | $\left \right $ |
| | Section No. 7 Bill No. 4 Waterproofing | | | K | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 7 Bill No. 5 Roof Covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 29 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 6 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at | m2 | 29 | | |
| | edges where required | m2 | 29 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 Section No. 7 Bill No. 5 Roof Covering | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.6 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 6 Carpentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | | |
|---|--|---|----|---|---|--|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | | |
| | Particle board | | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | | |
| | <u>Sizes:</u> | | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | | |
| | Prices_ | | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | | |
| | | | | | | |
| | ROOFS, ETC | | | | | |
| | Sawn softwood grade 5: | | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 14 | | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 45 | | | |
| | | | | | | |
| | Carried Forward | | | R | | |
| | Section No. 7 Bill No. 6 Carpentry and Joinery | | | | | |
| | Diatho Consulting (PTY) LTD | | | | | |
| | | | | | | |
| | | | l | | I | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|---|---|
| 3 | 50 x 76mm Purlins | m | 46 | | |
| | EAVES, VERGES, ETC | | | | |
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 16 | | |
| | DOORS, ETC | | | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 5 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm undercut (D2) | No | 3 | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | | | | |
| | | No | 2 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 | | | R | |
| | Section No. 7 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | ł |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| l | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 3 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward Section No. 7 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| [| Brought Forward | | | R | |
|---|---|-------|-----|---|--|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 3 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel</u> plates countersunk screwed along edges at not exceeding 200mm centres | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 6 | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | <u>"Dorma" or similar approved:</u> | | | | |
| 7 | DSS-130 Engraved "Male" information sign | No | 2 | | |
| | SUNDRIES | | | | |
| 8 | 25mm Diameter wall mounted door stop plugged | No | 5 | | |
| | BATHROOM FITTINGS | | | | |
| | <u>"Kimberley-Clark"or similar approved:</u> | | | | |
| 9 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 3 | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 Section No. 7 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 8 Metalwork | | ĸ | |
| | Diatho Consulting (PTY) LTD | | | |

| | 1 | l D | 1 1 | |
|---|---|-----|-----|--|
| Brought Forward | | ĸ | | |
| Fixing: | | | | |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | | |
| <u>References:</u> | | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | | |
| • 21111/FSPS/S001 | | | | |
| and bound into the back of these bills of quantities | | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Carried Forward Section No. 7 | | R | | |
| Bill No. 8 Metalwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | | R | |
|---|--|----|---|---|--|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 3 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 2 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 4 | Window type NE1, 533 x 654mm high (N1) | No | 4 | | |
| 5 | Window type NE7, 1022 x 654mm high (N2) | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 | | | R | |
| | Section No. 7 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 9 Plastering | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 7 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought | Forward |
|---------|--------------|
| Diougin | . i oi mai a |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 7 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 17 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on concrete:</u> | | | | |
| 2 | On screed | m2 | 17 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 | | | R | |
| | Section No. 7 Bill No. 9 Plastering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.10 | | | |
| | <u>PLUMBING AND DRAINAGE</u> (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 10 Plumbing and Drainage | | K | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | 1 |
|--|---|---|
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | 1 |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| Carried Forward | R | |
| Section No. 7 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 7 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 7 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| | | - |
|---|---|-------|
| Brought Forward | R | |
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| | | |
| Carried Forward | R | |
| Section No. 7 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|---|---|-----|
| General: | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| Carried Forward | R | |
| Section No. 7 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |
| | I | I I |

| | | | | | Nev.00 |
|---|--|----|---|---|--------|
| | Brought Forward | | | R | |
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 1 | 150 x150mm Box gutters | m | 6 | | |
| 2 | 100 x 75mm Rainwater pipes | m | 5 | | |
| 3 | Extra over gutter for stopped end | No | 2 | | |
| 4 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | |
| 5 | Extra over rainwater pipe for bend | No | 2 | | |
| 6 | Extra over rainwater pipe for shoe | No | 2 | | |
| 7 | Extra over rainwater pipe for eaves or plinth offset | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 7 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | | | | | 101100 |
|----|---|----|----|---|--------|
| | Brought Forward | | | R | |
| | SANITARY FITTINGS | | | | |
| | <u>"Vaal" or similar approved:</u> | | | | |
| 8 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 3 | | |
| 9 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 3 | | |
| 10 | Flat back urinal overall size 295 x 315 x 415mm high with 40mm chromium plated domical grating (Code 878720) and top inlet spreader (Code 8543) with two hanger brackets with flushmaster junior (Code 812720) hung to wall | No | 3 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 11 | 50mm Code 365 CP bottle trap | No | 3 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 40 | | | | | |
| 12 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 9 | | |
| 13 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 3 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 14 | 50mm Pipes | | 45 | | |
| | | m | 45 | | |
| 15 | 110mm Pipes | m | 15 | | |
| | | | | | |
| | Carried Forward Section No. 7 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | · | | R |
|----|--|----|------|---|
| 16 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 135 | |
| 17 | Ditto, but 110mm diameter | m | 45 | |
| | Extra over uPVC pipes for fittings: | | | |
| 18 | 50mm Bend | No | 18 | |
| 19 | 50mm Junction | No | 18 | |
| 20 | 50mm Junction with cleaning eye and lid | No | 18 | |
| 21 | 110mm Straight pan connector | No | 3 | |
| 22 | 110mm Bend | No | 6 | |
| 23 | 110mm Junction | No | 6 | |
| 24 | 110mm Reducing junction | No | 9 | |
| 25 | 110mm Access bend | No | 3 | |
| 26 | 110mm Double junction | No | 9 | |
| 27 | 110mm "GI Two-way" vent valve | No | 3 | |
| | Testing: | | | |
| 28 | Testing waste pipe system | | Item | |
| | WATER SUPPLIES | | | |
| | Class 1 copper pipes with capillary couplings: | | | |
| 29 | 15mm Pipe fixed to walls, in chases, etc | m | 27 | |
| 30 | Ditto, but 22mm diameter | m | 45 | |
| | | | | |
| | | | | |
| | | | | - |
| | Carried Forward Section No. 7 Bill No. 10 Plumbing and Drainage | | | R |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 31 | 15mm Fittings | No | 45 | | |
| 32 | 22mm Fittings | No | 45 | | |
| | Testing: | | | | |
| 33 | Testing water pipe system | | Item | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 7 | | | R | |
| | Section No. 7 Bill No. 10 | | | | |
| | Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.11 | | | |
| | <u>GLAZING</u> | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Float glass: | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 7 Bill No. 11 Glazing | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|---|-----|---|---|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m | 2 3 | 6 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 7 | | R | |
| | Section No. 7 Bill No. 11 | | | - |
| | Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 7 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 7 Bill No. 12 Paintwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | R | 1 |
|---|---|---|---|
| Previously painted wood surfaces: | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | |
| PAINT SPECIFICATIONS | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | |
| COLOURS | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | |
| | | | |
| PAINTWORK, ETC TO NEW WORK | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | |
| Fascias and barge boards, including priming metal jointing strips m2 | 4 | | |
| METAL SURFACES WITH | | | |
| | | | |
| | | | 1 |
| Carried Forward | | R | |
| Section No. 7 Bill No. 12 Paintwork | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | 1 |

1

| | Brought Forward | | 1 | R | |
|---|---|----|----|---|--|
| | <u>One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel:</u> | | | | |
| 2 | Door frames | m2 | 9 | | |
| 3 | Windows | m2 | 5 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 22 | | |
| | ON WOOD SURFACES | | | | |
| | <u>One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on:</u> | | | | |
| 6 | Doors | m2 | 18 | | |
| 7 | Roof timbers at eaves and verges | m2 | 29 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 47 | | |
| | Carried Forward to Summary of Section No. 7 Section No. 7 Bill No. 12 Paintwork | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| Bill No | SECTION SUMMARY - SM3 + 3UR Male Educators Ablutions | Page No | | Amount |
|------------|--|------------|---|--------|
| 1 | Earthwork | 239 | | |
| 2 | Concrete,Formwork and Reinforcement | 243 | | |
| 3 | Masonry | 247 | | |
| 4 | Waterproofing | 249 | | |
| 5 | Roof Covering | 251 | | |
| 6 | Carpentry and Joinery | 254 | | |
| 7 | Ironmongery | 257 | | |
| 8 | Metalwork | 260 | | |
| 9 | Plastering | 264 | | |
| 10 | Plumbing and Drainage | 274 | | |
| 11 | Glazing | 276 | | |
| 12 | Paintwork | 279 | | |
| | Carried to Final Summary Section No. 7 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Operated Forewood | | | |
| | Carried Forward Section No. 8 Bill No. 1 Earthwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

| Bro | ugh | t Fo | rwa | rd |
|-----|------------|------|-----|----|
| | ~ <u>9</u> | | | |

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 8 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|-----|---|---|
| | <u>Filling</u> | | | | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | <u>Testing:</u> | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 3 | | |
| 2 | Trenches | m3 | 7 | | |
| 3 | Trenches and holes for thickening under surface beds, etc | m3 | 1 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 4 | Soft rock | m3 | 1 | | |
| 5 | Hard rock | m3 | 0,4 | | |
| | Extra over all excavations for carting away: | | | | |
| 6 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 9 | | |
| | | | | | |
| | | | | | ┝ |
| | Carried Forward | | | R | |
| | Section No. 8 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Risk of collapse of excavations: | | | | |
| 7 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 24 | | |
| | Keeping excavations free of water: | | | | |
| 8 | Keeping excavations free of all water other than subterranean water | | ltem | | |
| | FILLING ETC | | | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 9 | Backfilling to trenches, holes, etc | m3 | 2 | | |
| | G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: | | | | |
| 10 | Under floors, steps, pavings, etc | m3 | 3 | | |
| | Compaction of surfaces: | | | | |
| 11 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 26 | | |
| | Prescribed density tests on filling: | | | | |
| 12 | "Modified AASHTO Density" test | No | 3 | | |
| | SOIL POISONING | | | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 13 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 20 | | |
| | Carried Forward | | | R | |
| | Section No. 8 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|---|----|---|--|
| 14 | To bottoms and sides of trenches, etc m2 | 35 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 8 | | R | |
| | Section No. 8 Bill No. 1 | | | |
| | Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 2 Concrete, Formwork, and Reinforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | 1101.00 |
|--|---|---------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 8 Bill No. 2 Concrete, Formwork, and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | · | | R | |
|---|---|----|----|---|--|
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 1 | | |
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| | Strip footings | m3 | 3 | | |
| | Surface beds on waterproofing | m3 | 3 | | |
| | TEST BLOCKS | | | | |
| 2 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 3 | Surface beds, slabs, etc | m2 | 20 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY | | | | |
| | Rough formwork to sides: | | | | |
| 4 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 39 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 5 | Not exceeding 300mm high to edges of surface beds | m | 41 | | |
| | | | | | |
| | Carried Forward Section No. 8 Bill No. 2 Concrete, Formwork, and Reinforcement | I | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R |
|---|--|----|------|---|
| | Saw-cut joints: | | | |
| 6 | 6 x 10mm Saw-cut joints in top of concrete | m | 49 | |
| | REINFORCEMENT (PROVISIONAL) | | | |
| | Mild steel reinforcement to structural concrete work: | | | |
| 7 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,06 | |
| | High tensile steel reinforcement to structural concrete work: | | | |
| 8 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,15 | |
| | Fabric reinforcement: | | | |
| 9 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 20 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 8 Section No. 8 | | | R |
| | Bill No. 2 Concrete, Formwork, and Reinforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | Diatho Consulting (PTY) LTD | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 3 Masonry | | | |
| | Diatho Consulting (PTY) LTD | | | |

| 10 | | |
|----|---|---------------|
| | | |
| 58 | | |
| | | |
| | R | |
| | | |
| | | 10 58 R |

| | Brought Forward | | | R | |
|----|--|----|-----|---|--|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 3 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 55 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 49 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 90 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 182 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 25 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 24 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 109 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 8 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 7 | | |
| 12 | Fair raking cutting | m | 10 | | |
| | <u>Brick-on-edge header course coping, sills, etc. of face</u> <u>bricks (Allow a Prime Cost Amount of R5</u> <u>500.00/1000 bricks delivered to site excluding VAT)</u> pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 6 | R | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | <u>One layer 375 micron embossed polyethylene</u> dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 56 | | |
| 2 | In walls vertically at reveals | m2 | 4 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 24 | | |
| | JOINT SEALANTS ETC | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 49 | | |
| | <u>White silicone sealing compound including backing</u> cord, bond breaker, primer, etc | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 41 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 | | | R | |
| | Section No. 8 Bill No. 4 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | Carried Forward Section No. 8 Bill No. 5 Roof covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 34 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 7 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at | | | | |
| | edges where required | m2 | 34 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 | | | R | |
| | Section No. 8 Bill No. 5 Roof covering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Quantity | Rate | Amount |
|---|----------|------|--------|
| SECTION NO. 8 | | | |
| BILL NO.6 | | | |
| CARPENTRY AND JOINERY | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| Fixing: | | | |
| Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| Joinery: | | | |
| Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| Carried Forward | | R | |
| Section No. 8 Bill No. 6 Carpentry and Joinery | | | |
| Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|---|----|---|---|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
| | Particle board | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| | <u>Sizes:</u> | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| | Prices | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | | |
| | ROOFS, ETC | | | | |
| | Sawn softwood grade 5: | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 14 | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 45 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 8 Bill No. 6 Carpontry and Joinery | | | | |
| | Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | ł |

TMT-LDOE-2023/24-LPCL23/02D Construction of water, Sanitation and Fencing

Tihabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|----------|--|
| 3 | 50 x 76mm Purlins | m | 46 | <u>p</u> | |
| | EAVES, VERGES, ETC | | | | |
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 17 | | |
| | DOORS, ETC | | | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 5 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm undercut (D2) | No | 4 | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | No | 0 | | |
| | | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 | | | R | |
| | Section No. 8 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| l | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 4 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward | | | R | |
| | Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | I | | R | |
|---|---|-------|-----|---|---|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 4 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres</u> | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 8 | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | "Dorma" or similar approved: | | | | |
| 7 | DSS-130 Engraved "Male" information sign | No | 2 | | |
| | SUNDRIES | | | | |
| 8 | 25mm Diameter wall mounted door stop plugged | No | 6 | | |
| | BATHROOM FITTINGS | | | | |
| | "Kimberley-Clark"or similar approved: | | | | |
| 9 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 4 | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 Section No. 8 Bill No. 7 Ironmongery Diatho Consulting (PTY) LTD | 3 | | R | _ |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 8 Metalwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | l R | | |
|---|-----|--|--|
| | | | |
| Fixing: | | | |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | |
| References: | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | |
| • 21111/FSPS/S001 | | | |
| and bound into the back of these bills of quantities | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Carried Forward | R | | |
| Section No. 8 Bill No. 8 Metalwork | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | |

| | Brought Forward | | | R | l |
|---|--|----|---|---|---|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick walls:</u> | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 4 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 2 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 4 | Window type NE1, 533 x 654mm high (N1) | No | 5 | | |
| 5 | Window type NE7, 1022 x 654mm high (N2) | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 | | | R | |
| | Section No. 8 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | SECTION NO. 8 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward Section No. 8 Bill No. 9 Plastering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 8 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought | Forward |
|---------|-------------|
| Biougin | . I OI Wala |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 8 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|--|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 20 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 20 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 8 | | | R | |
| | Section No. 8 Bill No. 9 Plastering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.10 | | | |
| | PLUMBING AND DRAINAGE (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | 1 |
|--|---|---|
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| Carried Forward | R | |
| Section No. 8 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 8 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 8 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| Brought Forward | R | |
|---|---|--|
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| Carried Forward | R | |
| Section No. 8 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|---|---|--|
| General: | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| | | |
| Carried Forward Section No. 8 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |
| | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | ENVIRO-LOO TOILET SYSTEMS | | | | |
| 1 | Enviro-loo industrial system CER/ABS-V1 (Code FG⊡1040STDCA/A) | No | 4 | | |
| 2 | Enviro Loo System Model B 1040 Standard installed strictly in accordance with manufacturers instructions, unit comprising of top unit and two x louvred inlets (PL.1), drying plate (PL.2), two x air inlets (PL.3), 2300mmlong outlet vent pipe (PL.5), ventilation extraction unit (PL.6) fixed to wall with vent wall bracket (PL.7), 1 bag mounting screws and organic starter, | | | | |
| | enzyme and toilet cleaner (PL.8) | No | 4 | | |
| 3 | Supply and install pre-cast concrete double wash⊡trough, complete with all necessary 19mm galvanised pipework including soakaway size 1000 x 1000 x 1000mm covered with "bidim" | No | 4 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 8 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | l |
|----|--|----|------|---|---|
| | INSPECTION BY ENVIRO-LOO/SUPPLIER | | | | |
| 4 | Two site visits to be made by the "Enviro loo" suppliers to assist/support the contractor in the installation of the "enviro loo" and a final inspection to be ascertain the enviro loo has been installed correctly at which time a Certificate of Compliance should be issued between the Department of Education Limpopo and Enviro Loo Options Limpopo | | ltem | | |
| | White glazed fireclay or vitreous china coupling with SABS specification 497 in | | | | |
| 5 | Lecico Atlas 50cm basin colour White, fixed with stainless steel screws and washers to plugs in wall and sealed with abe Dow Corning acetoxy silicone sealant where basin meets wall. • Material: Vitreous China • Basin code: (ATLBASWHU0500UE) • Height: 500mm • Width: 410mm • Depth: 480mm | No | 2 | | |
| 6 | Elbow taps | No | 2 | | 1 |
| 0 | RAINWATER DISPOSAL | NO | 2 | | 1 |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 7 | 150 x150mm Box gutters | m | 7 | | 1 |
| 8 | 100 x 75mm Rainwater pipes | m | 3 | | 1 |
| 9 | Extra over gutter for stopped end | No | 2 | | 1 |
| 10 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | 1 |
| 11 | Extra over rainwater pipe for bend | No | 2 | | 1 |
| 12 | Extra over rainwater pipe for shoe | No | 2 | | |
| | Carried Forward Section No. 8 Bill No. 10 Plumbing and Drainage Diatho Consulting (PTY) LTD | | | R | |
| | | | | | 1 |

| 13 Extra over rainwater pipe for eaves or plinth offset No 2 13 Image: state of the stat | | R | | | 1 | Brought For | |
|---|---|---|---|--|----|--|----|
| | | | 2 | | No | Extra over rainwater pipe for eaves or plinth offset | 13 |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Carried Forward R Section No. 8 | | R | | | I | | |
| Bill No. 10 Plumbing and Drainage | | | | | | Bill No. 10 | |
| Diatho Consulting (PTY) LTD | | | | | | | |
| | 1 | | | | | | |

| | Brought Forward | | | R | |
|----|---|----|---|---|--|
| | SANITARY FITTINGS | | | | |
| | <u>"Vaal" or similar approved:</u> | | | | |
| 14 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 3 | | |
| 15 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 4 | | |
| 16 | Flat back urinal overall size 295 x 315 x 415mm high with 40mm chromium plated domical grating (Code 878720) and top inlet spreader (Code 8543) with two hanger brackets with flushmaster junior (Code 812720) hung to wall | | | | |
| | | No | 3 | | |
| 17 | 19mm chrome plated push button taps to wash troughs | No | | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 18 | 50mm Code 365 CP bottle trap | No | 3 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 19 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 7 | | |
| 20 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 3 | | |
| | <u>SUNDRIES</u> | | | | |
| 21 | Stainless-steel 24L SHE-BIN plugged to wall | No | | | |
| | SANITARY PLUMBING | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 8 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | uPVC pipes: | | | | |
| 22 | 50mm Pipes | m | 30 | | |
| 23 | 110mm Pipes | m | 20 | | |
| 24 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 90 | | |
| 25 | Ditto, but 110mm diameter | m | 60 | | |
| | Extra over uPVC pipes for fittings: | | | | |
| 26 | 50mm Bend | No | 12 | | |
| 27 | 50mm Junction | No | 12 | | |
| 28 | 50mm Junction with cleaning eye and lid | No | 12 | | |
| 29 | 110mm Straight pan connector | No | 4 | | |
| 30 | 110mm Bend | No | 8 | | |
| 31 | 110mm Junction | No | 8 | | |
| 32 | 110mm Reducing junction | No | 12 | | |
| 33 | 110mm Access bend | No | 4 | | |
| 34 | 110mm Double junction | No | 12 | | |
| 35 | 110mm "GI Two-way" vent valve | No | 4 | | |
| | Testing: | | | | |
| 36 | Testing waste pipe system | | ltem | | |
| | WATER SUPPLIES | | | | |
| | | | | | |
| | Carried Forward Section No. 8 Bill No. 10 Plumbing and Drainage Diatho Consulting (PTY) LTD | | | R | |
| | Plumbing and Drainage | | | | |

| I | Draught Fam. | ard | | R | |
|----|--|------|------|---|---|
| | Brought Forw | aru | | n | |
| | Class 1 copper pipes with capillary couplings: | | | | |
| 37 | 15mm Pipe fixed to walls, in chases, etc | m | 30 | | |
| 38 | Ditto, but 22mm diameter | m | 50 | | |
| | Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 39 | 15mm Fittings | No | 50 | | |
| 40 | 22mm Fittings | No | 50 | | |
| | Testing: | | | | |
| 41 | Testing water pipe system | | Item | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | _ |
| | Carried Forward to Summary of Section N | o. 8 | | R | |
| | Section No. 8 Bill No. 10 | | | | = |
| | Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Float glass:</u> | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 8 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|---|-----|---|---|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m | 2 4 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | _ |
| | Carried Forward to Summary of Section No. 8 | | R | = |
| | Section No. 8 Bill No. 11 Glazing | | | |
| | Glazing Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 8 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | | |
| | Carried Forward Section No. 8 Bill No. 12 Paintwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | R | |
|---|---|---|--|
| Previously painted wood surfaces: | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | |
| PAINT SPECIFICATIONS | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | |
| COLOURS | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | |
| | | | |
| PAINTWORK, ETC TO NEW WORK | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | |
| Fascias and barge boards, including priming metal jointing strips m2 | 4 | | |
| METAL SURFACES WITH | | | |
| | | | |
| | | | |
| Carried Forward | | R | |
| Section No. 8 Bill No. 12 Paintwork | | | |
| Diatho Consulting (PTY) LTD | | | |
| | | | |

1

| | Brought Forward | I | I | R | I |
|---|--|----|----|---|---|
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Door frames | m2 | 11 | | |
| 3 | Windows | m2 | 7 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 26 | | |
| | ON WOOD SURFACES | | | | |
| | One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: | | | | |
| 6 | Doors | m2 | 21 | | |
| 7 | Roof timbers at eaves and verges | m2 | 30 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 51 | | |
| | Carried Forward to Summary of Section No. 8 Section No. 8 Bill No. 12 Paintwork Diatho Consulting (PTY) LTD | | | R | |

| Bill | SECTION SUMMARY - M4 + 3UR Male Learners Ablutions | Page | | Amount |
|----------------|--|------------------|---|--------|
| No 1 | Earthwork | No 285 | | |
| 2 | Concrete, Formwork, and Reinforcement | | | |
| 3 | | 289 | | |
| | Masonry | 293 | | |
| 4 | Waterproofing | 295 | | |
| 5 | Roof covering | 297 | | |
| 6 | Carpentry and Joinery | 300 | | |
| 7 | Ironmongery | 303 | | |
| 8 | Metalwork | 306 | | |
| 9 | Plastering | 310 | | |
| 10 | Plumbing and Drainage | 322 | | |
| 11 | Glazing | 324 | | |
| 12 | Paintwork | 327 | | |
| | Carried to Final Summary Section No. 8 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 1 Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

| Brought Forward | d |
|-----------------|---|
|-----------------|---|

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 9 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | <u>Filling</u> | | | | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 4 | | |
| 2 | Trenches | m3 | 9 | | |
| 3 | Trenches and holes for thickening under surface beds, etc | m3 | 2 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 4 | Soft rock | m3 | 1 | | |
| 5 | Hard rock | m3 | 1 | | |
| | Extra over all excavations for carting away: | | | | |
| 6 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 11 | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 9 Bill No. 1 | | | R | |
| | Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing TIhabeleni Primary School

Rev.06

| | Brought Forward | | | R | 1 |
|----|---|----|------|---|---|
| | Risk of collapse of excavations: | | | | 1 |
| 7 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 58 | | l |
| | Keeping excavations free of water: | | | | I |
| 8 | Keeping excavations free of all water other than subterranean water | | ltem | | l |
| | FILLING ETC | | | | 1 |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 9 | Backfilling to trenches, holes, etc | m3 | 3 | | I |
| | <u>G5 filling material supplied by the contractor, compacted to 95% Mod AASHTO density:</u> | | | | l |
| 10 | Under floors, steps, pavings, etc | m3 | 4 | | I |
| | Compaction of surfaces: | | | | 1 |
| 11 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 29 | | |
| | Prescribed density tests on filling: | | | | 1 |
| 12 | "Modified AASHTO Density" test | No | 4 | | 1 |
| | SOIL POISONING | | | | 1 |
| | Soil insecticide in accordance with SANS 5859: | | | | I |
| 13 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 32 | | |
| | | | | _ | |
| | Carried Forward Section No. 9 Bill No. 1 Earthwork | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|---|----|---|--|
| 14 | To bottoms and sides of trenches, etc m2 | 42 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 9 | | R | |
| | Section No. 9 Bill No. 1 | | | |
| | Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 2 Concrete, Formwork and Reinforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | 1164.00 |
|--|---|---------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 9 Bill No. 2 Concrete, Formwork and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | UNREINFORCED CONCRETE CAST AG | ht Forward | | R | |
|---|--|------------|---|---|--|
| | EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 1 | | |
| | Carrie Section No. 9 Bill No. 2 Concrete, Formwork and Reinforcement Diatho Consulting (PTY) LTD | ed Forward | | R | |

| | Brought Forward | ı | | R | |
|---|--|----|----|---|--|
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| | Strip footings | m3 | 3 | | |
| | Surface beds on waterproofing | m3 | 3 | | |
| | TEST BLOCKS | | | | |
| 2 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 3 | Surface beds, slabs, etc | m2 | 25 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 4 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 51 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 5 | Not exceeding 300mm high to edges of surface beds | m | 51 | | |
| | Saw-cut joints: | | | | |
| 6 | 6 x 10mm Saw-cut joints in top of concrete | m | 67 | | |
| | REINFORCEMENT (PROVISIONAL) | | | | |
| | | | | | |
| | Carried Forward Section No. 9 Bill No. 2 | 1 | | R | |
| | Concrete, Formwork and Reinforcement | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | I | | |

| ĺ | Brought Forward | | | R | |
|---|--|----|------|---|--|
| | Mild steel reinforcement to structural concrete work: | | | | |
| 7 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,08 | | |
| | High tensile steel reinforcement to structural concrete work: | | | | |
| 8 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,19 | | |
| | Fabric reinforcement: | | | | |
| 9 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 25 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 9 Section No. 9 | | | R | |
| | Bill No. 2 Concrete, Formwork and Reinforcement | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 3 Masonry | | ĸ | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|--|
| | Hollow walls: | | | | |
| | Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| | Bagged and sealed walls: | | | | |
| | Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| | Face bricks : | | | | |
| | Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| | All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| | Pointing: | | | | |
| | Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | | |
| | FOUNDATIONS (PROVISIONAL) | | | | |
| | Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| 1 | One brick walls | m2 | 13 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 2 | 150mm Wide reinforcement built in horizontally | m | 75 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|---|--|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 4 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 72 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 63 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 62 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 233 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 28 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 12 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 143 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | • | • | | |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 8 | | |
| 12 | Fair raking cutting | m | 11 | | |
| | Brick-on-edge header course coping, sills, etc. of face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 7 | R | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | | | _ | |
| | Carried Forward Section No. 9 Bill No. 4 Waterproofing | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| ĺ | Brought Forward | | | R | | |
|---|---|----|----|---|--|--|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | | |
| | One layer 375 micron embossed polyethylene dampproof course (SANS 952-1985 type B): | | | | | |
| 1 | In walls | m2 | 72 | | | |
| 2 | In walls vertically at reveals | m2 | 5 | | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | | |
| 3 | Under surface beds | m2 | 30 | | | |
| | JOINT SEALANTS ETC | | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 67 | | | |
| | White silicone sealing compound including backing cord, bond breaker, primer, etc | | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 57 | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | Carried Forward to Summary of Section No. 9 | | | R | | |
| | Section No. 9 Bill No. 4 Waterproofing | | | N | | |
| | Diatho Consulting (PTY) LTD | | | | | |
| | | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | Carried Forward Section No. 9 Bill No. 5 Roof Covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|----|---|---|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 44 | | |
| | Accessories: | | | | |
| 2 | Apex flashings 462mm girth | m | 9 | | |
| | ROOF AND WALL INSULATION | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at | | | | |
| | edges where required | m2 | 44 | | |
| | | | | | |
| | | | | | - |
| | Carried Forward to Summary of Section No. 9 Section No. 9 Bill No. 5 Roof Covering | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.6 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 6 Carpentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|---|----|---|--|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
| | Particle board | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| | <u>Sizes:</u> | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| | Prices | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | | |
| | ROOFS, ETC | | | | |
| | Sawn softwood grade 5: | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 16 | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 51 | | |
| | | | | | |
| | Carried Forward Section No. 9 | | | R | |
| | Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|----------|---|
| 3 | 50 x 76mm Purlins | m | 52 | <u>p</u> | |
| | EAVES, VERGES, ETC | | | | |
| | Medium density plain fibre-cement fascias and barge boards: | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 20 | | |
| | DOORS, ETC | | | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 5 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm undercut (D2) | No | 7 | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | | | | |
| | | No | 2 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 9 | | | R | |
| | Section No. 9 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | 1 |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 5 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|---|---|-------|-----|---|---|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 5 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres</u> | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 10 | | |
| | DOOR CLOSERS | | | | |
| | "Dorma" or similar approved: | | | | |
| 7 | "Dorma" TS73N/EN3-4 parallel arm door closer delayed closing-push side fitting. | No | 1 | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | "Dorma" or similar approved: | | | | |
| 8 | DSS-131 Engraved "Female" information sign, plugged | No | 2 | | |
| | SUNDRIES | | | | |
| 9 | 25mm Diameter wall mounted door stop plugged | No | 9 | | |
| | BATHROOM FITTINGS | | | | |
| | | | | | |
| | | | | | _ |
| | Carried Forward Section No. 9 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|---|---|--|
| | "Vaal Paragon" or similar approved | | | | |
| 10 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 1 | | |
| 11 | Brushed stainless steel body, rust resistant, she bin, approximately 330 x 280 x 180mm etc | No | 1 | | |
| | "Kimberley-Clark"or similar approved | | | | |
| 12 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | No | 6 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 9 | | | R | |
| | Section No. 9 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 8 Metalwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | | l D | 1 1 | |
|---|--|-----|-----|--|
| Brought Forward | | ĸ | | |
| Fixing: | | | | |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | | |
| References: | | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | | |
| • 21111/FSPS/S005 | | | | |
| and bound into the back of these bills of quantities | | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| Carried Forward Section No. 9 | | R | | |
| Bill No. 8 Metalwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | | R | l |
|---|--|----|---|---|---|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 5 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 1 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 4 | Window type NE1, 533 x 654mm high (N1) | No | 7 | | |
| 5 | Window type NE7, 1022 x 654mm high (N2) | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 9 | | | R | |
| | Section No. 9 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 9 Plastering | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 9 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

R

| Brought Forwar | |
|----------------|---|
| | α |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 9 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|------|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 23 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 23 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 9 | | | R | |
| | Section No. 9 Bill No. 9 Plastering | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.10 | | | |
| | PLUMBING AND DRAINAGE (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Wire gratings: | | | |
| | Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 9 Bill No. 10 Plumbing and Drainage | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | R | |
|--|---|--|
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| Carried Forward | R | |
| Section No. 9 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 9 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 9 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| Brought Forward | R | |
|---|---|--|
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| Carried Forward | R | |
| Section No. 9 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|---|---|--|
| General: | | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | | |
| As-built drawings: | | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | | |
| | | |
| Carried Forward Section No. 9 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | ENVIRO-LOO TOILET SYSTEMS | | | | |
| 1 | Enviro-loo industrial system CER/ABS-V1 (Code FG⊡1040STDCA/A) | No | 7 | | |
| 2 | Enviro Loo System Model B 1040 Standard installed strictly in accordance with manufacturers instructions, unit comprising of top unit and two x louvred inlets (PL.1), drying plate (PL.2), two x air inlets (PL.3), 2300mmlong outlet vent pipe (PL.5), ventilation extraction unit (PL.6) fixed to wall with vent wall bracket (PL.7), 1 bag moutting screws and organic starter, | | _ | | |
| • | enzyme and toilet cleaner (PL.8) | No | 1 | | |
| 3 | Supply and install pre-cast concrete double wash⊡trough, complete with all necessary 19mm galvanised pipework including soakaway size 1000 x 1000 x 1000mm covered with "bidim" | No | 7 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| | INSPECTION BY ENVIRO-LOO/SUPPLIER | | | | |
| 4 | Two site visits to be made by the "Enviro loo" suppliers to assist/support the contractor in the installation of the "enviro loo" and a final inspection to be ascertain the enviro loo has been installed correctly at which time a Certificate of Compliance should be issued between the Department of Education Limpopo and Enviro Loo Options Limpopo | | Item | | |
| | White glazed fireclay or vitreous china coupling with SABS specification 497 in | | | | |
| 5 | Lecico Atlas 50cm basin colour White, fixed with stainless steel screws and washers to plugs in wall and sealed with abe Dow Corning acetoxy silicone sealant where basin meets wall. • Material: Vitreous China • Basin code: (ATLBASWHU0500UE) • Height: 500mm • Width: 410mm • Depth: 480mm | No | 2 | | |
| 6 | Elbow taps | No | 2 | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 7 | 150 x150mm Box gutters | m | 9 | | |
| 8 | 100 x 75mm Rainwater pipes | m | 5 | | |
| 9 | Extra over gutter for stopped end | No | 2 | | |
| 10 | Extra over gutter for outlet for 100 x 75mm pipe | No | 2 | | |
| 11 | Extra over rainwater pipe for bend | No | 2 | | |
| 12 | Extra over rainwater pipe for shoe | No | 2 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|---|---|----------|
| 13 | Extra over rainwater pipe for eaves or plinth offset | No | 2 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | \vdash |
| | Carried Forward Section No. 9 | | | R | |
| | Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | | | | | |
|----|---|----|----|---|------|
| | Brought Forward | | | R | |
| | SANITARY FITTINGS | | | | |
| | <u>"Vaal" or similar approved:</u> | | | | |
| 14 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 5 | | |
| 15 | "Daisy Elite" 772403 close-coupled WC suite comprising pan with double flap heavy duty thermoset seat (Code: 8531Z0) and matching 9 litre cistern | No | 7 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 16 | 50mm Code 365 CP bottle trap | No | 5 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 17 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 12 | | |
| 18 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 5 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 19 | 50mm Pipes | m | 25 | | |
| 20 | 110mm Pipes | m | 35 | | |
| 21 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 33 | | |
| 22 | Ditto, but 110mm diameter | m | 46 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 9 Bill No. 10 Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | | |

| | Brought For | ward | | R | |
|----|--|------|------|---|--|
| | Extra over uPVC pipes for fittings: | | | | |
| 23 | 50mm Bend | No | 10 | | |
| 24 | 50mm Junction | No | 10 | | |
| 25 | 50mm Junction with cleaning eye and lid | No | 10 | | |
| 26 | 110mm Straight pan connector | No | 7 | | |
| 27 | 110mm Bend | No | 14 | | |
| 28 | 110mm Junction | No | 14 | | |
| 29 | 110mm Reducing junction | No | 21 | | |
| 30 | 110mm Access bend | No | 7 | | |
| 31 | 110mm Double junction | No | 21 | | |
| 32 | 110mm "GI Two-way" vent valve | No | 7 | | |
| | Testing: | | | | |
| 33 | Testing waste pipe system | | Item | | |
| | WATER SUPPLIES | | | | |
| | Class 1 copper pipes with capillary couplings: | | | | |
| 34 | 15mm Pipe fixed to walls, in chases, etc | m | 36 | | |
| 35 | Ditto, but 22mm diameter | m | 60 | | |
| | Extra over Class 1 copper pipes for capillary fittings: | | | | |
| 36 | 15mm Fittings | No | 60 | | |
| 37 | 22mm Fittings | No | 60 | | |
| | | | | | |
| | | | | | |
| | Carried Forv | ward | | R | |
| | Section No. 9 Bill No. 10 | | | | |
| | Plumbing and Drainage | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|---|------|---|--|
| | Testing: | | | |
| 38 | Testing water pipe system | ltem | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 9 | | R | |
| | Section No. 9 Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Float glass:</u> | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 9 Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|--|---|---|--|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m2 | 4 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 9 Section No. 9 | | R | |
| | Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 9 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | | |
| | Carried Forward Section No. 9 Bill No. 12 Paintwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|---|----|---|---|--|
| Previously painted wood surfaces: | | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | | |
| PAINT SPECIFICATIONS | | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | | |
| COLOURS | | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | | |
| | | | | |
| PAINTWORK, ETC TO NEW WORK | | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | | |
| Fascias and barge boards, including priming metal jointing strips | m2 | 5 | | |
| METAL SURFACES WITH | | | | |
| | | | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 9 Bill No. 12 Paintwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| | Brought Forward | I | | R | I |
|---|---|----|----|---|---|
| | One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel: | | | | |
| 2 | Door frames | m2 | 17 | | |
| 3 | Windows | m2 | 9 | | |
| 4 | Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| 5 | Extra over for paintwork in the "Deep" colour group | m2 | 33 | | |
| | ON WOOD SURFACES | | | | |
| | <u>One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on:</u> | | | | |
| 6 | Doors | m2 | 32 | | |
| 7 | Roof timbers at eaves and verges | m2 | 33 | | |
| 8 | Extra over for paintwork in the "Deep" colour group | m2 | 65 | | |
| | Carried Forward to Summary of Section No. 9 Section No. 9 Bill No. 12 Paintwork Diatho Consulting (PTY) LTD | | | R | |

| Bill No | SECTION SUMMARY - F7 Female Learners Ablutions | Page No | | Amount |
|------------|--|------------|---|--------|
| 1 | Earthwork | 333 | | |
| 2 | Concrete, Formwork and Reinforcement | 338 | | |
| 3 | Masonry | 342 | | |
| 4 | Waterproofing | 344 | | |
| 5 | Roof Covering | 346 | | |
| 6 | Carpentry and Joinery | 349 | | |
| 7 | Ironmongery | 353 | | |
| 8 | Metalwork | 356 | | |
| 9 | Plastering | 360 | | |
| 10 | Plumbing and Drainage | 372 | | |
| 11 | Glazing | 374 | | |
| 12 | Paintwork | 377 | | |
| | Carried to Final Summary Section No. 9 Diatho Consulting (PTY) LTD | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.1 | | | |
| | EARTHWORKS (PROVISIONAL) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be included in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" or "soft rock". | | | |
| | The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock". | | | |
| | The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, therefore "earth", but possibly interspersed with "hard rock". | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 10 Bill No. 1 Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth". The trial holes also indicate that the water table is at a maximum depth of approximately 1000mm.

A soils investigation has been carried out on site by the engineer and the report is annexed to these bills of quantities. Descriptions of excavations shall be deemed to include all ground conditions classifiable as "earth" described in the above report and where conditions of a more difficult character are indicated these are separately measured

Subterranean water:

No subterranean water is expected

Should the Contractor however, encounter any subterranean water on the site, he shall immediately notify the Principal Agent thereof and submit recommendations for keeping the works free from subterranean water together with all costs involved therewith

Excavation for working space in rock:

Notwithstanding clause 10 measurement rule 27 of the Standard System of Measuring Building Work, excavation for working space in material of a more different character (e.g. soft or hard rock) will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carting away of excavated material

Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site

Carried Forward

Section No. 10 Bill No. 1 Earthwork

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|---|----|-----|---|--|
| | <u>Filling</u> | | | | |
| | Notwithstanding the reference to prescribed multiple handling in clause 1 page 10 of the Standard System (7th Edition, 2015) of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material | | | | |
| | Testing: | | | | |
| | Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| | | | | | |
| | EXCAVATIONS, FILLING, ETC | | | | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels under floors | m3 | 4 | | |
| 2 | Trenches | m3 | 9 | | |
| 3 | Trenches and holes for thickening under surface beds, etc | m3 | 1 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 4 | Soft rock | m3 | 1 | | |
| 5 | Hard rock | m3 | 0,5 | | |
| | Extra over all excavations for carting away: | | | | |
| 6 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 11 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 10 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

TMT-LDOE-2023/24-LPCL23/02D Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Risk of collapse of excavations: | | | P | |
| 7 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 30 | | |
| | Keeping excavations free of water: | | | | |
| 8 | Keeping excavations free of all water other than subterranean water | | Item | | |
| | FILLING ETC | | | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 9 | Backfilling to trenches, holes, etc | m3 | 3 | | |
| | <u>G5 filling material supplied by the contractor.</u> compacted to 95% Mod AASHTO density: | | | | |
| 10 | Under floors, steps, pavings, etc | m3 | 4 | | |
| | Compaction of surfaces: | | | | |
| 11 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 29 | | |
| | Prescribed density tests on filling: | | | | |
| 12 | "Modified AASHTO Density" test | No | 4 | | |
| | SOIL POISONING | | | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 13 | Soil insecticide (protection against termites) applied as specified under floors, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 29 | | |
| | Carried Forward | | | R | |
| | Section No. 10 Bill No. 1 Earthwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|--|----|---|--|
| 14 | To bottoms and sides of trenches, etc m2 | 45 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 10 | | R | |
| | Section No. 10 Bill No. 1 | | | |
| | Earthwork | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.2 | | | |
| | CONCRETE, FORMWORK AND REINFORCEMENT | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | <u>Cost of tests:</u> | | | |
| | Breeze concrete: | | | |
| | Breeze concrete shall consist of twelve parts clean dry furnace ash, free from coal or other foreign matter, to one part cement (1:12); the ash graded up to particles which will pass a 16,5mm ring from a minimum which fails to pass a 4,75mm mesh. The finer materials from the screening are to be first mixed with the cement into a mortar and the ash added afterwards and thoroughly incorporated | | | |
| | | | | |
| | Carried Forward Section No. 10 Bill No. 2 Concrete,Formwork and Reinforcement | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | | 1.00 |
|--|---|------|
| Brought Forward | R | |
| Lightweight concrete: | | |
| Lightweight concrete shall have a density of 600kg/m ³ for the top 50mm and 400kg/m ³ for the remaining thickness. The minimum thickness at outlets, channels, etc shall be 50mm | | |
| Waterproof concrete: | | |
| "Waterproof concrete" shall have the same properties as normal concrete, but the following shall be modified to make the the concrete more water-tight: 1. a cement/water ratio of minimum 1.9 and maximum 2.1 | | |
| 2. minimum OPC content of 300kg/m3 3. Polypropolene micro fibres added to concrete at rate of 182 million per m3 | | |
| Formwork: | | |
| Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use | | |
| The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself | | |
| Formwork to soffits of solid slabs, etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described | | |
| Formwork to soffits of slabs, beams, etc shall be deemed to be propped up exceeding 1,5m and not exceeding 3,5m high unless otherwise described | | |
| | | |
| Carried Forward Section No. 10 Bill No. 2 Concrete,Formwork and Reinforcement | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | Brought Forward | ł | | R | |
|---|--|----|----|---|--|
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 15MPa/19mm concrete: | | | | |
| 1 | Surface blinding under footings and bases | m3 | 1 | | |
| | REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | <u>30MPa/19mm concrete:</u> | | | | |
| | Strip footings | m3 | 3 | | |
| | Surface beds on waterproofing | m3 | 3 | | |
| | TEST BLOCKS | | | | |
| 2 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | CONCRETE SUNDRIES | | | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 3 | Surface beds, slabs, etc | m2 | 25 | | |
| | ROUGH FORMWORK (DEGREE OF ACCURACY III) | | | | |
| | Rough formwork to sides: | | | | |
| 4 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 51 | | |
| | MOVEMENT JOINTS, ETC | | | | |
| | Expansion joints with 10mm softboard between vertical concrete and brick surfaces: | | | | |
| 5 | Not exceeding 300mm high to edges of surface beds | m | 56 | | |
| | | | | | |
| | Carried Forward Section No. 10 Bill No. 2 Concrete,Formwork and Reinforcement | ł | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | I | R |
|---|---|----|------|---|
| | Saw-cut joints: | | | |
| 6 | 6 x 10mm Saw-cut joints in top of concrete | m | 67 | |
| | REINFORCEMENT (PROVISIONAL) | | | |
| | Mild steel reinforcement to structural concrete work: | | | |
| 7 | Mild steel bar reinforcement (8 to 40mm diameter bars) | t | 0,08 | |
| | High tensile steel reinforcement to structural concrete work: | | | |
| 8 | High tensile steel bar reinforcement (8 to 40mm diameter bars) | t | 0,19 | |
| | Fabric reinforcement: | | | |
| 9 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 25 | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 10 | | | R |
| | Section No. 10 Bill No. 2 Concrete,Formwork and Reinforcement | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |
| | | I | I | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.3 | | | |
| | MASONRY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | BRICKWORK | | | |
| | <u>General:</u> | | | |
| | Non-load bearing brickwork is to be built to full height less 20mm gap next to the ceiling and is to be left for 14 days before grouting up in 1:3 cement mortar. | | | |
| | Sizes in descriptions: | | | |
| | Where sizes in descriptions are given in brick units, "one brick" shall represent the length and "half brick" the width of a brick | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 10 Bill No. 3 Masonry | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | | R | |
|---|----|----|---|--|
| Hollow walls: | | | | |
| Descriptions of hollow walls shall be deemed to include leaving every fifth perpend of the bottom course of the external skin open as a weep hole | | | | |
| Bagged and sealed walls: | | | | |
| Walls in two skins described as "bagged and sealed" shall be deemed to include having the outer face of the inner skin bagged with 1:6 cement and sand mixture and sealed with two coats bitumen emulsion waterproofing coating | | | | |
| Face bricks : | | | | |
| Bricks shall be ordered timeously to obtain uniformity in size and colour | | | | |
| All face brickwork shall be regularly cleaned down as the work proceeds and shall be protected as necessary by an approved method | | | | |
| Pointing: | | | | |
| Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include smooth floated square recessed, hollow recessed, weathered pointing, etc | | | | |
| | | | | |
| FOUNDATIONS (PROVISIONAL) | | | | |
| Brickwork of NFP bricks (14 MPa nominal compressive strength) in class 1 mortar: | | | | |
| One brick walls | m2 | 13 | | |
| 2,5mm Brickwork reinforcement: | | | | |
| 150mm Wide reinforcement built in horizontally | m | 75 | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 10 Bill No. 3 Masonry | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|---|---|
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 3 | Extra over brickwork for face brickwork | m2 | 4 | | |
| | SUPERSTRUCTURE | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 4 | One brick walls | m2 | 72 | | |
| | BRICKWORK SUNDRIES | | | | |
| | Joint forming material in movement joints: | | | | |
| 5 | 12mm Fibre board built in vertically through brick walls | m | 63 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 6 | 75mm Wide reinforcement built in horizontally | m | 62 | | |
| 7 | 150mm Wide reinforcement built in horizontally | m | 233 | | |
| | Prestressed fabricated concrete lintels, including necessary temporary supports: | | | | |
| 8 | 110 x 75mm Lintels in lengths not exceeding 3m long | m | 28 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 9 | Half brick wall faced on both sides | m2 | 12 | | |
| 10 | Extra over brickwork for face brickwork | m2 | 143 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 10 Bill No. 3 Masonry | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | • | • | | • |

| | Brought Forward | | | R | |
|----|---|---|----|---|--|
| 11 | Extra over brickwork for brick-on-edge header course lintel pointed on face and 120mm soffit | m | 8 | | |
| 12 | Fair raking cutting | m | 10 | | |
| | Brick-on-edge header course coping, sills, etc. of face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with recessed joints on all exposed faces | | | | |
| 13 | 150mm Wide sills set sloping and slightly projecting | m | 6 | | |
| | Carried Forward to Summary of Section No. 10 Section No. 10 Bill No. 3 Masonry Diatho Consulting (PTY) LTD | | | R | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.4 | | | |
| | WATERPROOFING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Waterproofing: | | | |
| | Waterproofing of roofs, basements, etc shall be laid under a ten year guarantee. Waterproofing to roofs shall be laid to even falls to outlets, etc with necessary ridges, hips and valleys. Descriptions of sheet or membrane waterproofing shall be deemed to include additional labour to turn-ups and turn-downs | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 10 Bill No. 4 Waterproofing | | | |
| | Diatho Consulting (PTY) LTD | | | |

| ĺ | Brought Forward | | | R | l |
|---|---|----|----|---|---|
| | DAMPPROOFING OF WALLS AND FLOORS | | | | |
| | One layer 375 micron embossed polyethylene dampproof course (SANS 952-1985 type B): | | | | |
| 1 | In walls | m2 | 72 | | |
| 2 | In walls vertically at reveals | m2 | 5 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 3 | Under surface beds | m2 | 30 | | |
| | JOINT SEALANTS ETC | | | | |
| | <u>Two- part grey polysulphide sealing compound</u> including backing cord, bond breaker, primer, etc | | | | |
| 4 | 6 x 10mm In saw cut joints in floors | m | 67 | | |
| | <u>White silicone sealing compound including backing cord, bond breaker, primer, etc</u> | | | | |
| 5 | 6 x 10mm In expansion joints in floors, including raking out expansion joint filler as necessary [LI] | m | 56 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 10 | | | R | |
| | Section No. 10 Bill No. 4 Waterproofing | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.5 | | | |
| | ROOF COVERINGS | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Profiled metal roof sheeting and accessories shall be supplied with a 10 year guarantee and be installed by an approved installer | | | |
| | All fixing holes shall be drilled and not punched | | | |
| | Roof covering accessories shall be manufactured from the same material as used for roof covering | | | |
| | | | | |
| | PROFILED METAL SHEETING AND ACCESSORIES | | | |
| | | | | |
| | Carried Forward Section No. 10 Bill No. 5 Roof Covering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | | |
|---|---|----|----|---|--|--|
| | 0,6 mm "Klip-Lok 406" or similar approved light industrial Z275 spelter galvanised steel sheeting, with "Classicoat" finish one side and half coat "Classicoat Grey" other side, and accessories fixed to timber purlins or rails at approximately 1500mm centres: | | | | | |
| 1 | Roof coverings with pitch not exceeding 25 degrees | m2 | 40 | | | |
| | Accessories: | | | | | |
| 2 | Apex flashings 462mm girth | m | 8 | | | |
| | ROOF AND WALL INSULATION | | | | | |
| | <u>"Sisalation 405" or similar approved residential grade aluminium foil based insulation:</u> | | | | | |
| 3 | Insulation sheeting laid taut over purlins at approximately 1000mm centres and fixed concurrent with roof covering with minimum 150mm stapled laps, including galvanised steel straining wires at not exceeding 400mm centres and double-sided tape at | | | | | |
| | edges where required | m2 | 40 | | | |
| | | | | | | |
| | Corriad Eastward to Summary of Section No. 40 | | | R | | |
| | Carried Forward to Summary of Section No. 10 Section No. 10 Bill No. 5 Roof Covering | | | к | | |
| | Diatho Consulting (PTY) LTD | | | | | |
| | | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.6 | | | |
| | CARPENTRY AND JOINERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Fixing: | | | |
| | Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins, or to be shot-pinned, to brickwork or concrete | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 500mm centres, and where described as "bolted", the bolts have been given separately elsewhere | | | |
| | Joinery: | | | |
| | Descriptions of frames shall be deemed to include frames, transomes, rails, etc | | | |
| | Carried Forward | | R | |
| | Section No. 10 Bill No. 6 Carpentry and Joinery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|--|---|----|---|------|
| | Descriptions of hardwood joinery shall be deemed to include sinking and pelleting heads and nuts of bolts | | | | |
| | Particle board | | | | |
| | All particle board shall comply with SANS 50312 having the required marking as per SANS 50312/EN 312 | | | | |
| | Decorative thermosetting plastic laminate covering: | | | | |
| | Laminate covering shall be glued under pressure and edge strips of same shall be butt jointed at junctions with adjacent similar finish | | | | |
| | <u>Sizes:</u> | | | | |
| | Sizes are nominal and the Contractor shall make allowance in his prices for minor variances in stated finished sizes of timber doors, door members, door frames, architraves, etc | | | | |
| | Prices_ | | | | |
| | Prices for all joinery work are to include for general framing, housing and notching, arris rounded angles, glueing, blocking, planting on, screwing, adhesives, dowels, pellets, cross tongues, screws and nails and setting up complete and also for all square cutting and waste. Tops shall be secured with metal or hardwood buttons. | | | | |
| | | | | | |
| | ROOFS, ETC | | | | |
| | Sawn softwood grade 5: | | | | |
| 1 | 38 x 114mm Wall plates bolted | m | 27 | | |
| 2 | 38 x 114mm Rafters in lengths exceeding 3,9m and not exceeding 6,6m | m | 85 | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 10 Bill No. 6 | | | | |
| | Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | |] |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | | | R | |
|---|--|----|----|---|---|
| 3 | 50 x 76mm Purlins | m | 88 | | |
| | EAVES, VERGES, ETC | | | | |
| | <u>Medium density plain fibre-cement fascias and barge boards:</u> | | | | |
| 4 | 19 x 235mm Fascias and barge boards, including aluminium H-profile jointing strips | m | 18 | | |
| | DOORS, ETC | | | | |
| | Solid chipcore flush doors with hardwood veneer, hung to steel frames: | | | | |
| 5 | 40mm Door 914 x 2032mm high (D3) | No | 1 | | |
| | Wrought meranti doors hung to steel frames: | | | | |
| 6 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding including 150mm | | | | |
| | undercut (D2) | No | 5 | | |
| 7 | 44mm Framed batten door 813 x 2032mm high of 44 x 150mm top rail and stiles, 22 x 150mm middle ledge and braces and 22 x 220mm bottom rail filled in with 22mm V-jointed one side boarding and including weatherboard (D1) | | | | |
| | | No | 1 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 10 | | | R | |
| | Section No. 10 Bill No. 6 Carpentry and Joinery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | ł |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.7 | | | |
| | IRONMONGERY | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Proprietary items: | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | |
| | Prices are to be based on the specific products/articles specified. | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 10 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | | R | |
|---|---|----|---|---|--|
| | Locks: | | | | |
| | Notwithstanding Clause 2, Item 3 of the "Ironmongery" trade of the Standard System (7th Edition, 2015) of Measuring Building Wor, descriptions of locks shall be deemed to include two keys per lock | | | | |
| | Finishes to ironmongery: | | | | |
| | Where applicable, finishes to ironmongery are indicated by suffixes in accordance with the following list: BS Satin bronze lacquered CH Chromium plated SC Satin chromium plated SE Silver enamelled GE Grey enamelled AN Anodised natural AS Anodised silver AB Anodised bronze AG Anodised gold ABL Anodised black PB Polished brass PL Polished and lacquered PT Epoxy coated SD Sanded BBS Brushed stainless steel | | | | |
| | | | | | |
| | CATCHES, CABIN HOOKS, ETC | | | | |
| 1 | 150mm Cabin hook and eye including 70 x 70 x 20mm chamfered hardwood block twice oiled and plugged | No | 5 | | |
| | LOCKS | | | | |
| | "Union Assa Abloy" or similar approved: | | | | |
| 2 | 50mm Brass padlock | No | 2 | | |
| 3 | Four lever lockset | No | 2 | | |
| | Carried Forward | | | R | |
| | Section No. 10 Bill No. 7 Ironmongery | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|-------|-----|---|--|
| 4 | "Ref. CZ80941SC" Indicator bolt | No | 5 | | |
| | HANDLES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| 5 | ASSA ABLOY Anodised Silver straight pull handle (Code: AL5515-300BBAS) with 300mm fixing centres | Pairs | 2,0 | | |
| | PUSH PLATES AND KICK PLATES | | | | |
| | <u>"Union Assa Abloy" or similar approved:</u> | | | | |
| | <u>1.2mm Thick satin finished "Union" stainless steel plates countersunk screwed along edges at not exceeding 200mm centres</u> | | | | |
| 6 | 200 x 800mm Type "SS5089-200W" kicking plate | No | 10 | | |
| | DOOR CLOSERS | | | | |
| | <u>"Dorma" or similar approved:</u> | | | | |
| 7 | "Dorma" TS73N/EN3-4 parallel arm door closer delayed closing-push side fitting. | No | 1 | | |
| | LETTERS, NAMEPLATES, ETC | | | | |
| | "Dorma" or similar approved: | | | | |
| 8 | DSS-131 Engraved "Female" information sign, plugged | No | 1 | | |
| 9 | DSS-133 Engraved "Disabled" information sign, plugged | No | 1 | | |
| | SUNDRIES | | | | |
| 10 | 25mm Diameter wall mounted door stop plugged | No | 7 | | |
| | | | | | |
| | Carried Forward Section No. 10 Bill No. 7 Ironmongery | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | Brought Forward | | R | 1 |
|----|---|-----|---|---|
| | BATHROOM FITTINGS | | | |
| | "Vaal Paragon" or similar approved | | | l |
| 11 | 32mm Type 9 back grab rail 800mm long plugged N | o 1 | | |
| 12 | 32mm Type 8 side grab rail 900mm girth plugged N | p 1 | | |
| | <u>"Kimberley-Clark"or similar approved:</u> | | | l |
| 13 | "Ref. SQ2 code 405607B" white lockable toilet roll holder | o 6 | | |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | l |
| | | | | |
| | Carried Forward to Summary of Section No. 10 | | R | |
| | Section No. 10 Bill No. 7 Ironmongery | | | |
| | Diatho Consulting (PTY) LTD | | | l |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.8 | | | |
| | METALWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Descriptions of bolts, anchors, etc: | | | |
| | Descriptions of bolts shall be deemed to include nuts and washers | | | |
| | Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete | | | |
| | Items described as "holed for bolt(s)" shall be deemed to exclude the bolts, unless otherwise described | | | |
| | Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres | | | |
| | Carried Forward Section No. 10 Bill No. 8 Metalwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| Brought Forward | | R | 1 1 | 1 |
|---|--|---|-----|---|
| | | | | I |
| Fixing: | | | | I |
| Unless otherwise described, descriptions of items shall be deemed to include for fixing to brickwork or concrete | | | | |
| Where items are described as "bolted", the bolts are measured elsewhere as stated in clause N.7 of the Model Preambles | | | | |
| References: | | | | |
| References in descriptions of windows, doors, gates, etc refer to the respective types of windows, doors, etc detailed in the Architect's window schedules numbered | | | | |
| • 21111/FSPS/S005 | | | | |
| and bound into the back of these bills of quantities | | | | |
| Tenderers are to price the following items in conjunction with the above Architect's drawings, etc and no claim arising from brevity of descriptions in these bills of quantities, of items shown on the Architect's drawings, etc shall be entertained | | | | |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | I |
| | | | | |
| Carried Forward | | R | | I |
| Section No. 10 Bill No. 8 Metalwork | | | | |
| Diatho Consulting (PTY) LTD | | | | 1 |
| | | | | I |
| | | | | |

| | Brought Forward | | | R | |
|---|--|----|---|---|---|
| | STEEL GATES, SCREENS, ETC | | | | |
| | Welded screens and gates, to brickwalls: | | | | |
| 1 | Single gate and frame size to fit standard door, size 813 x 2032mm high | No | 2 | | |
| | PRESSED STEEL DOOR FRAMES | | | | |
| | <u>1,6mm Double rebated frames suitable for half brick</u> walls: | | | | |
| 2 | Frame for door size 813 x 2032mm high | No | 5 | | |
| | <u>1,6mm Double rebated frames suitable for one brick</u> walls: | | | | |
| 3 | Frame for door size 813 x 2032mm high | No | 1 | | |
| 4 | Frame for door size 914 x 2032mm high | No | 1 | | |
| | STEEL WINDOWS, DOORS, ETC | | | | |
| | Standard windows: | | | | |
| 5 | Window type NE1, 533 x 654mm high (N1) | No | 6 | | |
| 6 | Window type NE7, 1022 x 654mm high (N2) | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | ╞ |
| | Carried Forward to Summary of Section No. 10 | | | R | |
| | Section No. 10 Bill No. 8 Metalwork | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.9 | | | |
| | PLASTERING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Moisture tests: | | | |
| | Before any finishes, coverings, etc are applied to screeds, plastering, etc or any other in-situ finish, moisture tests are to be carried out to the complete satisfaction of the Project Manager to ensure that these surfaces have the correct moisture content for the finish to be applied | | | |
| | Labours, etc | | | |
| | Labours such as fair, rounded and chamfered edges, trowel cuts, throats, V-joints, angles, etc shall be deemed to be included in the descriptions | | | |
| | | | | |
| | Convied Ferryard | | | |
| | Carried Forward Section No. 10 Bill No. 9 Plastering | | R | |
| | Diatho Consulting (PTY) LTD | | | |

R

R

Brought Forward

Sample Panels

A sample panel size 1m x1m, of each of the various plaster type wall and floor finishes in this contract, shall be prepared for the approval of the Project Manager and the cost of the sample panel(s) shall be deemed to be included in the overall costs of the <u>relevant</u> wall and floor finishes

GRANOLITHIC

Method:

The method to be used shall be either the monolithic method or the bonded method

Preparation:

For granolithic applied monolithically, the concrete floor shall be swept clean after bleeding of the concrete has ceased and the slab has begun to stiffen; any remaining bleed water shall be removed and the granolithic applied immediately thereafter. For granolithic to be bonded to the floor slab after it has hardened, the slab surface shall be hacked (preferably by mechanical means) until all laitance, dirt, oil, etc is dislodged and swept clean of all loose matter. The slab shall then be wetted and kept damp for at least six hours before applying the granolithic

Mix:

Unless otherwise described, granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SANS 1083 and shall generally be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Carried Forward

Section No. 10 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

R

R

| Brought | Forward |
|---------|-------------|
| Diougin | . I OI Wala |

Panels:

Granolithic shall be laid in panels not exceeding 14m² for monolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width

Where possible joints between panels shall be positioned over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with V-joints

Laying:

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand-and-cement slurry brushed over the surface and allowed to partially set before applying the granolithic. The granolithic shall be throughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened. Any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection:

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Colour:

Coloured granolithic shall be tinted with an approved colouring pigment mixed into a true and even colour

Carried Forward

Section No. 10 Bill No. 9 Plastering

Diatho Consulting (PTY) LTD

| | Brought Forward | | | R | |
|---|--|----|----|---|---|
| | TINTED WHITE CEMENT SCREEDS | | | | |
| | Tinted screed shall be composed of one bag White Portland Cement and two wheelbarrows "Malmesbury" sand. Surfaces shall be finished with a steel trowel to leave a smooth finish and coated with two coats "Earthcote S.I. Floorcote" two-pack polyurethane floor sealer applied as per the manufacturer's recommendations | | | | |
| | NOTE: Tinted screeds are to be strengthened with "Primal Eccos" acrylic polymer (15% of the water volume is to be substituted with the acrylic polymer during the mixing process) | | | | |
| | Coarse sand is to be used for these screeds | | | | |
| | All tinting, finishing, strengthening, etc are to be mixed, applied, etc strictly in accoprdance with the manufacturer's instructions | | | | |
| | CEMENT PLASTER | | | | |
| | Unless otherwise described, cement plaster shall be taken to mean Class 1 cement plaster i.e. 1:4 cement:sand plaster (common cement) | | | | |
| | | | | | |
| | CEMENT SCREEDS TO CONCRETE | | | | |
| | Cement screeds steel trowelled, on concrete: | | | | |
| 1 | 30mm Thick to floors | m2 | 25 | | |
| | FLOOR AND WALL SEALERS | | | | |
| | <u>Minimum two coats approved epoxy coat, on</u> <u>concrete:</u> | | | | |
| 2 | On screed | m2 | 25 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 10 | | | R | |
| | Section No. 10 Bill No. 9 Plastering | | | | _ |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Quantity | Rate | Αmoι |
|---|----------|------|------|
| SECTION NO. 10 | | | |
| BILL NO.10 | | | |
| PLUMBING AND DRAINAGE (PROVISIONAL) | | | |
| | | | |
| PREAMBLES | | | |
| The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| SUPPLEMENTARY PREAMBLES | | | |
| Wire gratings: | | | |
| Descriptions of gutter outlets, etc shall be deemed to include wire balloon gratings | | | |
| Stormwater channels: | | | |
| Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | | | |
| Carried Forward | | R | |
| Section No. 10 Bill No. 10 Plumbing and Drainage | | | |
| Diatho Consulting (PTY) LTD | | | |

| | | • |
|--|---|-------|
| Brought Forward | R | |
| French drains: | | |
| Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | |
| Septic tanks: | | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | | |
| <u>Stainless steel basins, sinks, wash troughs, urinals, etc:</u> | | |
| Stainless steel for economy basins, domestic sinks and worktops shall be Type 430 (17/0) | | |
| Stainless steel for urinals, basins, quality sinks, wash troughs, institutional equipment, etc shall be Type 304 (18/8) | | |
| Stainless steel for laboratory sinks, photographic equipment, etc shall be Type 316 (18/8) | | |
| Units shall have standard aprons on all exposed edges and tiling keys against walls where applicable | | |
| Sealing of edges: | | |
| Outer edges of sinks, basins, baths, urinals, etc are to be sealed against adjacent surfaces with approved mildew resistant silicone sealant and prices must include therefor | | |
| | | |
| Carried Forward | R | |
| Section No. 10 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R | |
|--|---|--|
| uPVC pipes and fittings: | | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | | |
| uPVC pressure pipes and fittings: | | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | | |
| High density polyethylene (HDPe) pipes and fittings: | | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | | |
| "Polycop" polypropylene pipes: | | |
| Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings | | |
| Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Carried Forward | R | |
| Section No. 10 Bill No. 10 Plumbing and Drainage | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

R

R

Brought Forward

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016. Only compression fittings shall be used in walls or in ground

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claims for extra bushes, reducers, etc will be entertained

Fixing of pipes:

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls, etc casting in, building in or suspending not exceeding 1m below suspension level

Paper wrapping to pipes:

Pipes chased into brickwork must be wrapped with two layers of stout brown paper tied with wire. Rates are to include for wrapping around joints and fittings

Carried Forward

Section No. 10 Bill No. 10 Plumbing and Drainage

Diatho Consulting (PTY) LTD

| Brought Forward | R | |
|---|---|--|
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SANS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SANS 1200L : Medium-pressure pipelines SANS 1200LD : Sewers SANS 1200LE : Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| Carried Forward | | |
| Section No. 10 Bill No. 10 Plumbing and Drainage | R | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| Brought Forward | R |
|---|---|
| <u>General:</u> | |
| Descriptions of cast iron roof outlets shall be deemed to include joints to pipes and casting into concrete (adaptors for joints to PVC pipes, etc are given separately) | |
| Descriptions of overflow pipes where measured in number, shall be deemed to include joints to cisterns and splay cut ends | |
| Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | |
| Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | |
| Descriptions of WC pans, slop hoppers, etc shall be deemed to include for joints to soil pipes (pan connectors are separately measured) and shall have straight or side outlets and "P" or "S" traps as necessary | |
| Description of waste unions shall be deemed to include rubber or vulcanite plugs and chains fixed to fittings. | |
| As-built drawings: | |
| Where required, the Contractor shall prepare an updated set of as-built drawings. At completion of the contract the Contractor shall hand these drawings to the Project Manager for reproducing onto the originals for handing over to the Employer (provision for allowance of as-built drawings elsewhere) | |
| | |
| Carried Forward Section No. 10 Bill No. 10 Plumbing and Drainage | R |
| Diatho Consulting (PTY) LTD | |
| | |

| | | | | | Nev.00 |
|---|--|----|---|---|--------|
| | Brought Forward | | | R | |
| | Proprietary items: | | | | |
| | Where applicable, the manufacturers' names or product catalogue titles are given in sub-headings preceding the items | | | | |
| | Note that the manufacturers names specified in this trade are for the purposes of competitive pricing. | | | | |
| | Prices are to be based on the specific products/articles specified. | | | | |
| | On request, returnable samples are to be provided to the Project Manager for consideration | | | | |
| | | | | | |
| | RAINWATER DISPOSAL | | | | |
| | 0,6mm Galvanised sheet steel gutters and rainwater pipes with powder coated finish on outside to match roof sheeting colour: | | | | |
| 1 | 150 x150mm Box gutters | m | 8 | | |
| 2 | 100 x 75mm Rainwater pipes | m | 3 | | |
| 3 | Extra over gutter for stopped end | No | 2 | | |
| 4 | Extra over gutter for outlet for 100 x 75mm pipe | No | 3 | | |
| 5 | Extra over rainwater pipe for bend | No | 3 | | |
| 6 | Extra over rainwater pipe for shoe | No | 3 | | |
| 7 | Extra over rainwater pipe for eaves or plinth offset | No | 3 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 10 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | • | • | | • |

| | | | | | Rev.06 |
|----|--|----|----|---|--------|
| | Brought Forward | | | R | |
| | SANITARY FITTINGS | | | | |
| | "Vaal" or similar approved: | | | | |
| 8 | 455 x 290mm "Hibiscus" 7050 wash hand basin bolted to wall | No | 5 | | |
| 9 | Junior vitreous china low level suite colour White (Code: 751358), comprising 104° outlet washdown pan (Code: 751301) with matching 9 litre front single flush cistern (Code: 7109DP) including lid, fitments and flushpipe and Junior double flap wooden seat (Code: 8518Z0). | No | 5 | | |
| 10 | "Pearl Paraplegic" 7300SC paraplegic WC suite with lid, fitments, purpose made CP side flush lever and purpose made double flap white epoxy painted wooden seat | No | 1 | | |
| | TRAPS, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 11 | 50mm Code 365 CP bottle trap | No | 5 | | |
| | TAPS, VALVES, ETC | | | | |
| | "Cobra Watertech" or similar approved: | | | | |
| 12 | 15mm Code 232/350 FCP angle regulating valve and flexible connection pipe | No | 11 | | |
| 13 | 15mm Code FPT2A1RO-OGP01 "Roma" basin tap with waste union | No | 4 | | |
| 14 | 15mm Code 503-21CP elbow action pillar tap | No | 1 | | |
| | SANITARY PLUMBING | | | | |
| | uPVC pipes: | | | | |
| 15 | 50mm Pipes | m | 25 | | |
| | | | | | |
| | Carried Forward Section No. 10 Bill No. 10 Plumbing and Drainage Diatho Consulting (PTY) LTD | | | R | |
| | | | | | |

| | Brought Forward | ı | | R | |
|----|---|----|------|---|--|
| 16 | 110mm Pipes | m | 6 | | |
| 17 | 50mm Diameter pipe laid in and including trenches not exceeding 1m deep | m | 33 | | |
| 18 | Ditto, but 110mm diameter | m | 6 | | |
| | Extra over uPVC pipes for fittings: | | | | |
| 19 | 50mm Bend | No | 10 | | |
| 20 | 50mm Junction | No | 10 | | |
| 21 | 50mm Junction with cleaning eye and lid | No | 10 | | |
| 22 | 110mm Straight pan connector | No | 6 | | |
| 23 | 110mm Bend | No | 12 | | |
| 24 | 110mm Junction | No | 12 | | |
| 25 | 110mm Reducing junction | No | 18 | | |
| 26 | 110mm Access bend | No | 6 | | |
| 27 | 110mm Double junction | No | 6 | | |
| 28 | 110mm "GI Two-way" vent valve | No | 6 | | |
| | Testing: | | | | |
| 29 | Testing waste pipe system | | Item | | |
| | WATER SUPPLIES | | | | |
| | Class 1 copper pipes with capillary couplings: | | | | |
| 30 | 15mm Pipe fixed to walls, in chases, etc | m | 33 | | |
| 31 | Ditto, but 22mm diameter | m | 55 | | |
| | | | | | |
| | Carried Forward Section No. 10 Bill No. 10 Plumbing and Drainage | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | R | |
|----|--|------|---|---|
| | Extra over Class 1 copper pipes for capillary fittings: | | | |
| 32 | 15mm Fittings No | 55 | | |
| 33 | 22mm Fittings No | 55 | | |
| | Testing: | | | |
| 34 | Testing water pipe system | Item | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 10 | | R | L |
| | Section No. 10 Bill No. 10 Plumbing and Drainage | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.11 | | | |
| | GLAZING | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Float glass: | | | |
| | The term "float glass" is used for monolithic annealed glass | | | |
| | Laminated glass: | | | |
| | Laminated glass to have polyvinyl butyral (PVB) interlayer(s) | | | |
| | | | | |
| | GLAZING TO STEEL WITH PUTTY | | | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 10 Bill No. 11 Glazing | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| | Brought Forward | | R | |
|---|--|---|---|--|
| | 6,38mm Obscure safety glass: | | | |
| 1 | Panes not exceeding 0,1m ² m2 | 4 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward to Summary of Section No. 10 Section No. 10 | | R | |
| | Bill No. 11 Glazing | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 10 | | | |
| | BILL NO.12 | | | |
| | PAINTWORK | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | PREPARATORY WORK TO EXISTING WORK | | | |
| | Previously painted plastered surfaces: | | | |
| | Surfaces shall be thoroughly washed down and allowed to dry completely before any paint is applied. Blistered or peeling paint shall be completely removed and minor cracks shall be opened, filled with a suitable filler and finished smooth | | | |
| | Previously painted metal surfaces: | | | |
| | Surfaces shall be thoroughly rubbed and cleaned down. Blistered or peeling paint shall be completely removed down to bare metal | | | |
| | | | | |
| | Carried Forward Section No. 10 Bill No. 12 Paintwork | | R | |
| | Diatho Consulting (PTY) LTD | | | |

-422-

| Brought Forward | | | R | |
|---|----|---|---|--|
| Previously painted wood surfaces: | | | | |
| Surfaces shall be thoroughly cleaned down. Blistered or peeling paint shall be completely removed and cracks and crevices shall be primed, filled with suitable filler and finished smooth | | | | |
| PAINT SPECIFICATIONS | | | | |
| All painting shall be done in accordance with "Plascon", etc specifications, unless otherwise described | | | | |
| COLOURS | | | | |
| When staining timber, the resultant colour or shade must be to the complete satisfaction of the Project Manager before any overcoating or preservative is applied | | | | |
| Paintwork is classified in the following different colour groups: "White", "Pastel", "Deep" and "Transparent" in accordance with the "Natural Colour System" (NCS) adopted by the SA National Standards Unless otherwise described, all paintwork shall be deemed to be classified in the "White" colour group | | | | |
| | | | | |
| PAINTWORK, ETC TO NEW WORK | | | | |
| ON FIBRE-CEMENT BOARD SURFACES | | | | |
| One coat alkali resistant primer and two coats superior quality acrylic emulsion paint for interior and exterior use, on: | | | | |
| Fascias and barge boards, including priming metal jointing strips | m2 | 5 | | |
| METAL SURFACES WITH | | | | |
| | | | | |
| | | | | |
| Carried Forward | | | R | |
| Section No. 10 Bill No. 12 Paintwork | | | | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

1

| Brought Forward | | | R | |
|--|---|--|---|--|
| <u>One coat alkyd based zinc phosphate primer and two coats premium quality polyurethane enamel paint, on steel:</u> | | | | |
| Door frames | m2 | 13 | | |
| Windows | m2 | 8 | | |
| Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) | m2 | 7 | | |
| Extra over for paintwork in the "Deep" colour group | m2 | 28 | | |
| ON WOOD SURFACES | | | | |
| One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: | | | | |
| Doors | m2 | 25 | | |
| Roof timbers at eaves and verges | m2 | 56 | | |
| Extra over for paintwork in the "Deep" colour group | m2 | 81 | | |
| Carried Forward to Summary of Section No. 10 Section No. 10 Bill No. 12 Paintwork Diatho Consulting (PTY) LTD | | | R | |
| | two coats premium quality polyurethane enamel paint, on steel: Door frames Windows Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) Extra over for paintwork in the "Deep" colour group ON WOOD SURFACES One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: Doors Roof timbers at eaves and verges Extra over for paintwork in the "Deep" colour group Extra over for paintwork in the "Deep" colour group Carried Forward to Summary of Section No. 10 Section No. 10 Bill No. 12 Paintwork | two coats premium quality polyurethane enamel paint, on steel: Door frames m2 Door frames m2 Windows m2 Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area) m2 Extra over for paintwork in the "Deep" colour group m2 ON WOOD SURFACES One coat primer, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on: Doors m2 Roof timbers at eaves and verges m2 Extra over for paintwork in the "Deep" colour group m2 Extra over for paintwork in the "Deep" colour group m2 Roof timbers at eaves and verges m2 Extra over for paintwork in the "Deep" colour group m2 Extra over for paintwork in the "Deep" colour group m2 Section No. 10 Bill No. 12 Paintwork M3 | two coats premium quality polyurethane enamel m2 paint, on steel: m2 Door frames m2 Windows m2 Sides measured over the full flat area) m2 Sides measured over the full flat area) m2 Che coat primer, one coat alkyd based universal m2 Undercoat and two coats superior quality universal m2 namel paint, on: m2 Doors m2 Roof timbers at eaves and verges m2 Extra over for paintwork in the "Deep" colour group m2 Roof timbers at eaves and verges m2 Extra over for paintwork in the "Deep" colour group m2 Roof timbers at eaves and verges m2 Extra over for paintwork in the "Deep" colour group m2 Bill No. 12 Paintwork | two coats premium quality polyurethane ename! III paint, on steel: Door frames m2 13 Undows m2 8 IIII 13 Windows m2 8 IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII |

| Bill | SECTION SUMMARY - GRD5 Grade R Unisex | Page | | Amount |
|----------------|--|------|---|--------|
| No 1 | Earthwork | No | | |
| 2 | | 383 | | |
| | Concrete,Formwork and Reinforcement | 387 | | |
| 3 | Masonry | 391 | | |
| 4 | Waterproofing | 393 | | |
| 5 | Roof Covering | 395 | | |
| 6 | Carpentry and Joinery | 398 | | |
| 7 | Ironmongery | 402 | | |
| 8 | Metalwork | 405 | | |
| 9 | Plastering | 409 | | |
| 10 | Plumbing and Drainage | 419 | | |
| 11 | Glazing | 421 | | |
| 12 | Paintwork | 424 | | |
| | Carried to Final Summary Section No. 10 | | R | |
| | Diatho Consulting (PTY) LTD | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 11 | | | |
| | BILL NO.1 | | | |
| | EXTERNAL WORK (PROVISIONAL) | | | |
| | (ALL TRADES) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The Model Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | Labour Intensive Methods: | | | |
| | The contractor will be required to use labour intensive for items which have been marked with the letters [LI] in the Scope of Work. | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Nature of ground: | | | |
| | The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "soft rock" or "hard rock" | | | |
| | | | | |
| | Carried Forward Section No. 11 | | R | |
| | Bill No. 1 External Work | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

R

R

| | Bro | ught | For | ward |
|--|-----|------|-----|------|
|--|-----|------|-----|------|

The nature of the ground is assumed to be gravel, therefore "earth", but possibly interspersed with "soft rock" or "hard rock"

The nature of the ground is assumed to be silty clay with loose river boulders varying in size up to approximately 450mm diameter, all of which will be deemed as "earth", but possibly interspersed with "hard rock"

Trial holes indicate that the nature of the ground is silty clay to a depth of approximately 500mm with fine to medium loose sandy material below, therefore "earth"

A soils investigation has been carried out on the site by the Engineer and the report is annexed to these bills of quantities. The soils report indicates that the ground varies between transported soils at surface comprising gravel layers of varying thickness and interspersed with clay, and weathered shales varying from very soft rock to medium hard rock consistency, all of which will be deemed as "earth". All very hard unweathered shale, ironstone, etc the removal of which necessitates the use of explosives or heavy duty hydraulic percussion hammers (peckers), will be classified as "hard rock"

Should the Contractor encounter any "soft" or "hard" rock in the excavations, he shall immediately notify the Engineer who shall be the sole arbiter as to what constitutes "soft" or "hard" rock for final account purposes

Subterranean water:

No subterranean water is expected

Excavation for working space in rock:

Notwithstanding clause 11 of the Standard System of Measuring Building Work, excavation for working space in rock will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be

Carried Forward

Section No. 11 Bill No. 1 External Work

Diatho Consulting (PTY) LTD

| Brought Forward | | | R | |
|---|----|-----|---|--|
| Carting away of excavated material: | | | | |
| Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site | | | | |
| Filling: | | | | |
| Notwithstanding the reference to prescribed multiple handling in Clause 1 of the Standard System of Measuring Building Work, prices for filling and backfilling shall include for all selection and any necessary multiple handling of material | | | | |
| <u>Testing:</u> | | | | |
| Prices for backfilling to trenches and holes only are to include for all necessary density tests in accordance with SANS 1200D | | | | |
| Maintenance period: | | | | |
| The maintenance period to civil works such as roads, parking and related earthworks shall be twelve calender months | | | | |
| | | | | |
| SITE CLEARANCE, ETC | | | | |
| Site clearance: | | | | |
| Digging up and removing rubbish, debris, vegetation, hedges, shrubs, bush, etc and trees not exceeding | | | | |
| 200mm girth | m2 | 746 | | |
| Stripping average 150mm thick layer of top soil and depositing material in prescribed stock piles on site | m2 | 746 | | |
| | | | | |
| | | | | |
| Carried Forward Section No. 11 Bill No. 1 External Work | | | R | |
| Diatho Consulting (PTY) LTD | | | | |
| | | | | |

| | Brought Forward | | R | |
|---|--|------|---|--|
| | REMOVAL OF TREES, ETC | | | |
| 3 | Tree stump exceeding 200mm and not exceeding 500mm girth No | 7 | | |
| | PAVINGS, ETC | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Testing of material and filling: | | | |
| | Descriptions of earth filling, compaction, etc shall be deemed to include for all necessary testing required in accordance with the SABS 1200 series | | | |
| | EARTHWORKS | | | |
| | Excavation in earth not exceeding 2m deep: | | | |
| 4 | Over site under paving etc to reduce levels and dispose in prescribed stock piles on site m3 | 180 | | |
| | Extra over all excavations for carting away: | | | |
| 5 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor m3 | 180 | | |
| | Compaction of surfaces: | | | |
| 6 | Rip and re-compact in-situ materials to a depth of 150mm, breaking down over size material and reconsolidate to 93% modified AASHTO density m2 | 500 | | |
| | Keeping excavations free of water: | | | |
| 7 | Keeping excavations free of all water other than subterranean water | ltem | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 11 | | | |
| | Bill No. 1 External Work | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|--|----|-----|---|--|
| | C4 filling supplied and carted on by the Contractor, stabilised with 2.5% OPC cement compacted in layers not exceeding 150mm to 97% Mod. AASHTO density | | | | |
| 8 | Sub-base under roads | m3 | 60 | | |
| | Earth filling from commercial sources supplied by the Contractor under parking areas, roadways, etc: | | | | |
| 9 | Sub-base course of G7 material compacted to 93% Mod AASHTO density | m3 | 60 | | |
| 10 | Base course stabilised G7 material with CEM II 32.5 BV compacted to 97% Mod AASHTO density | m3 | 60 | | |
| | <u>Weedkiller (active ingredients metalaclor 102,8 g/l, terbitilasien 248,6 g/l and atrasien 248,6 g/l) mixed in the proportion of 100 ml weedkiller to 100 l water and applied at a rate of 10 l/m2:</u> | | | | |
| 11 | Under paving, etc | m2 | 400 | | |
| | PRECAST CONCRETE | | | | |
| | Paving of 200 x 100 x 60mm "Type S-A" precast concrete paving bricks with butt joints, on 20mm thick river sand bed with sand-and-cement mixture swept into joints and hosed down, including preparation of ground or filling: | | | | |
| 12 | Paving in herringbone bond pattern to falls | m2 | 700 | | |
| | Precast concrete finished smooth on exposed surfaces, including bedding, jointing and pointing: | | | | |
| 13 | 150 x 300mm High kerbs (SANS 927 fig 8) with 150 x 150 x 300mm unreinforced concrete haunching at back of each joint, including excavation, backfilling, etc | m | 700 | | |
| | | | | | |
| | RAMPS | | | | |
| | Carried Forward | | | R | |
| | Section No. 11 Bill No. 1 External Work | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | | |

Rev.06

| | Brought Forward | | | R | |
|----|---|----|----|---|--|
| | EARTHWORKS | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 14 | Reduced levels under floors | m3 | 2 | | |
| | Extra over all excavations for carting away: | | | | |
| 15 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 2 | | |
| | <u>G7 filling material supplied by the contractor, compacted to 95% Mod AASHTO density:</u> | | | | |
| 16 | Under floors, steps, pavings, etc | m3 | 2 | | |
| | Compaction of surfaces: | | | | |
| 17 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO | | | | |
| | density | m2 | 15 | | |
| | Prescribed density tests on filling: | | | | |
| 18 | "Modified AASHTO Density" test | No | 5 | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 19 | Soil insecticide (protection against termites) applied as specified to bottoms and sides of trenches, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | | | | |
| | | m2 | 15 | | |
| | CONCRETE WORK | | | | |
| | 25MPa/19mm reinforced concrete: | | | | |
| | Ramps | m3 | 5 | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 11 Bill No. 1 External Work | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R |
|----|--|----|----|---|
| | Test cubes | | | |
| 20 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | |
| | <u>Finishing top surfaces of concrete smooth with a</u> steel trowel: | | | |
| 1 | Surface beds, slabs, etc to falls | m2 | 15 | |
| | FORMWORK | | | |
| | Smooth formwork to sides: | | | |
| 2 | Sloping outer edges of ramps approximately 450mm high extreme | m | 20 | |
| | REINFORCEMENT | | | |
| | Fabric reinforcement: | | | |
| 3 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 15 | |
| | | | | |
| | APRONS | | | |
| | EARTHWORKS | | | |
| | Excavation in earth not exceeding 2m deep: | | | |
| ļ | Reduced levels under floors | m3 | 35 | |
| | Extra over all excavations for carting away: | | | |
| 5 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 35 | |
| | | | | |
| | | | | |
| | Carried Forward Section No. 11 Bill No. 1 External Work | | | R |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Brought Forward | I | I | R | |
|----|---|----|-----|---|--|
| | G7 filling material supplied by the contractor, compacted to 95% Mod AASHTO density: | | | | |
| 26 | Under floors, steps, pavings, etc | m3 | 35 | | |
| | Compaction of surfaces: | | | | |
| 27 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 236 | | |
| | Prescribed density tests on filling: | | | | |
| 28 | "Modified AASHTO Density" test | No | 79 | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 29 | Soil insecticide (protection against termites) applied as specified to bottoms and sides of trenches, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 236 | | |
| | CONCRETE WORK | | | | |
| | 25MPa/19mm reinforced concrete: | | | | |
| | Aprons | m3 | 35 | | |
| | <u>Test cubes</u> | | | | |
| 30 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 12 | | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | | |
| 31 | Surface beds, slabs, etc to falls | m2 | 236 | | |
| | REINFORCEMENT | | | | |
| | Carried Forward Section No. 11 Bill No. 1 External Work Diatho Consulting (PTY) LTD | | | R | |

| I | Brought Forward | I | I | R | | |
|----|--|----|------|---|--|--|
| | Fabric reinforcement: | | | | | |
| 32 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 236 | | | |
| | | | | | | |
| | THE FOLLOWING IN RAINWATER STORAGE TANK STRUCTURES: | | | | | |
| | EXCAVATIONS, ETC | | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | | |
| 33 | Trenches | m3 | 19 | | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | | |
| 34 | Soft rock | m3 | 2 | | | |
| 35 | Hard rock | m3 | 1 | | | |
| | Extra over all excavations for carting away: | | | | | |
| 36 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 12 | | | |
| | Risk of collapse of excavations: | | | | | |
| 37 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 8 | | | |
| | Keeping excavations free of water: | | | | | |
| 38 | Keeping excavations free of all water other than subterranean water | | ltem | | | |
| | | | | | | |
| | Carried Forward Section No. 11 Bill No. 1 External Work | | | R | | |
| | Diatho Consulting (PTY) LTD | | | | | |

| | Brought Forward | | | R | |
|----|--|----|-----|---|--|
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 39 | Backfilling to trenches, holes, etc | m3 | 7 | | |
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 25MPa/19mm concrete: | | | | |
| | Strip footings | m3 | 8 | | |
| | Surface beds | m3 | 4 | | |
| | TEST BLOCKS | | | | |
| 40 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 2 | | |
| | MASONRY | | | | |
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 41 | One brick walls | m2 | 72 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 42 | 150mm Wide reinforcement built in horizontally | m | 187 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 43 | Extra over brickwork for face brickwork | m2 | 43 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 11 Bill No. 1 | | | | |
| | External Work | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|---|----|-------|---|--|
| | <u>Brick-on-edge header course coping, sills, etc. of</u> <u>face</u> <u>bricks (Allow a Prime Cost Amount of R5</u> <u>500.00/1000 bricks delivered to site excluding VAT)</u> pointed with recessed joints on all exposed faces | | | | |
| 44 | 220mm Copings on top of one brick walls | m | 64 | | |
| | | | | | |
| | FENCING | | | | |
| | PERIMETER FENCING | | | | |
| | GENERAL REPAIRWORK | | | | |
| | Repairwork to existing steel palisade fence, etc including cleaning down of all rust, scale, dirt, oil, etc degreasing, washing down with suitable detergent and removing all existing paint, contaminants, etc to bare metal surface, realigning all moving parts, replacing of damaged or missing palisades, screws, nuts, etc, lubricating where necessary and leaving in complete working order: | | | | |
| 45 | Palisade fence 1800mm high | m | 196 | | |
| | Spot priming bare metal surfaces, one coat alkyd based universal undercoat and two coats superior quality universal enamel paint, on work in poor condition: | | | | |
| 46 | Palisade fence | m2 | 2 347 | | |
| | FENCING AROUND GRADE R FACILITIES | | | | |
| | | | | | |
| | Carried Forward Section No. 11 Bill No. 1 External Work | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward <u>Steel palisade fencing, gates, etc including prepare</u> <u>and apply one priming coat and two coats high</u> <u>gloss enamel Traffic Green paint using compressor</u> <u>spay gun on metal stays, gates, framing and etc</u> | | | R | |
|----|--|----|-----|---|--|
| 47 | 1800mm High palisade fencing comprising of 40 x40 x 2mm angle iron welded flash with the back of the post 300mm from top of paling and 300mm from bottom of paling (350mm from ground level), 21 palings per panel consist of 30 x 30 x 2mm x 1 800mm High steel angle iron inserted and firmly welded to the bearers at 133mm centre to centre with "Devil Fork" on top and dove tail at the bottom welded to 76 x 76 x 2mm steel tubing posts 2 400mm long/ high with closing pyramid caps on top and M12 anti vandal nuts and bolts and posts set and cast into and including 300 x 300 x 600mm deep concrete base at 3 000mm centres. | m | 289 | | |
| 48 | 1500mm Wide x 1800mm High Swing gate comprising of 40 x40 x 2mm angle iron palings welded to a 50 x 25 x 1.6mm rectangular tubing bearer frame, palings are to be placed 133mm apart each other centre to centre and 2 No x 75mm x 75mm x 2mm steel square tubing posts at each side of the gate opening with closing pyramid caps on top and planted into concrete footing 450 x 450 x 600mm deep including excavations, backfilling and | | | | |
| | locking mechanism. | No | 1 | | |
| | | | | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 11 | | | R | |
| | Section No. 11 Bill No. 1 External Work | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 11 | | | |
| | BILL NO.2 | | | |
| | SITE SERVICES (PROVISIONAL) | | | |
| | (ALL TRADES) | | | |
| | | | | |
| | PREAMBLES | | | |
| | The General Preambles for Trades (2017 edition) as published by the Association of South African Quantity Surveyors shall be deemed to be incorporated in these bills of quantities and no claims arising from brevity of description of items fully described in the said General Preambles will be entertained | | | |
| | The following "Supplementary Preambles" are incorporated in this bill to satisfy the requirements of the project and shall take precedence over the provisions of the said General Preambles | | | |
| | SUPPLEMENTARY PREAMBLES | | | |
| | Stormwater channels: | | | |
| | Descriptions of channels shall be deemed to include necessary excavation, surface preparation, compaction, etc and disposal of surplus material on site | | | |
| | French drains: | | | |
| | Descriptions of french drains shall be deemed to include excavation, stone filling graded from 300mm diameter at bottom to 75mm diameter at top, approved geofabric filter blanket over stone, 300mm earthfilling over and disposal of surplus material on site | | | |
| | | | | |
| | Carried Forward | | R | |
| | Section No. 11 Bill No. 2 Site Services | | | |
| | Diatho Consulting (PTY) LTD | | | |

| | I |
|--|---|
| Brought Forward | |
| Septic tanks: | |
| Descriptions of proprietary type septic tanks shall be deemed to include excavation, bedding and jointing, concrete base slabs, jointing to drains and backfilling, compaction, etc all in accordance with the manufacturer's instructions and disposal of surplus material on site | |
| uPVC pipes and fittings: | |
| Sewer and drainage pipes and fittings shall be jointed and sealed with butyl rubber rings | |
| Soil, waste and vent pipes and fittings shall be solvent weld jointed or sealed with butyl rubber rings | |
| uPVC pressure pipes and fittings: | |
| Pipes of 50mm diameter and smaller shall be plain ended with solvent welded uPVC loose sockets and fittings | |
| Pipes of 63mm diameter and greater shall have sockets and spigots with push-in type integral rubber ring joints. Bends shall be uPVC and all other fittings shall be cast iron, all with similar push-in type joints | |
| High density polyethylene (HDPe) pipes and fittings: | |
| Pipes shall be type IV and of the class specified with "Plasson" or "Alprene" compression fittings | |
| | |
| Carried Forward Section No. 11 Bill No. 2 Site Services | |
| Diatho Consulting (PTY) LTD | |

R

Brought Forward

"Polycop" polypropylene pipes:

Polypropylene pipes 54mm diameter and smaller shall be seamless copper coloured Class 16 pipes jointed with "Fast-fuse" heat welded thermoplastic or where so described "Polylock" compression fittings

Pipes shall be firmly fixed to walls, etc with coloured nylon snap-in pipe clips with provision for accommodating thermal movement and jointed and fixed strictly in accordance with the manufacturer's instructions

Copper pipes:

Pipes shall be hard drawn and half-hard "Maksal" pipes of the class described. Class 0 (thin walled hard drawn) pipes shall not be bent. Class 1 (thin walled half-hard), Class 2 (half-hard) and Class 3 (heavy walled half-hard) pipes shall only be bent with benders with inner and outer formers. Fittings to copper waste, vent and antisyphon pipes, capillary solder fittings and compression fittings shall be "Cobra Watertech" type. Capillary solder fittings shall comply with ISO 2016

Copper pipes are to be installed in accordance with the latest revision of the Code of Practice for Copper Plumbing soldering techniques. Flux, solder, etc to be strictly in accordance with the manufacturer's requirements with special attention to copper flux composition

Reducing fittings:

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm, only the largest end or branch size is given. Should the Contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm, all sizes are given and no claim for extra bushes, reducers, etc will be entertained

Carried Forward

Section No. 11 Bill No. 2 Site Services

Diatho Consulting (PTY) LTD

R

| Brought Forward | R | |
|--|---|--|
| Disinfection of water pipework: | | |
| Water pipework is to be disinfected at completion in accordance with SABS 1200L (provision for disinfection elsewhere) | | |
| "Densyl" petrolatum anti-corrosion tape as manufactured by Denso SA (Pty) Ltd.: | | |
| Pipes to be taped shall be coated with the appropriate primer and the tape shall be applied in the appropriate widths and with suitable overlaps | | |
| Couplings and fittings to pipes shall be taped in strict accordance with the manufacturer's instructions including mastic, tape, "Layflat" sheeting, securing of same, etc | | |
| Prices for wrapping of pipes shall include for all work as described to couplings in the length | | |
| Laying, backfilling, bedding, etc of pipes: | | |
| Pipes shall be laid and bedded in accordance with manufacturers' instructions and trenches shall be carefully backfilled | | |
| Where no manufacturers' instructions exist, pipes shall be laid in accordance with Clauses 5.1 and 5.2 of each of the following: SABS 1200L : Medium-pressure pipelines SABS 1200LD : Sewers SABS 1200LE: Stormwater drainage | | |
| Pipe trenches, etc shall be backfilled in accordance with Clauses 3, 5.5, 5.6, 5.7 and 7 of SABS 1200DB : Earthworks (Pipe trenches) | | |
| Pipes shall be bedded in accordance with Clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SABS 1200LB : Bedding (Pipes) | | |
| Unless otherwise described, bedding of rigid pipes shall be Class B bedding | | |
| | | |
| Carried Forward | R | |
| Section No. 11 Bill No. 2 Site Services | | |
| Diatho Consulting (PTY) LTD | | |
| | | |

| | | | | | 1100.00 |
|---|---|----|-----|---|---------|
| | Brought Forward | | | R | |
| | <u>General:</u> | | | | |
| | Descriptions of pipes laid in and including trenches and of inspection chambers, catchpits, etc shall be deemed to include excavation, bedding, backfilling, compaction to a minimum of 98% Mod AASHTO density and disposal of surplus material on site | | | | |
| | Descriptions of service pipes and flexible connecting pipes shall be deemed to include connections to taps, cisterns, etc and to steel pipes (adaptors for connections to copper pipes, etc are given separately) | | | | |
| | | | | | |
| | STORMWATER MANAGEMENT: | | | | |
| | STORMWATER CHANNELS: | | | | |
| | EARTHWORKS | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 1 | Reduced levels stormwater channels | m3 | 60 | | |
| | Extra over all excavations for carting away: | | | | |
| 2 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 60 | | |
| | <u>G7 filling material supplied by the contractor, compacted to 95% Mod AASHTO density:</u> | | | | |
| 3 | Under stormwater channels, etc | m3 | 60 | | |
| | Compaction of surfaces: | | | | |
| 4 | Compaction of ground surface under stormwater channels etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO density | m2 | 400 | | |
| | Carried Forward | | | R | |
| | Section No. 11 Bill No. 2 Site Services | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

TMT-LDOE-2023/24-LPCL23/02D

Construction of water, Sanitation and Fencing

Tlhabeleni Primary School Rev.06

| | Prescribed density tests on filling: | | | |
|---|--|----|-----|---|
| 5 | "Modified AASHTO Density" test | No | 4 | |
| | Soil insecticide in accordance with SANS 5859: | | | |
| 6 | Soil insecticide (protection against termites) applied as specified to bottoms and sides of trenches, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 400 | |
| | CONCRETE WORK | | | |
| 7 | 25Mpa/19mm Mass concrete in V-shaped channel 700mm wide x 75mm thick cast in 2 000mm intervals with rounded salient edges and finished on exposed surfaces with 2:1 cement mortar, with and including one layer of ref.193 mesh reinforcement, laid to falls in panels not exceeding 2,0m long with 12mm bitumen impregnated soft board movement joints with exposed edges raked out for a depth of 10mm and filled with bituminous compound including all necessary excavations, form work, backfilling, clearing, levelling and etc. | m | 267 | |
| 3 | Extra for fair open end | No | 89 | |
|) | Extra for fair stopped end | No | 89 | |
| | Extra for angle intersection | No | 89 | |
| | Test cubes | | | |
| | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 10 | |
| | Finishing top surfaces of concrete smooth with a steel trowel: | | | |
| 2 | Stormwater channels to falls | m2 | 400 | |
| | RETAINING WALLS: | | | |
| | | | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services | | | R |
| | Diatho Consulting (PTY) LTD | | | |

| | | | | | - |
|----|--|----|------|---|-------|
| | Brought Forward | | | R | |
| | EXCAVATIONS, ETC | | | | |
| | Excavation in earth not exceeding 2m deep: | | | | |
| 13 | Trenches | m3 | 5 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 14 | Soft rock | m3 | 0,5 | | |
| 15 | Hard rock | m3 | 0,2 | | |
| | Extra over all excavations for carting away: | | | | |
| 16 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 7 | | |
| | Risk of collapse of excavations: | | | | |
| 17 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 32 | | |
| | Keeping excavations free of water: | | | | |
| 18 | Keeping excavations free of all water other than subterranean water | | Item | | |
| | UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES | | | | |
| | 25MPa/19mm concrete: | | | | |
| | Strip footings | m3 | 4 | | |
| | TEST BLOCKS | | | | |
| 19 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 1 | | |
| | MASONRY | | | | |
| | | | | | |
| | | | | | _ |
| | Carried Forward Section No. 11 Bill No. 2 Site Services | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

Rev.06

| | Brought Forward | · | | R | |
|----|---|----|-----|---|--|
| | Brickwork of NFX bricks (14 MPa nominal compressive strength) in class II mortar in loadbearing walls etc: | | | | |
| 20 | One brick walls | m2 | 10 | | |
| | 2,5mm Brickwork reinforcement: | | | | |
| 21 | 150mm Wide reinforcement built in horizontally | m | 59 | | |
| | FACE BRICKWORK | | | | |
| | Face bricks (Allow a Prime Cost Amount of R5 500.00/1000 bricks delivered to site excluding VAT) pointed with flush horizontal and vertical joints | | | | |
| 22 | Extra over brickwork for face brickwork | m2 | 20 | | |
| | <u>Brick-on-edge header course coping, sills, etc. of face</u> <u>bricks (Allow a Prime Cost Amount of R5</u> <u>500.00/1000 bricks delivered to site excluding VAT)</u> pointed with recessed joints on all exposed faces | | | | |
| 23 | 220mm Copings on top of one brick walls | m | 20 | | |
| | THE FOLLOWING IN SEPTIC TANK: | | | | |
| | EARTHWORKS | | | | |
| | Excavation in earth exceeding 2m and not exceeding 4m deep: | | | | |
| 24 | Septic tank pit | m3 | 140 | | |
| | Extra over trench and hole excavations in earth for excavation in: | | | | |
| 25 | Soft rock | m3 | 14 | | |
| 26 | Hard rock | m3 | 7 | | |
| | | | | | |
| | | | | | |
| | Carried Forward | ı | | R | |
| | Section No. 11 Bill No. 2 Site Services | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | I | 1 | " | |

| | Brought Forward | | | R | |
|----|---|----|------|---|--|
| | Extra over all excavations for carting away: | | | | |
| 27 | Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor | m3 | 125 | | |
| | Risk of collapse of excavations: | | | | |
| 28 | Sides of trench and hole excavations not exceeding 1,5m deep | m2 | 80 | | |
| | Keeping excavations free of water: | | | | |
| 29 | Keeping excavations free of all water other than subterranean water | | Item | | |
| | Earth filling obtained from the excavations and/or prescribed stock piles on site, compacted to 93% Mod AASHTO density: | | | | |
| 30 | Backfilling to trenches, holes, etc | m3 | 15 | | |
| | Compaction of surfaces: | | | | |
| 31 | Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 91% Mod AASHTO | | | | |
| | density | m2 | 80 | | |
| | Prescribed density tests on filling: | | | | |
| 2 | "Modified AASHTO Density" test | No | 5 | | |
| | Soil insecticide in accordance with SANS 5859: | | | | |
| 33 | Soil insecticide (protection against termites) applied as specified to bottoms and sides of trenches, etc including forming and poisoning shallow furrows against foundation walls, etc filling in furrows and ramming | m2 | 80 | | |
| | CONCRETE WORK | | | | |
| | | | | | |
| | | | | | |
| | Carried Forward | | | R | |
| | Section No. 11 Bill No. 2 Site Services | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | |
|----|--|----|------|---|--|
| | 15MPa/19mm unreinforced concrete: | | | | |
| 34 | Surface blinding under footings and bases | m3 | 15 | | |
| | 25MPa/19mm reinforced concrete: | | | | |
| | Mass concrete to bottoms | m3 | 20 | | |
| | Slabs | m3 | 15 | | |
| | Test cubes | | | | |
| 35 | Making and testing 150 x 150 x 150mm concrete strength test cube (Provisional) | No | 4 | | |
| | FORMWORK | | | | |
| | Smooth formwork to sides: | | | | |
| 36 | Edges, risers, ends and reveals not exceeding 300mm high or wide | m | 25 | | |
| | REINFORCEMENT | | | | |
| | Fabric reinforcement: | | | | |
| 37 | Type 395 fabric reinforcement in concrete surface beds, slabs, etc | m2 | 80 | | |
| | High tensile steel reinforcement to structural concrete work: | | | | |
| 38 | 110mm Diameter drain pipes, fixed raking or vertically in ramps to cleaning eyes, etc (no excavations) | | | | |
| | | m | 20 | | |
| 39 | All Diameter bars | t | 3,00 | | |
| 40 | 110mm Pipes laid in and including trenches not | | | | |
| | exceeding 1m deep | m | 20 | | |
| | | | | | |
| | | | | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R | | |
|----|--|----|-----|---|--|--|
| 41 | 110mm Pipes laid in and including trenches exceeding 1m and not exceeding 2m deep | m | 5 | | | |
| 42 | Extra over uPVC piping for 110mm bend | No | 5 | | | |
| | BRICKWORK | | | | | |
| | Brickwork of NFP bricks in class II mortar | | | | | |
| 43 | Half brick walls | m2 | 17 | | | |
| 44 | Extra over uPVC piping for 110mm junction | No | 20 | | | |
| 45 | One brick walls | m2 | 70 | | | |
| 46 | Extra over uPVC piping for 110mm stop end | No | 10 | | | |
| 47 | 110mm uPVC cleaning eye fixed to 110mm uPVC drain pipe, including 350 x 350 x 75mm thick in-situ 15 MPa/19mm mass concrete surround, the whole finished smooth on all exposed faces with exposed angles rounded, including all necessary excavations, formwork, backfilling, etc. | No | 2 | | | |
| | BRICKWORK SUNDRIES: | | | | | |
| | Bagging of 1:3 cement and sand mixture | | | | | |
| 48 | Outer face of external brick wall | m2 | 350 | | | |
| | | | | _ | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services | | | R | | |
| | Diatho Consulting (PTY) LTD | | | | | |

| | Brought Forward | | | R | |
|----|---|----|-----|---|-----|
| | 2,5mm Brickwork reinforcement: | | | | |
| 49 | 75mm Wide reinforcement built in horizontally | m | 44 | | |
| 50 | 150mm Wide reinforcement built in horizontally | m | 206 | | |
| | <u>One layer 250 micron green polyethylene waterproof sheeting (SANS 952-1985 type C) sealed at laps with PVC self-adhesive tape:</u> | | | | |
| 51 | Under surface beds | m2 | 50 | | |
| | SPECIAL FLOOR COATING | | | | |
| | Prepare all surfaces as neccessary, prime with "Flowprime" primer and apply 6mm thick anti-slip "Flowcrete Flowfresh HF" or similar approved heavy duty chemical resistant antimicrobial treated polyurethane resin floor screed of approved colour and applied by an approved specialist, on: | | | | |
| 52 | On internal plastered walls | m2 | 88 | | |
| | INTERNAL PLASTER | | | | |
| | Cement plaster steel trowelled, on brickwork: | | | | |
| 53 | On walls | m2 | 88 | | |
| | THE FOLLOWING IN PREFABRICATED 70KL STEEL TANK: | | | | |
| | EARTHWORKS | | | | |
| | SITE PREPARATION | | | | |
| 54 | Remove topsoil to nominal depth 150mm, stockpile and maintain | m2 | 25 | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services Diatho Consulting (PTY) LTD | | | R | |
| | | I | | I | I I |

| | Brought Forward | | | R | |
|----|---|----|----|---|--|
| | BULK EXCAVATION - TANK BASE | | | | |
| | <u>b) Extra-over for:</u> | | | | |
| 55 | Intermediate excavation | m3 | 3 | | |
| 56 | Hard rock excavation | m3 | 5 | | |
| | RESTRICTED EXCAVATIONS | | | | |
| 57 | Excavate for restricted foundations, footings and trenches in all materials and use for backfill or embankment or dispose. | m3 | 25 | | |
| | EARTHWORKS (ROADS, SUBGRADE) | | | | |
| 58 | Rip and re-compact insitu to 90% MOD AASHTO | m3 | 1 | | |
| 59 | Geotechnical grid (Traix TX170) | m2 | 1 | | |
| 60 | Backfill 500mm with course insitu material in 150mm layers. | m3 | 5 | | |
| | PREFABRICATED TANK | | | | |
| 61 | Supply, handle, install, erect hot dipped galvanised Prefabricated steel tank suitable for 70kl capacity. Including lockable access manhole with built-in screened vent. Internal and external ladder, a level indicator, as well as all fittings required for installation. And the supply, handling, installation, and erection of hot dipped galvanised steel support structures 6m high, including an access ladder with safety cage. As well as all standard fittings required for installation and walkway around tank base with rails | No | 1 | | |
| | CONCRETE | | | | |
| 62 | Binding layer in 15MPa concrete (50mm thick) | m2 | 1 | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services | | | R | |
| | Diatho Consulting (PTY) LTD | | | | |

| | | 1 | | _ | 1 | 1 |
|----|---|----|------|---|---|---|
| | Brought Forward | | | R | | |
| 63 | Shutter rough | m2 | 25 | | | |
| | SCHEDULED REINFORCEMENT | | | | | |
| 64 | Steel bars | t | 3,00 | | | |
| 65 | Strength of concrete grade 30/19 | m3 | 23 | | | |
| | UNFORMED SURFACE FINISHES | | | | | |
| 66 | Steel float | m2 | 25 | | | |
| 67 | M20 Bolts cast in complete with washer plate and nuts, all galvanised. | No | 16 | | | |
| | <u>PIPES</u> | | | | | |
| | Supply, lay, bed, test, disinfect flanged pipes complete with couplings for Class 16 mild steel pipes of the following diameter: (All material including fittings to be SABS approved) | | | | | |
| 68 | 1. 65 mm diameter | m | 18 | | | |
| 69 | 3. 80 mm diameter | m | 12 | | | |
| | Supply, handle, lay, disinfect, bed in flexible pipe bedding and test uPVC class 16 pipes complete with spigot and socket joints.(All material including fittings to be SABS approved) | | | | | |
| 70 | 1. 75 mm diamete | m | 12 | | | |
| 71 | 2. 90 mm diameter | m | 12 | | | |
| | Carried Forward Section No. 11 Bill No. 2 Site Services Diatho Consulting (PTY) LTD | | | R | | |

| | Brought Forward | | | R | |
|----|--|----|---|---|--|
| | SPECIALS AND FITTINGS | | | | |
| | Extra-over 8.2.1 for supplying, laying, bedding, jointing and testing of the following fittings for use on Steel pipes | | | | |
| | 90 degree bends | | | | |
| 72 | 1. 75mm | No | 4 | | |
| 73 | 2. 90mm | No | 8 | | |
| | Equal Tee | | | | |
| 74 | 1. 100mm x 100mm | No | 2 | | |
| | Extra-over 8.2.1 for supplying, laying, bedding, jointing and testing of the following fittings for use on uPVC pipes | | | | |
| | 90 degree bends | | | | |
| 75 | 1. 75mm | No | 1 | | |
| 76 | 2. 90mm | No | 1 | | |
| | <u>11.25 degree Bends</u> | | | | |
| 77 | 1. 75mm | No | 1 | | |
| 78 | 2. 90mm | No | 1 | | |
| | 22.5 degree Bends | | | | |
| 79 | 1. 75mm | No | 1 | | |
| 80 | 2. 90mm | No | 1 | | |
| | <u>45 degree Bends</u> | | | | |
| 81 | 1. 75mm | No | 1 | | |
| 82 | 2. 90mm | No | 1 | | |
| | Carried Forward Section No. 11 | | | R | |
| | Bill No. 2 Site Services | | | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |

| | Brought Forward | | | R |
|----------|---|----|---|---|
| | Flange adaptors | | | |
| 83 | 1. 110mm | No | 4 | |
| | Extra over Item 8.2.1 for supplying, fixing and bedding of valves; Class 16: | | | |
| | Viking Johnson/Klamflex flanged adaptors PN 16 | | | |
| 34 | 1. 100mm | No | 2 | |
| 35 | ND100 AVK Dismantling joint PN16 or similar approved | No | 4 | |
| 6 | ND100 flanged cosmos Meinecke WPD bulk meter with digital output or similar approved; Class 16 | No | 1 | |
| 7 | ND100 flanged Bermad 70F Y-Pattern strainer or similar approved; Class 16 | No | 2 | |
| 8 | ND100 flanged ball valve; Class 16 | No | 1 | |
| 9 | Steel Plinths | No | 4 | |
| 90 | DN25 automatic air release valve, Vent O Mat or similar approved brand as per inlet chamber detail; Class 25 | | | |
| | | No | 2 | |
| 1 | ND25 brass fullway gate valve to sabs 776 Class 10 | No | 2 | |
| <u>}</u> | ND25 galvanised barrel nipple PN16 | No | 2 | |
| 3 | ND100 In line tee with outlet diameter as specified in the nodal descriptions and reduced to 25bsp female end connection PN16 | No | 2 | |
| ٨ | ND400 mm 450mm lang dauble flagged ping. DN 46 to | No | 2 | |
| 4 | ND100 mm, 150mm long double flanged pipe, PN 16 to SANS standard | No | 2 | |
| | Carried Forward | | | R |
| | Section No. 11 Bill No. 2 Site Services | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | | R | | |
|-----|---|----|---|---|-----|------|
| 95 | ND100 mm, 600mm long double flanged pipe, PN 16 to SANS standard | | | | | |
| 96 | ND100 flanged Vosa Series 7354 Equilibrium float valve | No | 2 | | | |
| | or similar approved; Class 16 | No | 1 | | | |
| 97 | DN100 flanged mild steel flanged sweep tee; flanges drilled according to SANS 1123 table 16 | No | 1 | | | |
| 98 | DN100 Blank flange with 20 mm hole drilled onto it and 25 mm nipple welded onto it; nipple to be male threaded on one end. | | | | | |
| | | No | 1 | | | |
| 99 | DN25 Female threaded ball valve, PN16 | No | 1 | | | |
| 100 | DN25 Nipple, one end male and one end female threaded | | | | | |
| | | No | 1 | | | |
| 101 | DN25 automatic air release valve, Vent O Mat or similar approved brand as per tank inlet detail; Class 25 | No | 1 | | | |
| 102 | ND100 mm, 240mm long double flanged pipe, PN 16 to SANS standard | No | 1 | | | |
| 103 | ND150 mild steel pipe, PN 16,6m long,one end flanged as per detail drawing 14491-D-C-WAT-D05, actual length of pipe to be confirmed on site confirmed on site | No | 1 | | | |
| | Isolating valves | | | | | |
| | Extra-over item 6.13 for the supplying, installing cutting in and testing flanged Class 16 anti-clockwise closing non rising spindle resilient seal gate valves for steel pipes as shown on detailed drawings for pipe diameters | | | | | |
| 104 | 1. 100 mm diameter | No | 5 | | | |
| 105 | 2. 150 mm | No | 1 | | | |
| | | | | | | |
| | Carried Forward | | | R | | |
| | Section No. 11 Bill No. 2 Site Services | | | | | |
| | Diatho Consulting (PTY) LTD | | | | | |
| | | | | | | |
| | | I | I | I | I I | 1 |

| | Brought Forward | | | R | |
|-----|--|----|---|---|--|
| | CHAMBERS | | | | |
| 106 | Construct concrete inlet and outlet chamber Type 1 complete with step irons, and frames as per detailed drawings, up to 2.0m depth. | No | 1 | | |
| 107 | Construct scour valve chamber Type 4, complete with stepirons, frames and and scour wing wall structure as per detailed drawings up to 2.5m depth. | No | 1 | | |
| | <u>SUNDRIES</u> | | | | |
| 108 | Thrust blocks and pedestals class 25/19 concrete | m3 | 5 | | |
| | WATER STORAGE TANKS: | | | | |
| 109 | "Jojo" or similar approved Type SG1 polyethylene drinking water tanks with black lining internally, complete with tank connector at the bottom, inlet and over-flow on top or (side) with a 40mm fitting (female) and 430mm diameter lid with e-clips on top of the tank: 5250 Litre vertical tank (colour green) size 1800mm diameter x 2300mm high overall, the tank securely bolted in position to top of reinforced concrete base (base elsewhere measured) | No | 7 | | |
| | | | | | |
| | Carried Forward to Summary of Section No. 11 | | | R | |
| | Section No. 11 Bill No. 2 Site Services | | | | |
| | Diatho Consulting (PTY) LTD | | | | |

| | SECTION SUMMARY - Site Works | | | |
|------------|------------------------------|------------|---|--------|
| Bill No | | Page No | | Amount |
| 1 | External Work | 437 | | |
| 2 | Site Services | 455 | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried to Final Summary | | R | |
| | Section No. 11 | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |
| | | | | |

| ltem No | | Quantity | Rate | Amount |
|------------|---|----------|------|--------|
| | SECTION NO. 12 | | je. | |
| | BILL NO.1 | | | |
| | BUDGETARY ALLOWANCES | | | |
| | | | | |
| | PREAMBLES | | | |
| | <u>General:</u> | | | |
| | A Budgetary Allowance is a sum of money included in the contract sum for work intended for execution by the Contractor, the extent of which is identified but not detailed | | | |
| | Work for which budgetary allowances are provided will be measured and valued in accordance with clause 32 of the Principal Building Agreement and deducted in whole or in part if not required without any compensation for loss or profit on the said allowances | | | |
| | Each Budgetary Allowance may comprise more than one element of work | | | |
| | | | | |
| | BOREHOLE | | | |
| 1 | Budgetary Allowance of Two Hundred and Fifty Thousand Rand for installation of new borehole | ltem | | |
| 2 | Add Profit & Attendance | Item | | |
| | BOREHOLE REFURBISHMENT | | | |
| 3 | Budgetary Allowance of One Hundred and Fifty Thousand Rand for renovation of existing borehole | ltem | | |
| | | | | |
| | Carried Forward Section No. 12 | | R | |
| | Bill No. 1 Provisional Sum | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

| | Brought Forward | | R | |
|---|--|------|---|--|
| 4 | Add Profit & Attendance | ltem | | |
| | WATER TREATMENT PLANT | | | |
| 5 | Budgetary Allowance of Two Hundred and Twenty Five Thousand Rand Water treatment plant | ltem | | |
| 6 | Add Profit & Attendance | ltem | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Carried to Final Summary | | R | |
| | Section No. 12 Bill No. 1 Provisional Sum | | | |
| | Diatho Consulting (PTY) LTD | | | |
| | | | | |

- -

| Section No | FINAL SUMMARY | Page No | | Amount | |
|---------------|---|------------|---|--------|---|
| 1 | Preliminaries | 46 | | | |
| 2 | Demolitions | 50 | | | |
| 3 | Refurbishment of 4 Enviro-loo seats(Educators) | 90 | | | |
| 4 | SFD5 Female Educators Ablutions | 137 | | | |
| 5 | FD7 Female Learners Ablutions | 186 | | | |
| 6 | M3 + 3UR Male Learners Ablutions | 234 | | | |
| 7 | SM3 + 3UR Male Educators Ablutions | 280 | | | |
| 8 | M4 + 3UR Male Learners Ablutions | 328 | | | |
| 9 | F7 Female Learners Ablutions | 378 | | | |
| 10 | GRD5 Grade R Unisex | 425 | | | |
| 11 | Site Works | 456 | | | |
| 12 | Provisional Sums | 458 | | | |
| | SUB TOTAL | | R | | |
| | CONTRACT CONTINGENCIES | | | | |
| | Allow the sum of 10% (ten percent) of the above sub total for Contingencies to be spent as the Principal Agent may direct and to be deducted in whole or in part if not required | | R | | |
| | SUB TOTAL | | R | | |
| | VALUE ADDED TAX | | | | |
| | Value Added Tax [15%] | | R | | |
| | | | | | |
| | Carried to Form of Tender | | R | | |
| | Diatho Consulting (PTY) LTD | | | | |
| | | | | | |
| | | | | | |
| l | | | | | İ |