



- **WALLS :** INTERNAL-PREPARATION-CLEAN OFF AND DRY
 - FILL AND APPLY 2 COATS DECO PLASTER PRIMER UNDERCOAT
 - FINISH - 2 COATS DECO PREMIER SHEEN - WHITE
- **WALLS :** EXTERNAL-PREPARATION-CLEAN OFF AND DRY
- **CEILING :** PREPARATION-CLEAN OFF AND DRY
 - FILL AND APPLY 2 COATS DECO PLASTER PRIMER UNDERCOAT
 - FINISH - 2 COATS DECO PREMIER SHEEN - WHITE
- **DOORS - GALVANISED IRON**
 - PREPARATION - WASH CLEAN WITH SOAP DETERGENT AND DRY
 - FINISH - NIL
- **FLOOR - MICRO CONCRETE TOPPING**
 - THE FLOOR SHALL BE WOOD FLOATED INITIALLY, THEN SMOOTHED OFF WITH A STEEL TROWEL TO A FINAL SMOOTH FINISH
- THE FLOOR SHALL BE GIVEN 7 DAYS TO CURE PRIOR TO PAINTING
 - PREPARATION - WASH CLEAN AND DRY
 - FINISH - 3 COATS 'EPIDUCT' EPOXY FLOOR PAINT-GREY

- ### CONCRETE NOTES:

- CONCRETE WORK TO BE IN ACCORDANCE WITH SANS 1200
- CONCRETE STRENGTH AT 28 DAYS = 25MPa
- CONCRETE STRENGTH FOR BLINDING LAYER AT 28 DAYS = 15MPa
- CONCRETE TO BE POURED WHERE THE AIR TEMPERATURE WILL DROP BELOW 4 DEG. CELSIUS IN 8 HOURS AFTER POURING, UNLESS A SUITABLE AN APPROVED ADDITIVE IS ADDED TO THE MIXES.

A2