




INFRASTRUCTURE MAINTENANCE

PROCUREMENT SPECIFICATION

Specification For A Cordless Angle Grinder (230mm)

Editor:	Engineer RN Mechanical Technology	Rotondwa Ludzulu	
Approved:	Senior Engineering Technologist RN Mechanical Technology	Molefi Moeketsane	
Authorised:	Senior Engineering Technologist RN Mechanical Technology	Molefi Moeketsane	

Date: 24 April 2022

Circulation Restricted To:

Transnet Freight Rail - Infrastructure

© This document as a whole is protected by copyright. The information herein is the sole property of Transnet Ltd. It may not be used, disclosed or reproduced in part or in whole in any manner whatsoever, except with the written permission of and in a manner permitted by the proprietors.

Contents

1. Scope	4
2. Operating Conditions	4
3. Qualifications	4
4. Performance	4
5. General Requirements	4
6. Detailed Requirements	4
6.1 Cordless Angle grinder Requirements	4
6.2 Grinder Bits Requirements.....	5
6.3 Weight.....	5
6.4 Operator Comfort.....	5
6.5 Noise Emission	5
6.6 Body	5
6.7 Safety	5
6.8 Ergonomics	6
7. Quality Control.....	6
8. Data Plate	6
9. Legal and Operational	6

1. Scope

- 1.1 This specification outlines the requirements of a heavy duty, battery operated Cordless Angle Grinder required by Transnet Freight Rail.
- 1.2 Each cordless angle grinder shall be supplied with three sets of grinder bits as detailed under section 6.2 below.
- 1.3 The supplier shall ensure that each complete cordless angle grinder set is manufactured from **high-quality, robust materials**, suitable for heavy-duty industrial use.

2. Operating Conditions

- 2.1 Machines will be operated in all weather conditions at altitudes ranging from sea level up to 1850 m above sea level, under relative humidity levels between 10% to 90%, and in environments varying from saline coastal areas to dry and dusty inland regions.
- 2.2 The machine must operate reliably within an ambient air temperatures range of -5° C to 45° C.

3. Qualifications

- 3.1 The design of the cordless angle grinder is to be that of the manufacturer; however, it must be of robust construction to withstand the sustained heavy-duty demands of railway infrastructure environment.
- 3.2 A “no-tool” adjustment machine is preferred.

4. Performance

- 4.1 A service life of not less than 7 years is expected from each machine. The actual design life of the machine is to be stated.
- 4.2 The cordless angle grinder must be designed for easy and economically maintenance, using standard workshop tools and equipment.

5. General Requirements

- 5.1 The cordless angle grinder is to be designed for professional use, it must be able to perform in rugged conditions and in a wide variety of applications.
- 5.2 The cordless angle grinder must be easy to start, safe for handling and operation.
- 5.3 The cordless angle grinder and its grinder bits must be of high quality to handle any job.
- 5.4 The cordless angle grinder must be supplied complete in a carry case with two (2) batteries.
- 5.5 The cordless angle grinder must be supplied with three (3) sets of grinding disc as per details under 6.2.

6. Detailed Requirements

6.1 Cordless Angle grinder Requirements

Below table outline the technical requirements for the cordless angle grinder:

Cordless Angle grinder	
Battery voltage	32 V - 42V
Motor Type	Brushless
No-load speed	+6500 rpm (tolerance +/-1000 rpm)
Battery type	Lithium-ion
Wheel Diameter	230 mm

Torque Settings	
Grinding Wheel	
Wheel Diameter	230 mm
Noise/vibration information	
Sound pressure level	80 - 95 dB(A)
Sound power level	95 - 105dB(A)

6.2 Grinding disc Requirements

6.2.1 The grinding disk material must have high elasticity to reduce risk of breakage.

6.2.2 Grinding disc as per below are required:

Dimensions ø mm		QTY length (mm)
230	Diamond Cutting disc	3
230	Steel Cutting disc (1mm)	3
230	Flap Disc	3

6.3 Weight

The weight of the angle grinder including the battery and grinding disc shall not exceed 8.2kg

6.4 Operator Comfort

The angle grinder must comply with SANS 8662-1:1998 (Hand-Held Portable Power Tools - Measurement of Vibrations at the Handle Part 1:General).

6.5 Noise Emission

The angle grinder must comply to EN 62841-2-1(Declaration and verification of noise emission values of machinery and equipment).

6.6 Body

6.6.1 The body of the grinder and its components must be robust.

6.6.2 The grinder must be well protected against rust

6.6.3 The grip on the handles must have a non-slip surface.

6.6.4 Machines will be acceptable in standard factory production finish and colour.

6.6.5 Details to be furnished.

6.6.6 Due cognisance must be given to the life requirement of the machine.

6.7 Safety

6.7.1 A safety trigger that prevents accidental switch-on must be fitted to the cordless angle grinder.

6.7.2 The maximum rated operating speed (rpm) of the angle grinder must be clearly marked.

6.7.3 More safety features should be installed for operators safety and comfort.

6.7.4 The machine must have hand guards with quick stop feature installed for operators safety.

6.8 Ergonomics

- 6.8.1 The angle grinder must be ergonomically designed for maximum operator productivity and safety.

7. Quality Control

- 7.1 All machines must be manufactured in an environment that complies to the latest ISO 9000 to ISO 9004 or similar quality control standards. Details must be furnished.
- 7.2 Machines will be subject to a technical evaluation and the final decision will, amongst others, be based on these findings.

8. Data Plate

- 8.1 The machine must come with a data plate.
- 8.2 The maximum no load speed in RPMs must be clearly marked.
- 8.3 The actual weight in kilograms (Kg) of the machine must be shown on the machine.

NB : The cutting disc rated speed must be advised.

9. Legal and Operational

- 9.1 All machines must comply with the requirements of the Machinery safety and Occupational Safety Act, (Act 85 of 1993 – General and Driven Machinery Regulations).
- 9.2 The machine must be completely assembled and filled with lubricants and ready for service in all respects.
- 9.3 An operator's handbook, service manual and spare parts list must be supplied with each machine in order to ensure that the machine is operated in accordance to the manufacturer's instructions.
- 9.4 All machines and equipment must be supplied complete with essential tools such as allen keys, spanners etc. in order to make essential adjustments as well as to fit or remove consumable items.
- 9.5 Consumable items must be available locally and must be of standardised format in order to be used on equipment of more than one supplier.
- 9.6 All machines and equipment is to be guaranteed for a minimum period of 12 months against faulty material and workmanship - fair wear and tear excluded. Full details of guarantee is to be submitted.
- 9.7 The information as requested by the various clauses in this specification are to be supplied in the form of technical data, pamphlets and/or drawings. If this is not complied to, offers may be overlooked.
- 9.8 Sufficient training must be given to all operators of these machines.
- 9.9 Machines not already in service with Transnet Freight Rail must be made available for testing/evaluation during the adjudication of the tender. Technical improvements on existing machines/equipment is to be substantiated by physical examples.

END OF DOCUMENT