





INFRASTRUCTURE MAINTENANCE

SPECIFICATION

Specification for Torque Wrench with Sockets

Author:	Engineer	Rotondwa Ludzulu	
Approved:	Senior Engineering Technologist Engineering	Molefi Moeketsane	
Authorised:	Principal Engineer Engineering	Siboniso Vilakazi

Date: 22 November 2018

Circulation Restricted To:

Transnet Freight Rail - Infrastructure

© This document as a whole is protected by copyright. The information herein is the sole property of Transnet Ltd. It may not be used, disclosed or reproduced in part or in whole in any manner whatsoever, except with the written permission of and in a manner permitted by the proprietors.

Contents

1.	Scope.....	3
2.	Operating Conditions	3
3.	Qualifications	3
4.	Performance	3
5.	General Requirements.....	3
6.	Detailed Requirements.....	3
6.1.	Mass	3
6.2.	Operator Comfort	4
6.3.	Noise Emission.....	4
6.4.	Torque Range	4
6.5.	Wrench Mechanism.....	4
6.6.	Body	4
6.7.	Ergonomics	4
7.	Quality Control	4
8.	Legal and Operational	5

1. Scope

- 1.1 This specification outlines the requirements of a heavy duty Torque Wrench that will be used for the maintenance of railway infrastructure.

2. Operating Conditions

- 2.1. The Torque wrench will be operated in all weather conditions at altitudes varying from sea level to 1850 m above sea level, relative humidity 10% to 90% and atmospheric conditions which vary from heavily saline to dry and dusty.
- 2.2. Ambient air temperatures ranging from -5° C to 45° C.

3. Qualifications

- 3.1 The design of the machine is to be that of the manufacturer, but must be of robust construction in order to meet sustained heavy-duty demands of railway infrastructure maintenance.
- 3.2 A “no-tool” adjustment machine is preferred.
- 3.3 Only products proven in service will be considered. A list of users, both South African and International, is to be submitted.

4. Performance

- 4.1. A service life of not less than 7 years is expected from each machine. The actual design life of the machine is to be stated.
- 4.2 The torque wrench are to be easily and economically maintained with standard workshop tools and equipment.
- 4.3 The torque wrench must comply with ISO 9000

5. General Requirements

- 5.1 The machine must be a heavy-duty reversible impact wrench having a 12.7 (1/2”) square drive.
- 5.2 Heavy duty wrench sockets and extensions will be used on the machine.
- 5.3 The Torque wrench will be used in both vertical and horizontal positions.
- 5.4 The torque wrench will be supplied with different size sockets.

6. Detailed Requirements

6.1. Mass

- 6.1.1 The mass of the impact wrench shall be less than 3kg.

6.2. Operator Comfort

- 6.2.1 The Torque Wrench must comply with SANS 8662-1:1998 (Hand-Held Portable Power Tools - Measurement of Vibrations at the Handle Part 1: General) and SANS 8662 – 7:2003 (Hand-Held Portable Power Tools - Measurement of Vibrations at the Handle Part 7: Wrenches, screwdrivers and nut runners with impact, impulse or ratchet action).
- 6.2.2 It shall provide excellent grip even in oily conditions

6.3. Noise Emission

- 6.3.1 The Torque wrench must comply to BS EN ISO 4871:1997 (Declaration and verification of noise emission values of machinery and equipment).

6.4. Torque Range

- 6.4.1 The impact wrench must have an adjustable torque range from 60 Nm to 340Nm.
- 6.4.2 The torque range must be from 60Nm to no less than 340 Nm
- 6.4.3 It shall contain at least 60 ratchet teeth
- 6.4.4 The ratchet type shall be a push through
- 6.4.5 It shall contain a locking mechanism that is easy to use

6.5. Wrench Mechanism

- 6.5.1 The Torque wrench mechanism is to be maintenance free.

6.6. Body

- 6.6.1 The body of the tool and its components must be robust.
- 6.6.2 The machine must be well protected against rust.
- 6.6.3 The grip on the handles must have a non-slip surface.
- 6.6.4 Machines will be acceptable in standard factory production finish and colour. Details to be furnished. Due cognisance must be given to the life requirement of the machine.

6.7. Ergonomics

- 6.7.1 The tool must be ergonomically designed for maximum operator productivity and safety.
- 6.7.2 The impact wrench must have an anti-vibration handle.

7. Quality Control

- 7.1 All machines must be manufactured in an environment that complies to the latest ISO 9000 to ISO 9004 or similar quality control standards. Details must be furnished.
- 7.2 Machines will be subject to a technical evaluation and the final decision will, amongst others, be based on these findings.
- 7.3 All Torque wrenches shall be supplied with the calibration certificate

8. Legal and Operational

- 8.1 All machines must comply with the requirements of the Machinery and Occupational Safety Act, (Act 85 of 1993 – General Machinery Regulations) and The Machinery Directive 98/37/EC.
- 8.2 The machine must be completely assembled and filled with lubricants and ready for service in all respects.
- 8.3 Where grease nipples are fitted these are to be to DIN 71412 (Lubricating Nipples – Cone Type) in easily accessible positions.
Full details of lubrication applicable to machines on offer to be submitted.
- 8.4 An operator's handbook, service manual and spare parts list must be supplied with each machine in order to ensure that the machine is operated in accordance to the manufacturer's instructions.
- 8.5 All machines and equipment must be supplied complete with essential tools such as allen keys, spanners etc. in order to make essential adjustments as well as to fit or remove consumable items.
- 8.7 Consumable items must be available locally and must be of standardised format in order to be used on equipment of more than one supplier.
- 8.8 All machines and equipment is to be guaranteed for a minimum period of 12 months against faulty material and workmanship - fair wear and tear excluded. Full details of guarantee is to be submitted.
- 8.9 The information as requested by the various clauses in this specification are to be supplied in the form of technical data, pamphlets and/or drawings. If this is not complied to, offers may be overlooked.
- 8.10 Each machine purchased will be issued with a project number consisting of 20 characters which must be stamped or engraved directly onto the machine **or** on the manufacturer's data plate **or** a separate riveted plate on the particular machine.
- 8.11 Sufficient training must be given to all operators of these machines.