

SPECIFICATION RT57-05-50-60

BUS, 55 - 60 SEATER

A bus body, 55 to 60 seated capacity that comply with the requirements of the "Compulsory Vehicle Standard" issued by the SABS; and the Road Traffic Act and Regulations as well as NCRS requirements and complying to the following is required:

1. STRUCTURE

- 1.1 The bus body must be fully compliant to SABS and NRCS Homologation and Roll Over compliance.
- 1.2 A full length hand rail must be fitted to the roof, in the middle of the passage.
- 1.3 The interior ceiling must be fitted with LED strip lights and controlled by the driver.
- 1.4 A modesty screen and partition must be fitted behind driver.
- 1.5 Two external rear view mirrors must be fitted.
- 1.6 The front bumper and rear bumper must be GRP moulded.
- 1.7 A 2.5 kg Dry Chemical Powder fire extinguisher must be installed and clearly marked.
- 1.8 Towing hitch – front end – as supplied with chassis
- 1.9 A spare wheel carrier must be fitted to the chassis and clearly marked.
- 1.10 Separate lockable body side lockers must be fitted.
- 1.11 A swing out battery carrier in a separate lockable body side locker, incorporating a toolbox must be fitted on the left hand side of the body.

Particulars of offer: _____

2. DOORS

- 2.1 A manually operated slam type passenger and driver's door must be fitted.
- 2.2 The entrance steps will be illuminated with a step light.

Particulars of offer: _____

3. SEATS

- 3.1 The driver's seat must be fully adjustable and fitted with a safety belt.
- 3.2 Individual split back seats in vinyl with lap type safety belts on all seats must be fitted.
- 3.3 All seats must be fitted with chrome top rails.
- 3.4 Optional: 3-point seat belts all seats
- 3.5 Optional: Semi luxury with high back rest reclining seats, with 3-point seat belts on all seats must be fitted.
 - 3.5.1 Seats will be designed to provide the best comfort and safety features.
 - 3.5.2 Armrest on all seats, cup holders and foot rests and grab handles.

Number of seats: _____

Seat configuration: _____

Particulars of offer: _____

4. EMERGENCY EXIT

- 4.1 Mechanically adjustable Emergency Exit roof hatches must be fitted.
- 4.2 Side or rear emergency exits must be provided.
- 4.3 These emergency exits must be clearly marked.

Particulars of offer: _____

5. WINDOWS

5.1 Windscreen

5.1.1 A tinted windscreen with wipers plus windscreen washer must be fitted.

5.1.2 Two sunvisors and Heater/demister for windscreen with hot and cold air must be fitted.

Particulars of offer: _____

5.2 Side Windows

5.2.1 Tinted Sliding Windows including the driver's window must be fitted.

Particulars of offer: _____

6. MUDGUARDS:

Sturdy, firmly braced mudguards must be fitted behind the rear wheels.

Particulars of offer: _____

7. FINISH:

All metal shall be thoroughly cleaned and primed and painted with two coats of prime and good quality automotive enamel to match the departments colour spec.

Particulars of offer: _____

8. PARTICULARS OF OFFER:

A detailed sketch or full drawing of the body offered, showing all leading dimensions, must be submitted with tender.

Particulars of offer: _____