

SPECIFICATION RT57-09-01-02

CONSTRUCTION MOTOR GRADERS (850Nm) 17,000kg

COMPLY / NOT COMPLY
(*Delete/Cross-Out whichever is not applicable)

Noted

(Bidder to initial each noted item)

1. **NOTE. Equipment supplied against this specification must also comply with the General Specification for earth moving equipment**

*Comply / Not Comply

2. **OPERATING MASS**

The operating mass of the complete machine, when fully equipped as specified shall not be less than 17 000 kg. A mass certificate shall be supplied with bidder's offer.

*Comply / Not Comply

The mass on the front axle shall be not less than 5 200kg and on the rear axles not less than 12 000kg.

*Comply / Not Comply

3. **ENGINE**

The net power output of the diesel engine shall not be less than 135kW. This power rating must apply in all gears.

*Comply / Not Comply

The net torque shall be not less than of 850Nm.

*Comply / Not Comply

The engine shall be turbo charged.

*Comply / Not Comply

The engine shall be fitted with an engine cut out to prevent excessive idling.

*Comply / Not Comply

4. **TRANSMISSION**

A power shift transmission is required. An inching facility shall be incorporated.

*Comply / Not Comply

The transmission shall incorporate not less than six forward and six reverse speeds.

*Comply / Not Comply

Traction shall be by means of four rear wheels, tandem mounted and all driven. Final drives shall be of the planetary type.

*Comply / Not Comply

The graders shall be capable of a forward road speed of not less than 40 km/h.

*Comply / Not Comply

The transmission must have an electronically controlled over speed protection.

*Comply / Not Comply

The differential must be fitted with a diff-lock or be of a no-spin type.

*Comply / Not Comply

5. FRONT WHEELS and STEERING

Hydraulic powered frame articulation of up to 20° to each side shall be featured.

*Comply / Not Comply

Articulation shall be behind the cab

*Comply / Not Comply

Full leaning wheel capability with power steering is required.

*Comply / Not Comply

The total arc of wheel lean when travelling straight ahead must be a minimum of 15 degrees.

*Comply / Not Comply

6. BRAKES

Foot controlled, power assisted disc brakes on the tandem wheels shall be provided.

*Comply / Not Comply

Brakes shall be of the multiple disc oil immersed type.

*Comply / Not Comply

A separately actuated, mechanical parking brake shall be fitted.

*Comply / Not Comply

7. TYRES

17.5x25-12 ply G3 having a bi-directional tread pattern, fitted to 3 piece rims are required on all wheels.

*Comply / Not Comply

8. CAB

The cab shall be fitted with a roll over protective structure (ROPS).

*Comply / Not Comply

The differential lock switch is to illuminate when the diff lock is in the **on** position.

*Comply / Not Comply

9. MOULDBOARD

The mouldboard length shall not be less than 4.27 m (14ft).

*Comply / Not Comply

Replaceable cutting edges and overlay end pieces shall be fitted. Edges shall be of high carbon steel and heat treated.

*Comply / Not Comply

The mouldboard, cutting edges and overlay end pieces must have hole spacing to the American Association of State Highway Officials standard and take M16 plough bolts.

*Comply / Not Comply

The blade down force is not to be less than 8 000 kg.

*Comply / Not Comply

Hydraulic control shall be provided for:

*Comply / Not Comply

(a) mouldboard side shift

*Comply / Not Comply

(b) circle side shift

*Comply / Not Comply

(c) mouldboard lift and lower

*Comply / Not Comply

(d) blade pitch adjustment

*Comply / Not Comply

The circle shall be hydraulically operated through 360°.

*Comply / Not Comply

The shoulder reach to the outside of the rear tyres with straight frame to the right must not be less than 1860 mm and to the left must not be less than 1750 mm.

Blade adjustment for bank sloping of 90° on both sides shall be provided.

*Comply / Not Comply

Blade control shall incorporate a float facility.

*Comply / Not Comply

Replaceable wear strips between frame and circle shall be fitted.

*Comply / Not Comply

The motor grader is to be fitted with pressure relief valves on all hydraulic circuits of the blade assembly to prevent undue stress to the components of the blade assembly should they come into contact with an immovable object whilst in motion.

A slip clutch may be fitted to the circle motor in place of a pressure relief valve.

*Comply / Not Comply

10. RIPPER/ SCARIFIER

A heavy duty rear mounted ripper/ scarifier shall be fitted.

*Comply / Not Comply

The ripping depth shall be not less than 400mm and a minimum of 3 shanks and 5 shank positions shall be fitted.

Comply / Not Comply

The scarifying depth shall not be less than 300 mm. A minimum of eight shanks shall be fitted.

*Comply / Not Comply

Shanks shall be supplied complete with replaceable tips.

*Comply / Not Comply

The ripper is to be fitted with a pressure relief valve on the hydraulic circuit to prevent undue stress to the components of the ripper/scarifier assembly should it come into contact with an immovable object while in motion.

*Comply / Not Comply

At each end of the ripper/scarifier frame, a piece of 30 mm inside diameter pipe (or 30x30 square tube), 200 mm long and closed off at the lower end, is to be welded at an angle of approximately 75 degrees to the horizontal (to hold red warning flags).

*Comply / Not Comply

The total mass of the assembly shall be not less than 1000kg

*Comply / Not Comply

11. LIGHTING AND ELECTRICAL

An orange rotating light shall be fitted on the roof of the cab in accordance with the OHS Act of 1993.

*Comply / Not Comply

12	FRAME WARRANTY	
	The grader frame must carry a minimum of a 10 year warranty	*Comply / Not Comply
13	OPTIONAL EXTRAS	
	The following optional extras are to be quoted for separately	
13.1	CENTRALISED LUBRICATION SYSTEM	
	The supply and installation of a single line centralised lubrication system (Vogel KFU 2-40/24V or equivalent) for the front suspension.	*Comply / Not Comply
13.2	SPARE RIM AND TYRE	
	Bidders are to quote separately for a spare rim and tyre of the same size as that fitted to the grader.	*Comply / Not Comply
13.3	BLADE FLOAT	
	Blade control incorporating a float facility.	*Comply / Not Comply
13.4	2 SEATER CAB	
	The cab is to accommodate one seated passenger in addition to the driver (trainer seat) and must comply with ISO 13459:2012. Seat belts are to be provided for both seats.	*Comply / Not Comply
13.5	ENGINE MONITORING SYSTEM	
	An engine monitoring system (Sentinel/ Lubrivent or equivalent) as specified in the General Conditions.	*Comply / Not Comply
13.6	UDF FILTER	
	The fitment of a UDF (Ultrafine Depth Filtration) diesel fuel filter as specified in the General Conditions.	*Comply / Not Comply
13.7	OIL SAMPLING VALVES	
	The fitment of oil sampling valves as specified in the General Conditions.	*Comply / Not Comply
13.8	SERVICE PLAN	
	1000h, 2000h and 3000h full maintenance service plans as specified in the General Specifications	*Comply / Not Comply
13.9	NUMBER PLATES	
	Supply of 2 number plates as specified in the General Specifications.	*Comply / Not Comply

13.10 LICENSING ON eNaTIS

Licensing on eNaTIS as specified in the General Specifications.

*Comply / Not Comply

13.11 WEST COAST PAINT SPECIFICATION

Painting to the “West Coast” specification as specified in the General Specifications.

*Comply / Not Comply

13.12 MANUALS

Operators, workshop and spares manuals as specified in the General Specifications.

*Comply / Not Comply

13.13 ORANGE LED LIGHT STRIPS

The fitment of orange LED light strips to the cab as specified in the General Specifications.

*Comply / Not Comply

13.14 TYRE PUMP

A power driven tyre pump as specified in the General Specifications.

*Comply / Not Comply

13.15 AIR CONDITIONING

Air conditioning for the cab.

*Comply / Not Comply

13.16 TRAINING

Training of operators and mechanics in terms of the General Specifications.

*Comply / Not Comply

TECHNICAL SCHEDULE

The Technical Schedule must be completed in full; failure to comply will invalidate your bid

Clearly delete/cross-out whichever is not applicable at YES/NO questions

DETAILS OF OFFER

1. MAKE AND MODEL

Make _____

Model _____

Manufacturer _____

Country of origin _____

Year of manufacture _____

2. OPERATING MASS

Complete machine _____ kg

On front axle _____ kg

On rear axles _____ kg

3. ENGINE

(a) Make _____

(b) Model _____

(c) Net power output (as specified) _____ kW

(d) Net torque output (as specified) _____ Nm

At rpm _____ rpm

(e) Maximum governed speed _____ rpm

(f) Fuel consumption at full load. _____

4. TRANSMISSION

(a) Make _____

(b) Model _____

(c) Powershift? YES / NO

(d) Number of speeds:

- Forward _____
- Reverse _____
- Maximum forward speed: 1st _____ km/h
- 2nd _____ km/h
- 3rd _____ km/h
- 4th _____ km/h
- 5th _____ km/h
- 6th _____ km/h

DETAILS OF OFFER

- 7th _____ km/h
- 8th _____ km/h
- Reverse: 1st _____ km/h
- 2nd _____ km/h
- 3rd _____ km/h
- 4th _____ km/h
- 5th _____ km/h
- 6th _____ km/h

5. FRONT WHEELS AND STEERING

Frame articulation _____ °

Arc of wheel lean _____ °

6. TYRES

Tyre size and ply _____

7. AIR CLEANER

(a) Make and model _____

(b) Safety element make and model _____

8. MOULDBOARD

(a) Length _____ mm

- (b) Mouldboard side shift, left and right _____mm_____mm
- (c) Blade down force _____kg
- (d) Maximum reach outside tyres, left and right _____mm_____mm
- (e) Maximum lift above ground _____mm
- (f) Type of pressure relief fitted _____

9. RIPPER/ SCARIFIER

- (a) Ripping depth _____mm
- (b) Number of ripper shanks supplied _____
- (c) Number of shank positions _____
- (d) Are shanks supplied complete with replaceable tips? YES / NO
- (e) Scarifying depth _____mm
- (f) Number of scarifier shanks _____

- (g) Total mass of assembly _____kg

10. GENERAL SPECIFICATIONS

Does the bid comply with the conditions of the attached "General Specifications" YES / NO

11. FRAME WARRANTY

Frame warranty _____yrs

12. OPTIONAL EXTRAS

Have the optional extras been quoted for? YES / NO

13. GENERAL

- (a) Are all the required accessories fitted? YES / NO
- (b) Are all drawings, brochures, graphs and sheets submitted? YES / NO
- (c) Is the offer completely to specification? YES / NO
- (d) State all deviations from the specifications _____

(e) Has the General Specification been completed?

YES / NO

Please note that failure to furnish all required technical specifications, brochures and information of products offered will invalidate the Bid.