

Item	Material	Short Text	Quantity requested	Umc
10	0000069	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 170 MM; WIDTH: 39 MM; ROW: SINGLE; SUPPL P/N: 6316; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	60	EA
20	0000083	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 35 MM; WIDTH: 11 MM; ROW: SINGLE; SUPPL P/N: 6202-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	120	EA
30	0000084	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 35 MM; ROW: SINGLE; SUPPL P/N: 6314; ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	40	EA
40	0000087	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 23 MM; ROW: SINGLE; SUPPL P/N: 6308C3; MEDIUM DUTY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA

50	0025316	BUSH, TAPER LOCK: BORE DIAMETER: 65 MM; SERIES: 3020; MATERIAL: STL; REFERENCE NO: 3020; KEYWAY: 18MM WIDTH, 4.4MM DEPTH	5	EA
60	0026531	BUSH, TAPER LOCK: BORE DIAMETER: 40 MM; SERIES: 2012; MATERIAL: STL; SPECIFICATION: ISO 9001-2008; MANUF P/N: 2012-40; REFERENCE NO: 2012; KEYWAY: 12MM WIDTH, 3.3MM DEPTH	100	EA
70	0026568	BUSH, TAPER LOCK: BORE DIAMETER: 1/2 IN; SERIES: 1210; MATERIAL: STL; REFERENCE NO: 1210	100	EA
80	0029816	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 17 MM; OUTSIDE DIAMETER: 40 MM; WIDTH: 12 MM; ROW: SINGLE; SUPPL P/N: 6203-2RS; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA
90	0029826	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 15 MM; OUTSIDE DIAMETER: 42 MM; WIDTH: 13 MM; ROW: SINGLE; SUPPL P/N: 6302; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA

100	0029837	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 16 MM; ROW: SINGLE; SUPPL P/N: 6206-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	40	EA
110	0029859	BEARING, ROLLER: TYPE: CYLINDRICAL; INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 23 MM; ROW: SINGLE; BORE SHAPE: CYLINDRICAL; STYLE: OPEN; CAGE MATERIAL: STL; ROLLING ELEMENT: CYLINDRICAL; SPECIFICATION: ISO 9001; SUPPL P/N: NU308STD; NOTE: ITEM MUST BE ORIGINAL PACKED AND SEALED; IBI 21928	10	EA
120	0029863	BEARING, ROLLER: TYPE: CYLINDRICAL; INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 37 MM; ROW: SINGLE; SUPPL P/N: NU315	5	EA
130	0029918	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 180 MM; WIDTH: 41 MM; ROW: SINGLE; SUPPL P/N: 7317BM; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA

140	0029921	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 23 MM; ROW: SINGLE; SUPPL P/N: 7308B; NOTE: ITEM MUST BE ORIGINAL PACKED, WITH STEEL GAGE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	35	EA
140	0029927	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 14 MM; ROW: SINGLE; SUPPL P/N: 6204-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
160	0029952	BEARING, BALL: TYPE: CONRAD; STYLE: OPEN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 6409; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
170	0029956	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; CAGE MATERIAL: STL; SUPPL P/N: 6304; ITEM MUST BE ORIGINAL PACKED; IBI 14788; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA

180	0029957	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6205; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
190	0029985	BEARING, ROLLER: TYPE: SLEW RING; INSIDE DIAMETER: 715 MM; OUTSIDE DIAMETER: 979 MM; WIDTH: 100 MM; ROW: SINGLE; SUPPL P/N: RKS22302-5707 XX; WITHOUT GEAR, NUMBER OF HOLES, OUTER RING 28, INNER RING 28, GREASE NIPPLES ON OUTER RING	10	EA
200	0030043	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 50 MM; LENGTH: 45 MM; MATERIAL: STEEL; SUPPL P/N: H311; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	120	EA
210	0030048	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 75 MM; LENGTH: 63 MM; MATERIAL: STEEL; SUPPL P/N: H317; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 110 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100	EA

220	0030050	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 75 MM; LENGTH: 63 MM; MATERIAL: STEEL; SUPPL P/N: H317; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 110 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	150	EA
230	0030090	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 160 MM; OUTSIDE DIAMETER: 290 MM; WIDTH: 80 MM; ROW: DOUBLE; SUPPL P/N: 22232CCKC3; REFERENCE NUMBER MUST BE CAST AND NOT ENGRAVED ON AND ORIGINAL PACKED	10	EA
240	0030093	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 170 MM; OUTSIDE DIAMETER: 280 MM; WIDTH: 88 MM; ROW: DOUBLE; SUPPL P/N: 23134CCK-C3; NOTE - THE REFERENCE NUMBER MUST BE CAST AND NOT ENGRAVED ON AND ORIGINAL PACKED	10	EA
250	0030157	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 140 MM; WIDTH: 33 MM; ROW: SINGLE; SUPPL P/N: 7313B; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
260	0030161	BEARING, ROLLER: TYPE: CYLINDRICAL; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 30 MM; ROW: SINGLE; SUPPL P/N: NU218	80	EA

270	0030165	BEARING, BALL: TYPE: SPHERICAL; STYLE: OPEN; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 36 MM; ROW: DOUBLE; SUPPL P/N: 2217K; NOTE! ITEM MUST BE ORIGINAL PACKED, TAPERED BORE.; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100	EA
280	0030184	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 16 MM; ROW: SINGLE; SUPPL P/N: 7206B; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	50	EA
290	0030192	BEARING, THRUST: ROLLING ELEMENT: BALL; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 27 MM; STYLE: OPEN; SUPPL P/N: 51213; SINGLE DIRECTION, SINGLE ROW	25	EA
300	0030204	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 230 MM; WIDTH: 64 MM; ROW: DOUBLE; BORE SHAPE: TAPER; SUPPL P/N: 22226CCK W33C3; NOTE - THE REFERENCE NUMBER MUST BE CAST AND NOT ENGRAVED ON AND MUST BE ORIGINAL PROTECTIVE PACKED	100	EA

310	0030213	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 100 MM; LENGTH: 77 MM; MATERIAL: STEEL; SUPPL P/N: HE322; SIZE 145 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	50	EA
320	0030259	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 200 MM; WIDTH: 53 MM; ROW: DOUBLE; SUPPL P/N: 22222CK-STD	120	EA
330	0030264	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6304-2RS; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA
340	0030265	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 17 MM; ROW: SINGLE; SUPPL P/N: 6305; ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA

350	0030268	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 6311; ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
360	0030281	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 80 MM; WIDTH: 21 MM; ROW: SINGLE; SUPPL P/N: 7307B; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
370	0030290	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: SHIELD; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 14 MM; ROW: SINGLE; SUPPL P/N: 6204Z; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	25	EA
380	0030304	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 65 MM; LENGTH: 55 MM; MATERIAL: STEEL; SUPPL P/N: H315; 98 MM OD; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; CAMDEN SKF BRAND ONLY; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	50	EA

390	0030305	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 100 MM; LENGTH: 77 MM; MATERIAL: STEEL; SUPPL P/N: H322; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 116.5 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100	EA
400	0030307	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 115 MM; LENGTH: 92 MM; MATERIAL: STEEL; SUPPL P/N: H3126; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 165 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	200	EA
410	0030309	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 140 MM; LENGTH: 119 MM; MATERIAL: STEEL; SUPPL P/N: H3132; 210 MM OD; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PACKED AND MARKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	35	EA
420	0030333	BEARING, THRUST: ROLLING ELEMENT: AXIAL SPHERICAL ROLLER; INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 225 MM; WIDTH: 58 MM; MANUF P/N: 29326-E1-XL; STANDARD FIT; ROW SINGLE; TYPE TAPER CONE/CUP	15	EA

430	0030339	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 6409C3; NOTE:THE REFERENCE NUMBER MUST BE CAST AND NOT ENGRAVED ON BEARING AND ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	75	EA
440	0030372	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 8 MM; OUTSIDE DIAMETER: 22 MM; WIDTH: 7 MM; ROW: SINGLE; SUPPL P/N: 608-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
450	0030382	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: SHIELD; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6205Z; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
460	0030383	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6205-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	50	EA

470	0030384	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: SEAL; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6205-RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
480	0030429	BEARING, THRUST: ROLLING ELEMENT: BALL; INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 78 MM; WIDTH: 22 MM; STYLE: OPEN; CAGE MATERIAL: STL; SUPPL P/N: 51210; SINGLE DIRECTION, SINGLE ROW, MEDIUM DUTY, PRESSED	10	EA
490	0030451	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 130 MM; WIDTH: 31 MM; ROW: DOUBLE; SUPPL P/N: 22215CK; SKF BRAND ONLY, NO OTHER BRANDS ACCEPTABLE	200	EA
500	0030453	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 230 MM; WIDTH: 64 MM; ROW: DOUBLE; SUPPL P/N: 22226CK-STD; NOTE - ITEM MUST BE ORIGINAL PACKED	200	EA
510	0030492	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 6311-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
520	0030497	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 40 MM; ROW: DOUBLE; SUPPL P/N: 22218 C-STD	20	EA

530	0030500	BEARING, ROLLER: TYPE: SELF ALIGNING SPHERICAL; INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 200 MM; WIDTH: 52 MM; ROW: DOUBLE; BORE SHAPE: CYLINDRICAL; CAGE MATERIAL: TVPB; ROLLING ELEMENT: ROLLER SPHERICAL; OEM P/N: 23026-E1-TVPB-C3-XL; E1-LUBRICATION GROOVE ON IN THE CENTRE OF OUTER RACE WITH 3 HOLES	10	EA
540	0030560	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: SEAL; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6304; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
550	0030561	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 70 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 63.5 MM; ROW: DOUBLE; SUPPL P/N: 3314A; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	35	EA
560	0030595	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 19 MM; ROW: SINGLE; SUPPL P/N: 6209-2RS; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	8	EA

570	0030595	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 19 MM; ROW: SINGLE; SUPPL P/N: 6209-2RS; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	400	EA
580	0030595	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 19 MM; ROW: SINGLE; SUPPL P/N: 6209-2RS; NOTE: ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	500	EA
590	0030598	BEARING, BALL: TYPE: THRUST SINGLE DIRECTION; STYLE: OPEN; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 110 MM; WIDTH: 19 MM; ROW: SINGLE; SUPPL P/N: 51117; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
600	0030624	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; ROW: SINGLE; SUPPL P/N: 6205-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	160	EA

610	0030636	EARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 31 MM; ROW: DOUBLE; SUPPL P/N: 22213CK-C3	25	EA
620	0030647	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 90 MM; WIDTH: 20 MM; ROW: SINGLE; SUPPL P/N: 6210C3; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
630	0030648	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 25 MM; ROW: SINGLE; SUPPL P/N: 6309C3; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
640	0030652	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 72 MM; WIDTH: 17 MM; ROW: SINGLE; SUPPL P/N: 6207-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA

650	0030985	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 72 MM; WIDTH: 19 MM; ROW: SINGLE; CAGE MATERIAL: STL; SUPPL P/N: 6306C3; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA
670	0031121	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 170 MM; WIDTH: 39 MM; ROW: SINGLE; SUPPL P/N: 7316B; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100	EA
680	0031123	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 39.7 MM; ROW: DOUBLE; SUPPL P/N: 3309NR; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
690	0031126	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 25 MM; ROW: SINGLE; SUPPL P/N: 6309-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA

700	0031130	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 6311C3; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA
710	0031131	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 19 MM; ROW: SINGLE; SUPPL P/N: 6209C3; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
720	0031148	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 25 MM; ROW: DOUBLE; SUPPL P/N: 22211CCKC3C3	200	EA
730	0031162	BEARING, SLEEVE: TYPE: JOURNAL THRUST; INSIDE DIAMETER: 80 MM; OUTSIDE DIAMETER: 133 MM; LENGTH: 218 MM; MATERIAL: STAINLESS STEEL; SUPPL P/N: 3065-204; 3065-181; 3065 - 204; DRAWING NO: E262 REV 1; E259 REV 1; 3065-181 ITEM 14 REV 0; 3065-204 ITEM 27 REV 0; REFERENCE NO: 43305-627-MOD10; BUSH; FOR AC AND DC LUB OIL PUMPS, TYPE 45375-039 AND 040, MANUAL VOLUME 4 BOOK 10 SECTION 27, ALSO FOR BOOSTER PUMP TURBINE, TYPE 43305-627-MOD10	5	EA

740	0031295	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 16 MM; ROW: SINGLE; SUPPL P/N: 6206C3; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	35	EA
750	0031741	BEARING, ROLLER: TYPE: CUP/CONE, TAPER; INSIDE DIAMETER: 71.44 MM; OUTSIDE DIAMETER: 136.53 MM; WIDTH: 41.28 MM; ROW: SINGLE; SUPPL P/N: 632-645	50	EA
760	0031758	BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 23 MM; ROW: DOUBLE; BORE SHAPE: TAPER; SUPPL P/N: 22209CCKC3	10	EA
770	0031882	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 60 MM; LENGTH: 65 MM; MATERIAL: STEEL; REFERENCE NO: H2313; SKEFKO TYPE, SIZE 69 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICAB	30	EA
780	0031883	BEARING, BALL: TYPE: SELF ALIGNING; STYLE: OPEN; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 140 MM; WIDTH: 48 MM; ROW: DOUBLE; SUPPL P/N: 2313KC3; OL 06 09 OC OC N N; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	120	EA

790	0031911	BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; INSIDE DIAMETER: 318 MM; OUTSIDE DIAMETER: 480 MM; WIDTH: 160 MM; ROW: DOUBLE; CAGE MATERIAL: STL; SUPPL P/N: 24064CCW33C3; FOR LOESCHE ROCKER ARM, PACKED IN WOODEN BOX IN CLEAN AND DRY CONDITION IN A FLAT POSITION	40	EA
800	0032294	BEARING, THRUST: ROLLING ELEMENT: ROLLER NEEDLE; INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 60 MM; WIDTH: 3 MM; SUPPL P/N: AXK4060; COMPLETE WITH 2 WASHERS AS4060 EACH 1MM THICK, ROW SINGLE	5	EA
810	0032378	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 40 MM; OUTSIDE DIAMETER: 80 MM; WIDTH: 23 MM; ROW: DOUBLE; SUPPL P/N: 22208CK; FOR USE ON WATER TREATMENT PLANT AIR CONDITIONING UNIT	10	EA
820	0032381	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 16 MM; ROW: SINGLE; SUPPL P/N: 6206-2RS; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	15	EA
830	0032387	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 55 MM; ROW: DOUBLE; SUPPL P/N: 22315-C3	5	EA
840	0032446	BEARING: TYPE: SE-HAMMER SHAFT; OUTSIDE DIAMETER: 65 MM; STYLE: SPLIT; MATERIAL: CI; DRAWING NO: 3-LTS-000483 REV 1; REFERENCE NO: 14; FOR LURGI PRECIPITATORS UNIT 4-6	800	EA

850	0032470	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 100 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 24 MM; ROW: SINGLE; SUPPL P/N: 6020-2ZC3; DUTY: MEDIUM; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	120	EA
860	0032486	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 190 MM; OUTSIDE DIAMETER: 320 MM; WIDTH: 104 MM; ROW: DOUBLE; SUPPL P/N: 23138C-W33	5	EA
870	0032511	BEARING, ROLLER: TYPE: SELF ALIGNING; INSIDE DIAMETER: 190 MM; OUTSIDE DIAMETER: 320 MM; WIDTH: 104 MM; ROW: DOUBLE; SUPPL P/N: 23138CJ/W33	5	EA
890	0032519	BEARING, ROLLER: TYPE: NEEDLE; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 42 MM; WIDTH: 4 MM; ROW: SINGLE; SUPPL P/N: 042502000; FOR USE WITH VKS1 160-25-10-33 VALVE, COMPLETE WITH WASHERS	5	EA
900	0032525	BEARING, FLANGE BLOCK: ROLLING ELEMENT: BALL; INSIDE DIAMETER: 75 MM; SHAPE: SQ; BLOCK SIZE: SQ 198 X THK 90 MM; BOLT MOUNTING: 4; BOLT DIAMETER: M23; HOUSING MATERIAL: CI; SUPPL P/N: UCFX15	650	EA

910	0032529	BEARING, SLEEVE: TYPE: HORIZONTAL SPLIT DE/NDE JOURNAL; INSIDE DIAMETER: 5 IN; OUTSIDE DIAMETER: 7.5 IN; LENGTH: 5 IN; MATERIAL: WHITE METAL BS 2613-70; SPECIFICATION: BS 2613- 70; SIZE: 5 IN; REFERENCE NO: 2LM3137/01; JKC 450/720; 2LM3489/01; SIZE 5 IN GA; FOR USE ON CONDENSATE EXTRACTION PUMP-CEP-MOTOR BEARINGS BOTH DRIVE END AND NDE SIDES; TECHNICAL EVALUATION MUST BE DONE PRIOR TO ORDER PLACEMENT THE FOLLOWING DOCUMENTS ARE REQUIRED FOR THE EVALUATION: BEARING/S DATA PACKAGE CONTAINING TYPICAL INSPECTION REPORT WITH ALL BEARING/S DIMENSIONS, CLEARANCES AND TOLERANCES AND ALSO TYPICAL MATERIAL TEST CERTIFICATES FOR NEWLY MANUFACTURED OR OLD REFURBISHED BEARINGS; NDT REPORTS SHOWING	20	EA
920	0032531	BEARING, ROLLER: TYPE: CYLINDRICAL; INSIDE DIAMETER: 180 MM; OUTSIDE DIAMETER: 300 MM; WIDTH: 118 MM; ROW: DOUBLE; REFERENCE NO: 24136COW33; MAIN CYL 87 R/ARM MILL	10	EA
930	0032597	BEARING, ROLLER: TYPE: CYLINDRICAL; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: NU311-C3	5	EA

940	0032601	BEARING, BALL: TYPE: CONRAD; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 65 MM; OUTSIDE DIAMETER: 140 MM; WIDTH: 33 MM; ROW: SINGLE; SUPPL P/N: QJ313MASTD; MODEL NO: M/P300- 350EME; FOR USE ON MATHER AND PLATT 2ND STAGE EXTRACTION PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	125	EA
950	0032676	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 55 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 29 MM; ROW: SINGLE; SUPPL P/N: 7311B; ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	10	EA
960	0032700	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 20 MM; OUTSIDE DIAMETER: 47 MM; WIDTH: 14 MM; ROW: SINGLE; SUPPL P/N: 6204-2Z; ITEM MUST BE ORIGINAL PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	25	EA
970	0033409	BEARING, SLEEVE: REFERENCE NO: A37913340025; FOR USE ON JOY TA18-28 COOPER TURBO COMPRESSOR, ITEMS TO BE PACKED	20	EA
980	0033411	BEARING: TYPE: BULLGEAR; SUPPL P/N: A37913340026; FOR USE ON JOY COOPER TURBO COMPRESSOR TYPE TA18-28	10	EA

990	0033412	BEARING, SLEEVE: TYPE: JOURNAL; INSIDE DIAMETER: 530 MM; OUTSIDE DIAMETER: 620 MM; LENGTH: 425 MM; MATERIAL: WHITE METAL; SUPPL P/N: NO 10; REFERENCE NO: S2079/05; FOR 600MW TURBO GENERATOR, EXITER, FOR GEN ROTOR WITH FORGING NO EESFX 21033 AND SIZE 527.2MM, NOTE - THIS IS NOT A STANDARD SIZE, A UNIQUE ID NO AND BONDING CERTIFICATE MUST BE PROVIDED, TO BE PACKED IN WOODEN BOXES	5	EA
1000	0033413	BEARING, SLEEVE: TYPE: JOURNAL; INSIDE DIAMETER: 535 MM; OUTSIDE DIAMETER: 615 MM; LENGTH: 400 MM; MATERIAL: WHITE METAL; SUPPL P/N: NO 10; REFERENCE NO: S2079/06; S2125/01; FOR 600MW TURBO GENERATOR, EXITER NO 10, FOR GEN ROTORS WITH FORGING NUMBER EESFX 22065 AND EESFX 21414 WITH SIZES 529.98MM, NOTE - THESE ARE NOT STANDARD SIZES, UNIQUE ID NUMBER AND BONDING CERTIFICATE TO BE SUPPLIED, TO BE PACKED IN WOODEN BOXES	5	EA
1020	0033414	BUSH, TAPER LOCK: BORE DIAMETER: 75 MM; SERIES: 4040; MATERIAL: STL; REFERENCE NO: 4040; KEYWAY: 20MM WIDTH, 4.9MM DEPTH	5	EA
1030	0034206	BEARING, SLEEVE: TYPE: MILL MOTOR; INSIDE DIAMETER: 125 MM; OUTSIDE DIAMETER: 215 MM; LENGTH: 193 MM; MATERIAL: WHITE METAL; SUPPL P/N: 2231140601	35	EA

1040	0034219	SLEEVE: TYPE: CONTROL; DIMENSIONS: ID 35 X OD 80 X LG 415 MM; MATERIAL: BRZ; APPLICATION: GEARBOX; SPECIFICATION: ISO 9001; SUPPL P/N: TCR40415440; MODEL NO: R110KGS; FOR USE ON VOITH TURBO GEARBOX	10	EA
1050	0034244	BUSH, TAPER LOCK: BORE DIAMETER: 60 MM; SERIES: 3020; MATERIAL: STL; SPECIFICATION: ISO 9001-2008; MANUF P/N: 3020-60; REFERENCE NO: 3020; KEYWAY: 18MM WIDTH, 4.4MM DEPTH, 108MM NOMINAL OD AT LARGE END OF TAPER	5	EA
1060	0034252	SLEEVE, SHAFT: TYPE: PROTECTION; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 121 MM; LENGTH: 303 MM; MATERIAL: STL; GRADE: X21262; SPECIFICATION: ISO 9001; MODEL NO: M/P300-350EME; REFERENCE NO: 204-171-189-001; FOR GLAND EXECUTION, FOR USE ON 2ND STAGE EXTRACTION	10	EA
1080	0034253	BEARING, BALL: TYPE: CONRAD; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 42.86 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 49.21 MM; ROW: SINGLE; SUPPL P/N: B251; ER27T; SEALMASTER, SIZE 1-11/16 INCH, FOR VOLUMETRIC COAL FEEDER MODEL 44115, BABCOCK; ITEM MUST BE ORIGINAL(PROTECTIVE) PACKED; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	40	EA

1090	0034257	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: SHIELD; INSIDE DIAMETER: 43 MM; OUTSIDE DIAMETER: 85 MM; WIDTH: 43 MM; ROW: SINGLE; SUPPL P/N: S1111K; REFERENCE NO: FAFNIR1111R; WITH LOCKING COLLAR FAFNIR; COLLAR SIZE 63MM O/D X 43MM I/D X 18MM WIDE, LIP SIZE 55MM I/D X 5MM DEEP WITH M9 GRUB SCREW, FOR COAL FEEDER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
1111	0034263	BEARING, BALL: TYPE: CONRAD; STYLE: OPEN; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 42 MM; WIDTH: 12 MM; ROW: SINGLE; DRAWING NO: L-A11163-B REV 1; REFERENCE NO: B253; 3L05; FOR VOLUMETRIC COAL FEEDER; DESIGN 1969; CLEANOUT CONVEYOR REDUCER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
1110	0034266	BEARING, BALL: TYPE: CONRAD; STYLE: DOUBLE SEAL; INSIDE DIAMETER: 19 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 31 MM; ROW: SINGLE; SUPPL P/N: NSK-UC-204-12S; FANFIR TYPE 1012, FOR VOLUMETRIC COAL FEEDER TOP SUPPORT ROLLER; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	200	EA

1120	0034270	BEARING, SLEEVE: TYPE: BUSH; INSIDE DIAMETER: 330 MM; OUTSIDE DIAMETER: 387 MM; LENGTH: 285 MM; MATERIAL: STL BABBITTED; LINER WHITE METAL LINED SHELL, CONSIST OF 2 HALVES, SIZE: 13 INCH, FOR ID FAN	20	EA
1130	0034276	BUSH, TAPER LOCK: BORE DIAMETER: 42 MM; SERIES: 1615; MATERIAL: STL; REFERENCE NO: 1615	15	EA
1140	0034280	SLEEVE, ADAPTOR: TYPE: BEARING; REFERENCE NO: H2312; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	65	EA
1150	0034599	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 118 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 28 MM; BLOCK SIZE: WD 130 X LG 448 X HT 285 MM; SHAFT HEIGHT: 150 MM; ROLLING ELEMENT: ROLLER CYLINDRICAL; HOUSING MATERIAL: STL; SUPPL P/N: SNA 526; SNA526; PLUMMER BLOCK, DUTY: HEAVY	90	EA
1160	0034614	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 85 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 28 MM; BLOCK SIZE: WD 102 X LG 400 X HT 234 MM; SHAFT HEIGHT: 124 MM; HOUSING MATERIAL: STL; SUPPL P/N: SNA522- 619; PLUMMER BLOCK	35	EA
1170	0034615	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 90 MM; BOLT DIAMETER: M20; BLOCK SIZE: WD 160 MM; ROLLING ELEMENT: SPHERICAL; HOUSING MATERIAL: STL; SUPPL P/N: SNA520-617; HOUSING, WITHOUT SEALS	50	EA

1180	0034691	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 67 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M20; BLOCK SIZE: WD 95 X LG 257 X HT 125 MM; SHAFT HEIGHT: 70 MM; ROLLING ELEMENT: SPHERICAL; HOUSING MATERIAL: CI; REFERENCE NO: SNA511; HOUSING, WITH TWO DOUBLE LIP SEALS	10	EA
1190	0034815	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 100 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M24; BLOCK SIZE: WD 136 X LG 340 X HT 194 MM; HOUSING MATERIAL: CI; SUPPL P/N: SNH518-615; DEEP GROOVE, PLUMMER WITH LOCATING RINGS, USED ON CONDITIONED ASH TAKE UP TENSION CABLE SHEAVE WHEELS AND FIRST COLLECTOR CONVEYOR DE NDE DRIVE SIDE	5	EA
1200	0034842	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 50 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M20; BLOCK SIZE: WD 68 X LG 254 X HT 132 MM; SHAFT HEIGHT: 71 MM; ROLLING ELEMENT: BALL/ROLLER SPHERICAL SELF ALIGNING; HOUSING MATERIAL: STL; SUPPL P/N: SNH511; DUTY: MEDIUM	15	EA

1210	0034973	BEARING, SLEEVE: TYPE: SPLIT BUSH; INSIDE DIAMETER: 502 MM; OUTSIDE DIAMETER: 545 MM; LENGTH: 255 MM; MATERIAL: WHITE METAL; DRAWING NO: R200/AO/5862/100- 101 REV 1; DUV(A4)006 REV 1; REFERENCE NO: SA763; SHELL TOP AND BOTTOM ITEM GLACIER; MATERIAL AS PER SPECIFICATION TO BE STAMPED ON REAR OF SHELL; FOR NO 1 TURBINE; IN SETS OF 2 TOP AND BOTTOM; MATERIAL CERTIFICATES TO BE SUPPLIED ON DELIVERY; ITEM MUST COMPLY TO DOCUMENT ETS0001 REV 1 OBTAINABLE FROM DESIGN AND SPEC MANAGER DUVHA POWER STATION; MACHINE STABILITY GROOVE ON 60 DEG ARC LOAD AREA OF CENTRE LINE OF BOTTOM HALF 1 IN WIDE BY 0.05 IN + 0.01IN DEEP BLENDING INTO SIDE OIL RELIEVE AS PER SITE NO JOURNAL DIAMETER TO BE CONFIRMED	10	EA
1220	0034982	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 93 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 21 MM; BLOCK SIZE: WD 120 X LG 313 X HT 175 MM; SHAFT HEIGHT: 95 MM; ROLLING ELEMENT: ROLLER CYLINDRICAL; HOUSING MATERIAL: CI; SUPPL P/N: SNA516-613; HOUSING, WITH ADAPTER SLEEVE; DUTY: HEAVY	36	EA
1230	0037044	SLEEVE: TYPE: ROCKER ARM CLAMPING; DIMENSIONS: ID 350 X OD 385 X LG 135 MM; MATERIAL: STL; DRAWING NO: 0.1526.00.0500 ITEM 6 REV 1; 0.1526.00.0500 REV 1; FOR LOESCHE MILL	5	EA

1240	0037049	SLEEVE: TYPE: SEAL; DIMENSIONS: ID 460 MM; MATERIAL: CS; SUPPL P/N: 02; DRAWING NO: 2.1526.00.0402 REV 1; FOR USE ON LOESCHE MILL ROLLER ASSEMBLY	5	EA
1250	0039172	BUSH, TAPER LOCK: BORE DIAMETER: 115 MM; SERIES: 5050; MATERIAL: CAST IRON; DUVHA MATERIAL CAST IRON	5	EA
1260	0044034	SLEEVE, SHAFT: TYPE: PUMP; INSIDE DIAMETER: 88 MM; OUTSIDE DIAMETER: 121 MM; LENGTH: 260 MM; MATERIAL: PB1-C; SUPPL P/N: M27929 P-4; DRAWING NO: 4SA2754P REV 1; MD/TR/8000201/C REV 1; REFERENCE NO: M27929; SULZER, FOR MATHER AND PLATT TYPE 10/12 EME MEDIVANE	5	EA
1270	0044196	BUSH, TAPER LOCK: BORE DIAMETER: 55 MM; SERIES: 2517; MATERIAL: STL; REFERENCE NO: 2517; KEYWAY: 16MM WD, 4.3MM DP, 70MM OD AT LARGE END OF TAPER	15	EA
1280	0045636	SLEEVE, SHAFT: TYPE: PUMP; REFERENCE NO: G075D21; FOR USE ON WARMAN 12/10G-AH METAL LINED EXPELLER TYPE	5	EA
1290	0045788	BEARING, SLEEVE: TYPE: JOURNAL; INSIDE DIAMETER: 260 MM; OUTSIDE DIAMETER: 278 MM; LENGTH: 370 MM; MATERIAL: STL; SUPPL P/N: G20; DRAWING NO: 9-104 609 629 REV 1; PUMP UNITS 4-6, PUMP TYPE: NPV 151, ITEMS TO BE PACKED IN WOODEN BOX, ITEMS TO BE STAMPED WITH PUMP	4	EA
1300	0048196	BUSH, TAPER LOCK: BORE DIAMETER: 100 MM; SERIES: 4040; MATERIAL: STL; SUPPLIER NOTE: THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED	5	EA

1310	0048491	SLEEVE, SHAFT: TYPE: PUMP DE; INSIDE DIAMETER: 135 MM; OUTSIDE DIAMETER: 189.5 MM; LENGTH: 350 MM; MATERIAL: STL; GRADE: M; SPECIFICATION: ISO 9001; SUPPL P/N: 31.24; MODEL NO: HPTPK43; REFERENCE NO: 104-137-426-001; FOR USE ON SULZER FEED PUMP	5	EA
1320	0048886	SLEEVE, SHAFT: INSIDE DIAMETER: 38 MM; OUTSIDE DIAMETER: 49 MM; LENGTH: 110 MM; MATERIAL: BRZ; KSB PUMP 5	5	EA
1330	0048978	SLEEVE, SHAFT: TYPE: DISTANCE; INSIDE DIAMETER: 215 MM; OUTSIDE DIAMETER: 250 MM; LENGTH: 310 MM; MATERIAL: STAINLESS STEEL; GRADE: 316; DRAWING NO: 9- 410.609.629 REV 1; LOWER, FOR USE ON SULZER CW PUMP; TYPE: NPV 151; FOR USE ON DUVHA UNITS 1 TO 4	5	EA
1340	0049057	BEARING, SLEEVE: TYPE: JOURNAL; INSIDE DIAMETER: 190 MM; OUTSIDE DIAMETER: 355 MM; LENGTH: 388 MM; MATERIAL: STL; DRAWING NO: 9- 104.609.629 REV 1; REFERENCE NO: G2; UPPER; FOR USE ON SULZER CW PUMP; TYPE NPV 151; FOR USE ON DUVHA UNITS 1-4; ITEMS TO BE PACKED IN WOODEN BOX, ITEMS TO BE WITH PUMP TYPE SULZER PUMPS DIVISION	12	EA
1350	0049166	SLEEVE, SHAFT: TYPE: PUMP; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 105 MM; LENGTH: 360 MM; MATERIAL: BRZ; SUPPL P/N: 12/14 DESC; DRAWING NO: 76- 04611JY REV 1; FOR APE 12/14 DESC	10	EA
1360	0053139	BEARING, SLEEVE: TYPE: SPLIT BUSH; INSIDE DIAMETER: 60 MM; OUTSIDE DIAMETER: 63 MM; ITEM 14.5; FOR LURGI PRECIPS UNIT 4-6	300	EA

1370	0070371	SLEEVE: TYPE: DISTANCE; SUPPL P/N: 103.155.869.001; FOR USE ON SULZER HP BYPASS VALVE ARS125	5	EA
1380	0078178	SLEEVE, ADAPTOR: TYPE: TAPER; SHAFT SIZE: 75 MM; LENGTH: 82 MM; MATERIAL: STEEL; SUPPL P/N: H2317; SIZE 110 MM OD; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
1390	0113020	BUSH, TAPER LOCK: BORE DIAMETER: 28 MM; SERIES: 2517; MATERIAL: CI; SUPPLIER NOTE: THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED	5	EA
1400	0144504	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 125 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 30 MM; BLOCK SIZE: 420 MM; SUPPL P/N: 22528; REFERENCE NO: SNK 528	5	EA
1410	0186163	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 30 MM; ROW: SINGLE; SUPPL P/N: 6218-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	100	EA
1420	0216629	BEARING, SLEEVE: TYPE: JOURNAL; MATERIAL: WHITE METAL; DRAWING NO: 905X5289 REV 1; TURBINE NO 11, STYLE TILTING PADS, SHAFT SIZ: 254MM, FOR UNIT 2, TO FIT EX MAJUBA 7 ROTOR	5	EA
1430	0216630	BEARING, SLEEVE: TYPE: JOURNAL; MATERIAL: WHITE METAL; DRAWING NO: 905X5284 REV 1; TURBINE NO 12, STYLE TILTING PADS, SHAFT SIZE 203.2MM, FOR UNIT 2, TO FIT EX MAJUBA 7 ROTOR	5	EA

1440	0219366	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 4-1/2 IN; BOLT MOUNTING: 4; BOLT DIAMETER: M20; BLOCK SIZE: WD 220 X LG 419.1 X HT 238.1 MM; SHAFT HEIGHT: 120.65 MM; ROLLING ELEMENT: SPHERICAL; HOUSING MATERIAL: CI; SUPPL P/N: AMEP5408YF	400	EA
1450	0232671	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: DOUBLE SHIELD; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 25 MM; ROW: SINGLE; SUPPL P/N: 6309-2Z; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	11	EA
1460	0243950	BEARING, ROLLER: TYPE: TAPER; INSIDE DIAMETER: 152.4 MM; OUTSIDE DIAMETER: 307.975 MM; WIDTH: 88.9 MM; ROW: SINGLE; BORE SHAPE: CYLINDRICAL; CAGE MATERIAL: STL; SUPPL P/N: HH234010; HH234048; CUP WIDTH 66.675 MM, CONE WIDTH 93.662 MM	5	EA
1470	0541156	SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 35 MM; LENGTH: 58 MM; MATERIAL: STEEL; REFERENCE NO: H308; WITH LOCKNUT AND LOCKING DEVICE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	5	EA
1480	0552726	SLEEVE, ADAPTOR: TYPE: ASH CRUSHER; SHAFT SIZE: 63.5 MM; LENGTH: 56 MM; MATERIAL: STAINLESS STEEL; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	60	EA

1490	0552727	BUSH, TAPER LOCK: BORE DIAMETER: 63.5 MM; SERIES: 3030; MATERIAL: CAST IRON; FOR USE ON ASH CRUSHER SHAFT	12	EA
1500	0552730	BUSH, TAPER LOCK: BORE DIAMETER: 140 MM; SERIES: 6050; MATERIAL: CAST IRON; FOR ASH PUMP	12	EA
1510	0568753	SLEEVE, COUPLING: TYPE: LP1/LP2; DIMENSIONS: LG 220 MM; MATERIAL: STL; SPECIFICATION: BS970817M40T; MANUF P/N: H6420; DRAWING NO: H4794 REV 0; MAIN TURBINE; ITEM TO BE PACKED AND RUST PROTECTIVE COATED FOR STORAGE; PILGRIM BRAND ONLY	22	EA
1520	0571540	SLEEVE, COUPLING: TYPE: LP2 GEN; DIMENSIONS: LG 220 MM; MATERIAL: STL; SPECIFICATION: BS 970817 M40 "T"; MANUF P/N: H6420; DRAWING NO: H4795 REV 0; MAIN TURBINE; ITEM TO BE PACKED AND RUST PROTECTED FOR STORAGE	22	EA
1530	0576075	SLEEVE, SHAFT: TYPE: UPPER PUMP; INSIDE DIAMETER: 258 MM; OUTSIDE DIAMETER: 384 MM; LENGTH: 390 MM; MATERIAL: ALUMINIUM; GRADE: LM4; MANUF P/N: 7709505069ZZ; DRAWING NO: 7709-7050 REV 0; ITEM 69; FOR CW TYPE APE 1600MM CONCRETE VOLUTE; TO BE PACKED IN WOODEN BOX; ITEM TO BE SPAMPED	12	EA
1540	0587648	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 45 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M12; BLOCK SIZE: WD 60 X LG 205 X HT 115 MM; ROLLING ELEMENT: ROLLER SPHERICAL; HOUSING MATERIAL: STL; REFERENCE NO: SNH 510	15	EA

1560	0587649	BEARING, PILLOW BLOCK: INSIDE DIAMETER: 60 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M12; BLOCK SIZE: WD 60 X LG 205 X HT 110 MM; ROLLING ELEMENT: ROLLER SPHERICAL; REFERENCE NO: SNH 508	5	EA
1570	0606297	BEARING: TYPE: PA FAN; INSIDE DIAMETER: 178.021 MM; OUTSIDE DIAMETER: 209.611 MM; WIDTH: 171.45 MM; MATERIAL: BS 970 GR 070M20; REFERENCE NO: D2891; SIROCCO PRESSURE FED	5	EA
1580	0610959	BUSH, TAPER LOCK: BORE DIAMETER: 75 MM; SERIES: 4030; MATERIAL: CAST IRON; FOR ASH PLANT	5	EA
1590	0611431	BUSH, TAPER LOCK: BORE DIAMETER: 100 MM; SERIES: 4030; MATERIAL: CAST IRON	16	EA
1600	0611432	BUSH, TAPER LOCK: BORE DIAMETER: 65 MM; SERIES: 4030; MATERIAL: CAST IRON	10	EA
1610	0611433	BUSH, TAPER LOCK: BORE DIAMETER: 80 MM; SERIES: 4030; MATERIAL: CAST IRON	10	EA
1620	0621229	BUSH, TAPER LOCK: BORE DIAMETER: 38 MM; SERIES: 2012; MATERIAL: CAST IRON; OD 120.7 X THK 31 MM; KEYWAY 10 X 3 MM	10	EA
1630	0629989	BUSH, TAPER LOCK: BORE DIAMETER: 125 MM; SERIES: 6050; MATERIAL: STL	10	EA
1640	0636043	BEARING, SLEEVE: TYPE: NO 5 JOURNAL; INSIDE DIAMETER: 170 MM; OUTSIDE DIAMETER: 210 MM; LENGTH: 130 MM; MATERIAL: WHITE METAL; MANUF P/N: 840415410; DRAWING NO: 3623-7009 PART 060/080 REV 0; USE ON VOITH GEARBOX MODEL R110KGS BEARING NO 5 ON SECONDARY SHAFT	15	EA

1650	0636044	BEARING, SLEEVE: TYPE: NO 4 JOURNAL; INSIDE DIAMETER: 170 MM; OUTSIDE DIAMETER: 210 MM; LENGTH: 170 MM; MATERIAL: WHITE METAL; MANUF P/N: 840415400; DRAWING NO: 3623-7009 PART 060/050 REV 0; USE ON VOITH GEARBOX MODEL NUMBER R110KGS BEARING NO 4 ON PRIMARY SHAFT	10	EA
1660	0636045	BEARING, SLEEVE: TYPE: NO 1 AND 2 JOURNAL; INSIDE DIAMETER: 220 MM; OUTSIDE DIAMETER: 260 MM; LENGTH: 210 MM; MATERIAL: WHITE METAL; MANUF P/N: 540344160; DRAWING NO: 3623-6843 PART 060/010 REV 0; USE ON VOITH GEARBOX MODEL NUMBER R110KGS BEARINGS NO 1 AND 2 ON INPUT SHAFT	18	EA
1670	0636046	BEARING, SLEEVE: TYPE: NO 6 JOURNAL; INSIDE DIAMETER: 170 MM; OUTSIDE DIAMETER: 210 MM; LENGTH: 130 MM; MATERIAL: WHITE METAL; MANUF P/N: 540312960; DRAWING NO: 3623-7009 PART 060/090 REV 0; USE ON VOITH GEARBOX MODEL NUMBER R110KGS BEARING NO 6 ON SECONDARY SHAFT	12	EA

1680	0644807	BEARING, SLEEVE: TYPE: NO 7 BFPT STEAM END; INSIDE DIAMETER: 176.44 UNDERSIZE MM; OUTSIDE DIAMETER: 222.25 MM; LENGTH: 88.9 MM; MATERIAL: WHITE METAL PS 20/018; SPECIFICATION: BS 4360 GR 43A; MANUF P/N: 610(A1)10432; TOP AND BOTTOM HALF WHITE METAL SHELLS SUPPLIED AS AN ASSEMBLY; LEMON BORE DESIGN BEARING; BEARING TO BE SUPPLIED UNDERSIZE AND FINAL MACHINING TO BE DONE FREE OF CHARGE UPTON DETERMINATION OF SIZE REQUIRED AT THAT TIME, THIS SIZE WITH BE SUPPLIED BY SITE ENGINEERING; DIMENSION CHECK SHEET; NDE AND BONDING CERTIFICATE TO BE SUPPLIED WITH DELIVERED PRODUCT	12	EA
1690	0676159	BUSH, TAPER LOCK: BORE DIAMETER: 115 MM; SERIES: 6050; MATERIAL: CAST IRON; MATERIAL CERTIFICATE TO BE SUPPLIED WITH ITEM	5	EA
1700	0706741	BEARING, BALL: TYPE: ANGULAR CONTACT; STYLE: OPEN; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 17 MM; ROW: SINGLE; MANUF P/N: 7305-B-TVP-UA; STATOR WATER PUMP; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION NUMBER (IF APPLICABLE).	12	EA

1710	0030488	BEARING, BALL: TYPE: DEEP GROOVE; STYLE: OPEN; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 17 MM; ROW: SINGLE; SUPPL P/N: 6305C3; ONLY SKF/NTN/NSK/RHP/KOYO ACCEPTABLE; VENDORS ARE RESPONSIBLE FOR ENSURING THAT THEY ARE PERFORMING AGAINST THE CORRECT DRAWING REVISION.	10	EA
------	---------	---	----	----







































